
Subject: a question on correct structure setting for EASE2 Grid in write_tiff

Posted by [yinghui Liu](#) on Tue, 01 Nov 2016 16:53:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

Dear All,

I have a question on write_tiff using IDL and can not solve it. I am writing to you to ask for your help.

I am re-mapping the data on EASE2 Grid, using a .gpd file as the following;

```
Map Projection:      Azimuthal Equal-Area (ellipsoid)
Map Reference Latitude:  90.0
Map Reference Longitude: 0.0
Map Rotation:         0.0
Map Equatorial Radius:  6378137.0 ; wgs84
Map Eccentricity:      0.081819190843 ; wgs84
Map Origin X:         -4512000. ; meters -1*9024*1000/2
Map Origin Y:         4512000. ; meters 9024*1000/2
Grid Map Origin Column: -0.5
Grid Map Origin Row:   -0.5
Grid Map Units per Cell: 1000. ; meters
Grid Width:           9024
Grid Height:          9024
```

This gpd file is adapted from a .gpd file from NSIDC, which covering the whole North Hemisphere.

; 1 km Northern Hemisphere EASE-Grid-2.0 grid parameter definition (nested in 36, 9 and 3 km gpd).

; This projection uses the WGS84 ellipsoid.

; The pole is exactly at the intersection of the middle 4 cells.

; The left/right/top/bottom latitude is 0.127234 degrees North

; (the equator goes just outside the edges of the grid coverage along the sides)

```
Map Projection:      Azimuthal Equal-Area (ellipsoid)
Map Reference Latitude:  90.0
Map Reference Longitude: 0.0
Map Rotation:         0.0
Map Equatorial Radius:  6378137.0 ; wgs84
Map Eccentricity:      0.081819190843 ; wgs84
Map Origin X:         -9000000. ; meters
Map Origin Y:         9000000. ; meters
Grid Map Origin Column: -0.5
Grid Map Origin Row:   -0.5
Grid Map Units per Cell: 1000. ; meters
Grid Width:           18000
Grid Height:          18000
```

After remapping, I want to write the data to GeoTIFF using IDL. The test IDL code I am using is as the following,

```
pro test
```

```
d= fltarr(9024,9024)
```

```
d(3000:6000,3000:6000) = 15.
```

```
d(6000:6500,6000:6500)=25.
```

```
g_tags = { ModelPixelScaleTag:[1000.d, 1000.d, 0d], $  
ModelTiepointTag:[-0.5d,-0.5d,0d,-4512000.d,4512000.d,0d], $  
  GTModelTypeGeoKey: 1s, $  
  GTRasterTypeGeoKey: 1s, $  
  GeographicTypeGeoKey: 4326s, $  
  ;ProjFalseEastingGeoKey: 0d, $  
  ;ProjFalseNorthingGeoKey: 0d, $  
  ProjCenterLongGeoKey: 0d, $  
  ProjCenterLatGeoKey: 90d, $  
  ;ProjCenterEastingGeoKey: 4511.5d, $  
  ;ProjCenterNorthingGeoKey: 4511.5d, $  
  ProjCoordTransGeoKey: 10s, $  
  ProjLinearUnitsGeoKey: 9001s $  
}
```

```
write_tiff,'test.tif',d,/float,geotiff=g_tags
```

```
end
```

It does not work at all, and can not generate a GeoTIFF file. I have been reading the GeoTIFF specification for a couple of weeks, but still have no clue what the correct setting for the g_tags is.

I am wondering if you could help me on correctly writing the test data in a tiff file?

Thanks very much in advance for your time.

Yinghui Liu
