
Subject: Re: Object Funkiness

Posted by [Phil Williams](#) on Fri, 01 Aug 1997 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

J.D. Smith wrote:

```
>
> J.D. Smith wrote:
>>
>> OK OOP experts. Here's a conundrum...
>>
>> here's a procedure to test dynamic binding of methods in IDL...
>>
>> pro testdb
>>   a=obj_new('eeke','a')
>>   b=obj_new('eeke','b')
>>   list=[a,b]
>>   ran=fix(randomu(sd) ge .5)
>>   list[ran]->Message, ran, 1-ran
>>   obj_destroy,list
>>   return
>> end
>>
>> and the file eek__define.pro contains:
>>
>> pro eeke::Message, ran, ran2
>>   print,self.val,' random: ',ran, ran2
>>   return
>> end
>> function eeke::Init,val
>>   self.val=val
>>   return,1
>> end
>> pro eeke__define
~~~~~
```

The __define method should be a FUNCTION. I'm sure once this is done everything should work fine.

```
>>   struct={eeke,val:"}
>>   return
>> end
>>
```

phil

```
-- ****
```

Phil Williams, Ph.D.
Research Instructor

Children's Hospital Medical Center "One man gathers what
Imaging Research Center another man spills..."
3333 Burnet Ave. -The Grateful Dead
Cincinnati, OH 45229
email: williams@irc.chmcc.org
URL: <http://scuttle.chmcc.org/~williams/>
