

---

Subject: Re: Save and Common Blocks

Posted by [davidf](#) on Fri, 12 Sep 1997 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Daniel Williams writes:

> Although the documentation for IDL's 'save' procedure claims that it  
> keeps comon blocks, I find that when I resore a session, the common  
> blocks are not present. Is this an error on my part, or does 'save'  
> really not store the common blocks?  
>  
> And yes, I do use the '/all' option to 'save'.

The way the common blocks are restored might be confusing you.  
For example, if I create a common block named DATA like this:

```
IDL> Common DATA, c, d
IDL> c = 5
IDL> d = 10
IDL> Save, /All, File='junk.sav'
```

Then when that common block is restored, what I see are the  
variables c and d, but they have the DATA name in parentheses,  
like this:

```
IDL> Restore, 'junk.sav'
IDL> Help
C (DATA)      INT      =      5
D (DATA)      INT      =     10
```

If I declare the DATA common block in an IDL procedure or  
function, I now have access to those two variables.

Cheers,

David

---

David Fanning, Ph.D.  
Fanning Software Consulting  
Customizable IDL Programming Courses  
Phone: 970-221-0438 E-Mail: [davidf@dfanning.com](mailto:davidf@dfanning.com)  
Coyote's Guide to IDL Programming: <http://www.dfanning.com>

---