
Subject: Re: Xwindow, TVimage and PostScript fonts
Posted by [davidf](#) on Thu, 19 Aug 1999 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Roy E. Hansen (roy.hansen@triad.no) writes:

- > I know this post should be sent directly to David Fanning
- > but he answers all the questions on this newsgroup anyhow :-)

I really need to get a life. :-)

I'm making a vow to post only once a week, and
then only if someone really riles me up about color. :-)

Before I go....

- > I have been playing around with David Fanning's example programs to
- > see if I can snatch a few ideas for my next project. BTW, Xwindow is a
- > fantastic program.
- >
- > One thing that I need is a plot of an image with axis and a colorbar that
- > easily can be printed to high quality PostScript.
- > Easy, I thought. Use xwindow, tvimage and colorbar as in the following
- > example:
- >
- > ;----- Start hurrah.pro -----
- >
- > PRO hurrah, image, Xxx=xxx, Yyy=yyy
- >
- > erase
- > pos = [0.05, 0.1, 0.8, 0.9]
- > tvimage, image, position=pos
- > !p.position = pos
- > plot, xxx, yyy, /xsty, /ysty, /nodata, /noerase
- >
- > colorbar, position=[0.85, 0.1, 0.95, 0.9], /VERT, /RIGHT
- >
- > END ;----- hurrah.pro -----
- >
- >
- > image = hanning(64) # hanning(64)
- > xwindow, 'hurrah', image*200, Xxx=[0,1], Yyy=[0,1], /Out
- >
- > END ;----- main.pro -----
- >
- > This works except one detail:
- > How do I get readable fonts (i.e. PostScript and NOT Hershey fonts) on the PS output?

Well, before I answer this question for you, let me point out that your ERASE command is already going to hurt you in PostScript output, since that will force the output onto the *next* page. You will get a blank page every time you get output. Think of the trees!

So, I would fix both of these problems by writing your HURRAH program like this:

```
PRO hurrah, image, Xxx=xxx, Yyy=yyy

  IF !D.Name EQ 'PS' OR !D.Name EQ 'PRINTER' THEN BEGIN
    font = 0 ; or 1 if you want True-Type fonts
  ENDIF ELSE BEGIN
    erase
      font = -1
    ENDELSE
    pos = [0.05, 0.1, 0.8, 0.9]
    tvimage, image, position=pos
    !p.position = pos
    plot, xxx, yyy, /xsty, /ysty, /nodata, /noerase, FONT=font

    colorbar, position=[0.85, 0.1, 0.95, 0.9], /VERT, /RIGHT, FONT=font

  END ;----- hurrah.pro -----
```

By the way, I just a moment ago got an e-mail from David Ritscher (david.ritscher@bigfoot.com) who has sent me a new XWINDOW program that has implemented a multiple-command-line functionality with my LinkedList object. I haven't even had a chance to look at it yet, but we may make it available for people to fool around with. I've been working on a similar capability (also using that incredibly useful LINKEDLIST object) in my little free time.

So, if you liked XWINDOW, just hang on a bit. Something better may be just around the corner. :-)

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting

Phone: 970-221-0438 E-Mail: davidf@dfanning.com

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>

Toll-Free IDL Book Orders: 1-888-461-0155
