
Subject: Re: Efficient IDL programming

Posted by [deutsch](#) on Fri, 03 Dec 1993 22:49:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

In article 86221@yuma.ACNS.ColoState.EDU, dean@phobos.cira.colostate.edu writes:

>
> I would like to thank everybody who responded to my request for help in
> "extracting bits from bytes". Below is a test PRO that I made to read in
> the graphic file. It reads, converts, expands, enhances, and reverses my
> file (from (512,64) to (512,512)) in about 30 seconds.
>
> I started with DEC2BIN.PRO posted by Bill Thompson. This worked, but it
> took awhile to go thru 32,768 calculations. Both Chris Chase and Dr. Marty
> Ryba suggested "masks" which speed things up considerably.
>
> I just wanted to check to see if anyone would know if I can illminated
> the FOR DO BEGIN loops to make this PRO a little more efficient.
>
> Thanks again guys,
>
> Kelly Dean

Try using the following example to vectorize your code. I think this should be much more efficient at decoding your images since it contains no loops. Note that I'm using an orientation where the bits are encoded into bytes in the X direction; you seem to have done something a little differently, so my example may need to be modified for encoding direction.

```
xsize=512  
ysize=512
```

```
input_img=byte(indgen(xsize/8,ysize)) ; sample input image
```

```
tmp=lindgen(1.0*ysize*xsize) ; 1.0 to avoid int wrap  
tmp2=tmp-(tmp/8)*8 ; create mask input  
tmp3=reform(tmp2,xsize,ysize) ; reform to correct dim's  
mask=2L^tmp3 ; create bitmask
```

```
work=congrid(inimg,xsize,ysize) ; replicate each byte 8 times
```

```
outimg=(work and mask) ne 0 ; perform the mask
```

```
outimg=byte(outimg)*244b ; enhance value
```

```
end
```

I hope this works.. I'd be interested in hearing how much faster this works..
I get the conversion to run in about 5 seconds on SPARC 2.

cheers,
Eric

Eric Deutsch	Email: deutsch@astro.washington.edu
Department of Astronomy FM-20	Voice: (206) 543-1979
University of Washington	FAX: (206) 685-0403
Seattle, WA 98195	Johnson Hall, Room 226

```
>
> =====
=====
> pro test
>   head = bytarr(56)
>   premature_EOF = 1
>   ON_IOERROR, SHORT_GRF
> ;
> ;   Read "in house" graphic file.
> ;
>   OPENR, unit, 'dtopo:gms512.grf', /GET_LUN
>   READU, unit, head
>   chead = STRING(head)
>   ck_imx = STRMID(chead,0,6)
> ;
> ;   Verify that it is an IMX graphic file before proceeding
> ;
>   IF ( ck_imx EQ '%IMAGE' ) THEN BEGIN $
>       head_lgth = STRMID(chead,28,7)
>       IF ( head_lgth GT 56 ) THEN BEGIN $
>           rem_head = bytarr(head_lgth-56)
>           READU, unit, rem_head
>       ENDIF
>       xsize = strmid(chead,36,6)
>       ysize = strmid(chead,43,6)
>       imxgrf = bytarr(xsize,ysize/8)
>       graphic = bytarr(xsize,ysize)
>       readu, unit, imxgrf
>       premature_EOF = 0
>       SHORT_GRF: IF premature_EOF THEN PRINT, 'Short graphic'
>       close, unit
> ;
> ;   Create mask.
> ;
>       tmp = lindgen(8)
>       mask = 2L^tmp
> ;
> ;   Expand array(xsize,ysize/8) to array(xsize,ysize).
```

```

> ;
>     yyy = 0
>     FOR y = 0,(ysize/8)-1 DO BEGIN
>         xxx = 0
>         FOR x = 0,xsize-1 DO BEGIN
>             IF ( xxx EQ xsize ) THEN BEGIN $
>                 xxx = 0
>                 yyy = yyy + 1
>             ENDIF
> ;     Perform the conversion ( Dr. Marty Ryba (MIT) suggestion).
>         graphic(xxx,yyy) = (imxgrf(x,y) and mask) ne 0
>         xxx = xxx + 8
>     ENDFOR
>     yyy = yyy + 1
> ENDFOR
> ;
> ;     Enhance value so you can see it and reverse image, then display.
> ;
>         graphic(Where(graphic EQ 001b )) = 244b
>         graphic = rotate(graphic,7) ; Transpose 270 deg, (Xo,-Yo)
>         tv, graphic
>     ENDIF
> END

```
