
Subject: default_button

Posted by [pei zeng](#) on Mon, 17 Apr 2000 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have a dialog with an OK button which closes the dialog. I would like it to be a default button, so I can use "RETURN"/"ENTER" key or click using mouse.

After I run the code, the OK button looks like a normal button(not highlighted), but it functions like a default button(enter key works). What is wrong?

The code will look something like this:

```
PRO default_button, GROUP_LEADER=group
```

```
tlb=WIDGET_BASE(COLUMN=1, TITLE="Default Button", $
  TLB_SIZE_EVENTS=0, XPAD=0, YPAD=0, /FLOATING, $
  /TLB_KILL_REQUEST_EVENTS, GROUP_LEADER=group,/MODAL)
```

```
;  
; some other widget
```

```
;  
wOK=WIDGET_BUTTON(tlb,UVALUE='OK', VALUE='OK')
```

```
;  
; skip other codes
```

```
;  
; realize the widget
```

```
WIDGET_CONTROL, tlb, /REALIZE
```

```
; set default button
```

```
WIDGET_CONTROL, tlb, DEFAULT_BUTTON=wOK
```

```
;run program
```

```
XMANAGER, 'default_button', tlb
```

```
END
```
