
Subject: Date axis in object graphics (IDL 5.3)

Posted by [George Constantinides](#) on Mon, 31 Jul 2000 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi all IDL gurus,

This should be an easy one for you.

I am using LABEL_DATE to produce a time axis in object graphics as follows:

```
;..... some code ....
dummy = Label_Date(Date_Format = '%D-%M!C%H',Offset=start_date)
;..... some more code ....
xAxis = Obj_New("IDLgrAxis", 0, Color=[255,255,0], Ticklen=0.025, $
Minor=4, Range=xrange, Title=xtitle, TickDir=1, $
TickFormat = 'Label_Date',Location=[0, 0.2 ,0])
;.....
```

I expect the HOURS to appear below the date. This works in direct graphics but in object graphics it does not understand !C as a directive and instead displays it as a literal.

Am I going something wrong, or have I discovered bag number: 4527

Regards

GC

Subject: Re: Date axis in object graphics (IDL 5.3)

Posted by [Mark Hadfield](#) on Tue, 01 Aug 2000 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

"George Constantinides" <gconstantinides@mhl.nsw.gov.au> wrote in message news:39851C57.62251B78@mhl.nsw.gov.au...

> This should be an easy one for you.

> I am using LABEL_DATE to produce a time axis in object graphics as

> follows:

```
>
> ;..... some code ....
> dummy = Label_Date(Date_Format = '%D-%M!C%H',Offset=start_date)
> ;..... some more code ....
> xAxis = Obj_New("IDLgrAxis", 0, Color=[255,255,0], Ticklen=0.025, $
>
> Minor=4, Range=xrange, Title=xtitle, TickDir=1, $
> TickFormat = 'Label_Date',Location=[0, 0.2 ,0])
> ;.....
```

>
> I expect the HOURS to appear below the date. This works in direct
> graphics but in object graphics it does not understand !C as a directive
> and instead displays it as a literal.
>
> Am I going something wrong, or have I discovered bag number: 4527

No you're not doing anything wrong. Text objects do not recognise !C, although they do recognise other formatting codes if create with the ENABLE_FORMATTING property set.

I don't think it's really a bug (or a bag), just a limitation.

P.S. Ticktext objects created by an IDLgrAxis have ENABLE_FORMATTING turned off. To turn it on you can do:

```
oaxis->GetProperty, TICKTEXT=ticktext
for i=0,n_elements(ticktext)-1 do $
  if obj_valid(ticktext[i]) then $
    ticktext[i]->SetProperty, /ENABLE_FORMATTING
```

Mark Hadfield
m.hadfield@niwa.cri.nz <http://katipo.niwa.cri.nz/~hadfield/>
National Institute for Water and Atmospheric Research
PO Box 14-901, Wellington, New Zealand
