Subject: Re: Large File Plotting

Posted by davidf on Thu, 28 Sep 2000 07:00:00 GMT

View Forum Message <> Reply to Message

Pavel Romashkin (promashkin@cmdl.noaa.gov) writes:

- >> What is needed is
- >> something that can detect file size and
- >> only display to the pixel resolution of the
- >> screen.

>

- > I think this is exactly what you need. At 1024 x 768, a monitor is
- > capable of producing not better than 85 points per inch. Resample your
- > large array to the desired resolution and plot it. PLOT will do this
- > anyway (on a visual level), but a lot less efficiently.

>

- > If the axis you plot against is 5" long, then the maximum number of
- > points you'll be able to see is < 500. Use CONGRID for plotting:

>

> plot, congrid(a, 500)

>

> works very fast.

Another suggestion along this line is to use the NSUM keyword on the PLOT command. This indicates how many adjacent points IDL is to average in order to reduce the number of plotted points.

If you are in to widget programming, I think you should also be able to write something along the lines of ZPLOT on my web page that allows you to "zoom" into your data at different "resolutions". Some combination of resampling the actual data points and restricting the independent data range should work. I don't think this would be too hard to write.

Cheers.

David

--

David Fanning, Ph.D.

Fanning Software Consulting

Phone: 970-221-0438 E-Mail: davidf@dfanning.com

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: Large File Plotting Posted by promashkin on Thu, 28 Sep 2000 07:00:00 GMT

View Forum Message <> Reply to Message

- > What is needed is
- > something that can detect file size and
- > only display to the pixel resolution of the
- > screen.

I think this is exactly what you need. At 1024 x 768, a monitor is capable of producing not better than 85 points per inch. Resample your large array to the desired resolution and plot it. PLOT will do this anyway (on a visual level), but a lot less efficiently.

If the axis you plot against is 5" long, then the maximum number of points you'll be able to see is < 500. Use CONGRID for plotting:

plot, congrid(a, 500)

works very fast. Cheers, Pavel

Subject: Re: Large File Plotting Posted by Mark Hadfield on Thu, 28 Sep 2000 20:52:11 GMT View Forum Message <> Reply to Message

"Mark Przeslawski" < MarkPrzeslawski@ncodeinc.com> wrote in message news:st78offfa3gm3b@corp.supernews.com...

- > Does anyone have an example of plotting
- > very large time history data files. I tried
- > creating a 1 million point file and it plotted
- > okay. I tried a 10 million point file with
- > various plotting routines and it hung my
- > Windows 2000 machine (PIII, 700MHz,
- > 256Mb RAM). I tried plot, live plot,
- > and some of the covote plotting
- > routines to no avail.

That's interesting. On my machine (not too different from yours: NT 4.0, PII, 400 MHZ, 256 MB RAM) I find that if I can create the array I can plot it:

IDL> plot, findgen(1000000)
IDL> plot, findgen(10000000)
IDL> plot, findgen(20000000)
IDL> plot, findgen(50000000)

% Unable to allocate memory: to make array.

% Execution halted at: \$MAIN\$

Of course, speed is an issue: about 3 s per million floating-point values on my machine.

- > ... What is needed is
- > something that can detect file size and
- > only display to the pixel resolution of the
- > screen.

That's pretty much what the Direct Graphics plotting commands do. They just write pixels to the screen as they go; they don't keep a copy of the data or the plotting primitives. This is why IDL Direct Graphics is so good for plotting really large datasets, and why it is so frustratingly limited in some ways.

When plotting such large datasets you should avoid Object Graphics (including LIVE PLOT) and also Direct Graphics wrapper systems (like David's XWINDOW) that copy the data. You will also need to be careful about processing the data to avoid redundant copies, e.g. this generates two 10000000-element arrays

a = findgen(10000000)

b = a

but this generates only one

a = findgen(10000000)

b = temporary(a)

People other than me are more competent to advise you on handling large datasets.

Mark Hadfield m.hadfield@niwa.cri.nz http://katipo.niwa.cri.nz/~hadfield/ National Institute for Water and Atmospheric Research PO Box 14-901, Wellington, New Zealand

Hi! I'm a .signature virus! copy me into your .signature file to help me spread!