
Subject: Re: New IDL User Questions

Posted by [John-David T. Smith](#) on Tue, 08 May 2001 20:01:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

John Piccirillo wrote:

>
> Hello,
>
> I'm new to IDL, but not new to programming. I have
> the IDL manuals and Dr. Fanning's excellent book, nevertheless,
> I have a few basic questions:

This is a perfectly natural phenomenon. I'd write to David asking him to expand his book to cover the answers to every possible question. And also add his favorite recipes. And secrets of an effective backswing.

>
> 1. Editor Screen
> a. Is there a way to make the Editor full screen or extend
> over some of the other windows? Using resize doesn't do it.
> Does everyone confine themselves to this small window on their
> code?
> b. My scrolling mouse will scroll in the Output Log and Variable
> Watch
> windows, but not in the Editor Window. Que pasa?

One word. IDLWAVE.

<http://www.strw.leidenuniv.nl/~dominik/Tools/idlwave/>

> 2. Array Operations - Not being used to IDL type of array operations,
> is there a simpler way to do the following?
> a.
> For I = 0, 199 Do Begin
> For J = 0, 84 Do Begin
> If (ImageMask[I,J] EQ 1) Then ImageROI[I,J,*] =
> ImageS[I,J,*]
> Else ImageROI[I,J,*] = 0
> EndFor
> EndFor
> I thought of using the WHERE function as in,
> ROI = Where(ImageMask EQ 1)
> but ImageROI[ROI] = ImageS{ROI} leaves out the third dimension.

Yes, there are many. Here is one:

```
IDL> imageroi=rebin(imagemask eq 0,200,84,nz)
```

assuming the full dimensions are 200x84xnz. Once IDL 5.5 comes out, you should also be able to use a single vector of dimensions:

```
rebin(imagemask eq 0, [size(imagemask,/DIMENSIONS),nz])
```

and so on. (Craig, they have committed to adding this overlooked feature).

```
>
>      b.      ;blow-up image X 9 For Screen Display
>      I don't use the EXPAND function because I don't want to interpolate
> the data.
```

Almost everyone (except RSI, apparently) has a nice image viewer routine which does this for you, based on your window size. I wrote my own myself long ago, but you'd be better off starting with one of theirs. Hint: they often start with "im" or "tv", or and in "disp". Hint2: rebin() is again your friend, with SAMPLE=1 set.

```
>
> 3. PLOT
>      I have a couple of plots I want on the same Y Scale, the larger of
> the two
> data sets. Presently, I use plot to generate the scale to !y.range, and
> then test
> the two ranges and re-plot, as in.
>
> Window, 0, Title = ' P Target; NPix = ' + string(Fix(NumOnes)), $
> XSize = 350, YSize = 350, XPos = 0, YPos = 0
> Plot, WavL, MeanPT, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1
> PTYRange = !y.crange
> Window, 1, Title = ' P BkGnd; NPix = ' + string(Fix(17000 - NumOnes)), $
> XSize = 350, YSize = 350, XPos = 0, YPos = 375
> Plot, WavL, MeanPB, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1
> PBYRange = !y.crange
> SPRange = Max([PTYRange[1], PBYRange[1]])
> MaxY = [0,SPRange]
>
> ; replot all with new, uniform Y scale
> Window, 0, Title = 'P Target; NPix = ' + string(Fix(NumOnes)), $
> XSize = 350, YSize = 375, XPos = 0, YPos = 0
> Plot, WavL, MeanPT, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1, YRange =
> MaxY
> Window, 1, Title = 'P BkGnd ; NPix = ' + string(Fix(17000 - NumOnes)), $
> XSize = 350, YSize = 350, XPos = 0, YPos = 375
> Plot, WavL, MeanPB, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1, YRange =
> MaxY
>
```

Examine that data itself, find the min/max you'd like, and then set them for plotting directly with YRANGE, not forgetting YSTYLE=1 if you want to force the *exact* range (note the use of the < and > operators... very handy):

```
yr=[min(b1)<min(b2),max(b1)>max(b2)]  
plot,a1,b1,YRANGE=yr,/YSTYLE  
plot,a2,b2,YRANGE=yr,/YSTYLE
```

Good luck,

JD

Subject: Re: New IDL User Questions

Posted by [Liam E. Gumley](#) on Wed, 09 May 2001 00:31:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

"John Piccirillo" <jpicciri@radiancetek.com> wrote in message
news:<f6WJ6.8403\$2B6.790502@e420r-chi2.usenetserver.com>...

```
> b. ;blow-up image X 9 For Screen Display  
> For j = 0,84 Do Begin  
>   For i = 0,199 Do Begin  
>     JImage[3*i,3*j] = ImageS[i,j,[4]]  
>     JImage[3*i,3*j+1] = ImageS[i,j,[4]]  
>     JImage[3*i,3*j+2] = ImageS[i,j,[4]]  
>     JImage[3*i+1,3*j] = ImageS[i,j,[4]]  
>     JImage[3*i+1,3*j+1] = ImageS[i,j,[4]]  
>     JImage[3*i+1,3*j+2] = ImageS[i,j,[4]]  
>     JImage[3*i+2,3*j] = ImageS[i,j,[4]]  
>     JImage[3*i+2,3*j+1] = ImageS[i,j,[4]]  
>     JImage[3*i+2,3*j+2] = ImageS[i,j,[4]]  
>   EndFor  
> EndFor  
>  
> I don't use the EXPAND function because I don't want to interpolate  
> the data.
```

Let IMDISP do the work:

<http://cimss.ssec.wisc.edu/~gumley/imdisp.html>

Cheers,

Liam.

<http://cimss.ssec.wisc.edu/~gumley/>

Subject: Re: New IDL User Questions

Posted by [Craig Markwardt](#) on Wed, 09 May 2001 03:30:15 GMT

[View Forum Message](#) <> [Reply to Message](#)

"John Piccirillo" <jpicciri@radiancetek.com> writes:

```
> 2. Array Operations - Not being used to IDL type of array operations,
>   is there a simpler way to do the following?
>   a.
>       For I = 0, 199 Do Begin
>           For J = 0, 84 Do Begin
>               If (ImageMask[I,J] EQ 1) Then ImageROI[I,J,*] =
> ImageS[I,J,*]
>               Else ImageROI[I,J,*] = 0
>           EndFor
>       EndFor
> I thought of using the WHERE function as in,
>   ROI = Where(ImageMask EQ 1)
>   but ImageROI[ROI] = ImageS{ROI} leaves out the third dimension.
```

JD may have been thinking of a different question here. I believe you want only a slight modification to your code:

```
ROI = Where(ImageMask EQ 1)
ImageROI[ROI,*] = ImageS[ROI,*]
```

This will include the third dimension.

```
>   b. ;blow-up image X 9 For Screen Display
>   For j = 0,84 Do Begin
>       For i = 0,199 Do Begin
>           JImage[3*i,3*j] = ImageS[i,j,[4]]
> ...
>       EndFor
>   EndFor
```

Liam plugged IMDISP so I will plug PLOTIMAGE on my web page. If you really just want to expand an image then it is very straightforward to use the REBIN function. Otherwise either Liam or my image display program will be quite easy.

```
JImage = rebin(ImageS[*,*], 200*3, 85*3, 1)
```

The extra "1" is because ImageS[*,*,4] is really a 200x85x1 array.

Craig

<http://cow.physics.wisc.edu/~craigm/idl/idl.html> (PLOTIMAGE is under Graphics)

--

Craig B. Markwardt, Ph.D. EMAIL: craigmnet@cow.physics.wisc.edu
Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response

Subject: Re: New IDL User Questions
Posted by [Craig Markwardt](#) on Wed, 09 May 2001 03:31:45 GMT
[View Forum Message](#) <> [Reply to Message](#)

JD Smith <jdsmith@astro.cornell.edu> writes:
> assuming the full dimensions are 200x84xnz. Once IDL 5.5 comes out, you
> should also be able to use a single vector of dimensions:
>
> `rebin(imagemask eq 0, [size(imagemask,/DIMENSIONS),nz])`
>
> and so on. (Craig, they have committed to adding this overlooked
> feature).

Cool!

Craig

--

Craig B. Markwardt, Ph.D. EMAIL: craigmnet@cow.physics.wisc.edu
Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response

Subject: Re: New IDL User Questions
Posted by [John Piccirillo](#) on Wed, 09 May 2001 17:05:29 GMT
[View Forum Message](#) <> [Reply to Message](#)

Thanks to all for the concise and helpful answers to my questions.
I appreciate the help.

John Piccirillo, Ph.D.

Radiance Technologies Inc.
Huntsville, AL 35816
jpicciri@radiancetech.com

John Piccirillo <jpicciri@radiancetech.com> wrote in message
news:f6WJ6.8403\$2B6.790502@e420r-chi2.usenetserver.com...

> Hello,
>
> I'm new to IDL, but not new to programming. I have
> the IDL manuals and Dr. Fanning's excellent book, nevertheless,
> I have a few basic questions:
>
> 1. Editor Screen
> a. Is there a way to make the Editor full screen or extend
> over some of the other windows? Using resize doesn't do it.
> Does everyone confine themselves to this small window on their
> code?
> b. My scrolling mouse will scroll in the Output Log and Variable
> Watch
> windows, but not in the Editor Window. Que pasa?
>
> 2. Array Operations - Not being used to IDL type of array operations,
> is there a simpler way to do the following?
> a.
> For I = 0, 199 Do Begin
> For J = 0, 84 Do Begin
> If (ImageMask[I,J] EQ 1) Then ImageROI[I,J,*] =
> ImageS[I,J,*]
> Else ImageROI[I,J,*] = 0
> EndFor
> EndFor
> I thought of using the WHERE function as in,
> ROI = Where(ImageMask EQ 1)
> but ImageROI[ROI] = ImageS{ROI} leaves out the third dimension.
>
> b. ;blow-up image X 9 For Screen Display
> For j = 0,84 Do Begin
> For i = 0,199 Do Begin
> JImage[3*i,3*j] = ImageS[i,j,[4]]
> JImage[3*i,3*j+1] = ImageS[i,j,[4]]
> JImage[3*i,3*j+2] = ImageS[i,j,[4]]
> JImage[3*i+1,3*j] = ImageS[i,j,[4]]
> JImage[3*i+1,3*j+1] = ImageS[i,j,[4]]
> JImage[3*i+1,3*j+2] = ImageS[i,j,[4]]
> JImage[3*i+2,3*j] = ImageS[i,j,[4]]
> JImage[3*i+2,3*j+1] = ImageS[i,j,[4]]
> JImage[3*i+2,3*j+2] = ImageS[i,j,[4]]

```

> EndFor
> EndFor
>
> I don't use the EXPAND function because I don't want to interpolate
> the data.
>
> 3. PLOT
> I have a couple of plots I want on the same Y Scale, the larger
of
> the two
> data sets. Presently, I use plot to generate the scale to !y.range, and
> then test
> the two ranges and re-plot, as in.
>
> Window, 0, Title = ' P Target; NPix = ' + string(Fix(NumOnes)), $
> XSize = 350, YSize = 350, XPos = 0, YPos = 0
> Plot, WavL, MeanPT, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1
> PTYRange = !y.crange
> Window, 1, Title = ' P BkGnd; NPix = ' + string(Fix(17000 - NumOnes)),
$
> XSize = 350, YSize = 350, XPos = 0, YPos = 375
> Plot, WavL, MeanPB, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1
> PBYRange = !y.crange
> SPRange = Max([PTYRange[1], PBYRange[1]])
> MaxY = [0,SPRange]
>
> ; replot all with new, uniform Y scale
> Window, 0, Title = 'P Target; NPix = ' + string(Fix(NumOnes)), $
> XSize = 350, YSize = 375, XPos = 0, YPos = 0
> Plot, WavL, MeanPT, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1, YRange =
> MaxY
> Window, 1, Title = 'P BkGnd ; NPix = ' + string(Fix(17000 - NumOnes)), $
> XSize = 350, YSize = 350, XPos = 0, YPos = 375
> Plot, WavL, MeanPB, PSYM = 2, TickLen = 1, XGrid = 1, YGrid = 1, YRange =
> MaxY
>
> this seems inefficient, what is a better way?
>
> Thanks,
>
> John Piccirillo
>
>
>
>

```

Subject: Re: New IDL User Questions

Posted by [Jaco van Gorkom](#) on Thu, 10 May 2001 15:05:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

JD Smith wrote in message <3AF85085.7E5696AD@astro.cornell.edu>...

> John Piccirillo wrote:

...

>> 1. Editor Screen

>> a. Is there a way to make the Editor full screen or extend
>> over some of the other windows? Using resize doesn't do it.
>> Does everyone confine themselves to this small window on
their

>> code?

>> b. My scrolling mouse will scroll in the Output Log and Variable

>> Watch

>> windows, but not in the Editor Window. Que pasa?

>

> One word. IDLWAVE.

>

> <http://www.strw.leidenuniv.nl/~dominik/Tools/idlwave/>

...

For those who know, or are prepared to learn, emacs. In the IDLDE it helps to use the 'multiple window' setting, or 'separate editor window' under

Preferences. This works on Unix, but somehow I cannot find how to do this in the Windows version...

Jaco
