
Subject: Re: Way to determine big/little endian?

Posted by [David Fanning](#) on Thu, 20 Sep 2001 04:36:25 GMT

[View Forum Message](#) <> [Reply to Message](#)

Mark Rivers (rivers@cars.uchicago.edu) writes:

> Is there a built-in way to determine if the machine IDL is running on is
> big-endian or little-endian? I

Here is an article on the subject, with a little snippet
of code to tell you where you are.

http://www.dfanning.com/tips/endian_machines.html

The code looks like this:

```
little_endian = (BYTE(1, 0, 1))[0]
IF (little_endian) THEN $
  Print, "I'm little endian." ELSE $
  Print, "I'm big endian."
```

Cheers,

David

--

David W. Fanning, Ph.D.

Fanning Software Consulting

Phone: 970-221-0438, E-mail: david@dfanning.com

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>

Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: Way to determine big/little endian?

Posted by [Craig Markwardt](#) on Thu, 20 Sep 2001 04:45:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

"Mark Rivers" <rivers@cars.uchicago.edu> writes:

> Is there a built-in way to determine if the machine IDL is running on is
> big-endian or little-endian? I would expect that there might be a field in
> !version, but there is not.
>
> Here is what I am doing to set the Boolean value "big_endian":
>
> ; If this is a big-endian machine swap the byte order
> ; I don't know of a built-in IDL test for endianness, do it ourselves
> t1 = 1

```
> t2 = 1
> byteorder, t2, /sswap, /swap_if_big_endian
> big_endian = (t1 ne t2)
> if (big_endian) then str = swap_endian(str)
>
>
> Is there a simpler way? It would be nice if swap_endian accepted the
> /swap_if_big_endian and /swap_if_little_endian keywords the way byteorder
> now does.
```

I use this code when I need to. It's pretty much the same as yours, but I think mine is just a bit cuter :-).

```
big_endian = (long(['01'xb,'02'xb,'03'xb,'04'xb],0,1))(0) EQ '01020304'xl
```

I presume you could make your own SWAP_ENDIAN-like function which computed this value, and then implemented the /SWAP_IF... keywords.

Cheers,
Craig

--

Craig B. Markwardt, Ph.D. EMAIL: craigmnet@cow.physics.wisc.edu
Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response

Subject: Re: Way to determine big/little endian?
Posted by [David Fanning](#) on Thu, 20 Sep 2001 05:02:32 GMT
[View Forum Message](#) <> [Reply to Message](#)

Craig Markwardt (craigmnet@cow.physics.wisc.edu) writes:

```
> I use this code when I need to. It's pretty much the same as yours,
> but I think mine is just a bit cuter :-).
>
> big_endian = (long(['01'xb,'02'xb,'03'xb,'04'xb],0,1))(0) EQ '01020304'xl
```

Gosh, now I'm *really* embarrassed about my simple little contribution. I think I only had two sets of nested parentheses. :-(

Cheers,

David

--

David W. Fanning, Ph.D.
Fanning Software Consulting
Phone: 970-221-0438, E-mail: david@dfanning.com
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: Way to determine big/little endian?
Posted by [Craig Markwardt](#) on Thu, 20 Sep 2001 13:38:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

David Fanning <david@dfanning.com> writes:

```
> Craig Markwardt (craigmnet@cow.physics.wisc.edu) writes:
>
>> I use this code when I need to. It's pretty much the same as yours,
>> but I think mine is just a bit cuter :-).
>>
>> big_endian = (long(['01'xb,'02'xb,'03'xb,'04'xb],0,1))(0) EQ '01020304'xl
>
> Gosh, now I'm *really* embarrassed about my simple little
> contribution. I think I only had two sets of nested
> parentheses. :-(
```

Round blades! Round blades! :-) Actually I only had two sets of nested parentheses as well. Sigh, I like your submission a little better. It captures the essence of the test a little better.

Craig

--

Craig B. Markwardt, Ph.D. EMAIL: craigmnet@cow.physics.wisc.edu
Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response
