
Subject: Re: log scale of data coloring of IDLgrVolume object, not the axes
Posted by [David Fanning](#) on Wed, 30 Jan 2002 16:38:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

Todd Bowers (tbowers0@yahoo.com) writes:

- > Ok, I think I've figured out the whole log axis thing to get an
- > IDLgrSurface axis to show log scale, its all about scaling the
- > xyzCoord_Conv property of the surface with the logged bounds of your
- > data.
- >
- > But, I'm having trouble carrying this over using log scale for the
- > coloring of an IDLgrVolume object and the associated Hcolorbar from
- > David F. (keeping the xyz axes linear, just logging the color ramp).
- > Could anyone help?

HColorbar isn't designed for log scales, of course, but I think it is just a matter of passing it a color palette of values that have been scaled by some kind of log function. For example:

```
r = BytScl(Findgen(256)^10e-2)
g = r
b = r
thePalette = Obj_New('IDLgrPalette', r, g, b)
theColorbar = Obj_New('HColorbar', Palette=thePalette)
```

Cheers,

David

--

David W. Fanning, Ph.D.
Fanning Software Consulting
Phone: 970-221-0438, E-mail: david@dfanning.com
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: log scale of data coloring of IDLgrVolume object, not the axes
Posted by [1](#) on Fri, 08 Feb 2002 16:49:14 GMT

[View Forum Message](#) <> [Reply to Message](#)

David Fanning <david@dfanning.com> wrote in message

- >
- > HColorbar isn't designed for log scales, of course,
- > but I think it is just a matter of passing it a
- > color palette of values that have been scaled by
- > some kind of log function. For example:

```

>
> r = BytScl(Findgen(256)^10e-2)
> g = r
> b = r
> thePalette = Obj_New('IDLgrPalette', r, g, b)
> theColorbar = Obj_New('HColorbar', Palette=thePalette)
>

```

```

> r = BytScl(Findgen(256)^10e-2)
Why not alog10(Findgen(256)) ??

```

Thanks David. I had already tried this without success. The colors don't really ramp properly for a general color table (like Rainbow, colortable 13). Even if it did, the colors would be squished so much on one end that it'd be difficult to see what colors = what value.

Playing around, I did find that I get good coloring if I log the data as I bytscl it for the volume object.

```

loadct, 34 ; rainbow color table
tvLCT, r,g,b, /GET
colorTable = [[r],[g],[b]] ; [256,3] color table for vol coloring

```

```

;data of float values in fData. IDLgrVolume's need data bytscl'd
bData = bytscl(alog10(fData), /NaN)
oVol = OBJ_NEW('IDLgrVolume', DATA0=bData, RGB_TABLE0=colorTable)

```

Now the data looks good, but my Hcolorbar still has text annotations that range linearly from min(fData) to max(fData). I noticed that David's hcolorbar is just a little colored IDLgrImage with IDLgrAxis. So, I thought I'd just set the LOG keyword for the textAxis object in his code, maybe this'll work:

```

;//in David's HColorBar code
textAxis = Obj_New("IDLgrAxis", 0, Color=self.color, Ticklen=0.025, $
  Major=self.major, Minor=self.minor, Title=thisTitle, Range=self.range,
/Exact, $
  XCoord_Conv=longScale, Location=[1000, self.position(1), 0.001], $
/LOG)

```

but this squoshes this axis all up to the left of where it should be.

Any suggestions?