Subject: Re: Multiple surface colors in the Z buffer? Posted by David Fanning on Fri, 08 Feb 2002 18:12:12 GMT View Forum Message <> Reply to Message

Timm Weitkamp (weitkamp@esrf.fr) writes:

- > I have a segmented volumetric dataset, and am displaying its segments
- > in a single 3D image, rendering each segment surface with SHADE_VOLUME
- > and then POLYSHADE, plotting to the Z buffer to get hidden parts
- > removed.

>

- > This works fine except that all the surfaces are displayed in the same
- > color. However, I would like to display every segment in a different
- > color (yet continue to have IDL do the shading and hidden-surface
- > removal). Does anybody know if this can be achieved and how, or where
- > I can find material on this problem?

You will have to load different colors in different portions of the color table, then set the shading parameters to use just those colors (SET_SHADING) you want to render in.

Here is an example from my book that renders two surfaces, one in red shades and one in blue shades. You can probably have as many different color schemes as you have surfaces. within the constraints of 256 colors.

Cheers,

David

David W. Fanning, Ph.D. Fanning Software Consulting

Phone: 970-221-0438, E-mail: david@dfanning.com

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Toll-Free IDL Book Orders: 1-888-461-0155

PRO TwoSurf

; Create the data.

```
peak = Shift(Dist(20, 16), 10, 8)
peak = Exp(-(peak/5)^2)
saddle = Shift(peak, 6, 0) + Shift(peak, -6, 0) / 2B
```

; Load program colors.

colors = !D.Table Size/2

LoadCT, 1, NColors=colors LoadCT, 3, NColors=colors, Bottom=colors-1 ; Open a window and display first data set. Window, 1, XSize=300, YSize=300 Device, Decomposed = 0Set_Shading, Values=[0,colors-1] Shade Surf, peak, ZRange=[0.0, 1.2] ; Open a window and display second data set. Window, 2, XSize=300, YSize=300 Set_Shading, Values=[colors, 2*colors-1] Shade_Surf, saddle, ZRange=[0.0, 1.2] : Go into Z-buffer. thisDevice = !D.Name Set_Plot, 'Z', /Copy ; Configure Z device. Device, Set_Colors=2*colors, Set_Resolution=[300,300] ; Load objects in Z-buffer. Set Shading, Values=[0,colors-1] Shade Surf, peak, ZRange=[0.0, 1.2] Set_Shading, Values=[colors, 2*colors-1] Shade Surf, saddle, ZRange=[0.0, 1.2], /NoErase ; Take a snap-shot of Z-buffer display plane. picture = TVRD() ; Display the results. Set Plot, thisDevice Window, 3, XSize=300, YSize=300

END

TV, picture

Subject: Re: Multiple surface colors in the Z buffer? Posted by weitkamp on Tue, 12 Feb 2002 09:44:51 GMT

David Fanning <david@dfanning.com> wrote in message news:<MPG.16cdc2eb40b5b12b9897fa@news.frii.com>...

- > You will have to load different colors in different portions
- > of the color table, then set the shading parameters to use
- > just those colors (SET_SHADING) you want to render in.

That does the job, thanks a lot! Sorry for bothering, I must have overlooked SET_SHADING in the online help.

> Here is an example from my book

Thanks for the code. We have a copy of your book in our group but ... it's usually impossible to find ... mind you, it's not a big group, but still.

Timm

--

Timm Weitkamp
European Synchrotron Radiation Facility (ESRF)
BP 220, F-38043 Grenoble Cedex, France