Subject: Re: plots?
Posted by David Fanning on Tue, 20 Aug 2002 04:03:11 GMT
View Forum Message <> Reply to Message

helen (bin\_zheng\_99@yahoo.com) writes:

- > I have a problem about using plots. I want to use two plots for two
- > different data sets at the same time. If I just use one plots for one
- > data set, there is no problem. But when I use two, it doesn't work. It
- > seems the two plots interrupt each other. I want to know why?

I really can't tell what you are trying to do, but if you put a couple of plots into your code so you have a good reference point, it appears you are at least plotting into both windows. I've never seen the CONTINUE keyword before, and can't really tell what it does (or is suppose to do) in this program.

```
pro testPlots
arrayT = fltarr(11)
arrayX = fltarr(11)
arrayY = fltarr(11)
window, 1
plot,[0,10],[-10,10], /NoData
x1 = !X & y1 = !Y & p1 = !P
window,2
plot,[0,10],[-5,5], /NoData
x2 = !X & y2 = !Y & p2 = !P
for I=0, 10 Do begin
  arrayY[I] = cos(I+1)
  arrayX[I] = sin(I+1)
  arrayT[I] = I
wset, 1
!X = x1 \& !Y = x1 \& !P = p1
 plots,arrayT[I], arrayX[I], /continue
wset, 2
!X = x2 \& !Y = y2 \& !P = p2
 plots,arrayT[I], arrayY[I], /continue
endfor
end
Does this give you any clues!?
Are you trying to do this?
 arrayT = fltarr(11)
 arrayX = Sin(fltarr(11) + 1)
```

```
arrayY = Cos(fltarr(11) + 1)
Window,3, arrayT, arrayX
Window, 4, arrayT, arrayY
```

Cheers.

David

--

>

David W. Fanning, Ph.D.

Fanning Software Consulting, Inc.

Phone: 970-221-0438, E-mail: david@dfanning.com

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: plots?
Posted by Don J Lindler on Tue, 20 Aug 2002 11:51:01 GMT
View Forum Message <> Reply to Message

```
> I have a problem about using plots. I want to use two plots for two
> different data sets at the same time. If I just use one plots for one
> data set, there is no problem. But when I use two, it doesn't work. It
> seems the two plots interrupt each other. I want to know why?
>
> Thanks very much for any kind of help!
> I attach my simple program below:
> pro testPlots
> arrayT = fltarr(11)
> arrayX = fltarr(11)
> arrayY = fltarr(11)
> window, 1
> x1 = !X & y1 = !Y & p1 = !P
> window,2
> x2 = !X & y2 = !Y & p2 = !P
> for i=0, 10 Do begin
    arrayY[i] = cos(i+1)
>
     arrayX[i] = sin(i+1)
     arrayT[i] = i
> wset, 1
> !X = x1 \& !Y = x1 \& !P = p1
> plots,arrayT[i], arrayX[i], /continue
> wset, 2
> !X = x2 \& !Y = y2 \& !P = p2
> plots,arrayT[i], arrayY[i], /continue
```

```
> endfor
>
> end
```

The /continue is telling the routine to start plotting from where the last plots was performed. When you are changing wingows the routine is continuing the plot from the point where the other window left off. If you want to plot in this manner, I would suggest letting your program keep track of where you left off.

```
for i=0, 10 Do begin
    arrayY[i] = cos(i+1)
    arrayX[i] = sin(i+1)
    arrayT[i] = i
    if i gt 0 then begin
        wset, 1
      !X = x1 & !Y = x1 & !P = p1
        plots, arrayT[[i-1,i]], arrayX[[i-1,i]]
        wset, 2
      !X = x2 & !Y = y2 & !P = p2
        plots, arrayT[[i-1,i]], arrayY[[i-1,i]]
    end
endfor
```

Don

Subject: Re: plots?
Posted by Robert Stockwell on Tue, 20 Aug 2002 13:12:06 GMT
View Forum Message <> Reply to Message

```
> pro testPlots
> arrayT = fltarr(11)
> arrayX = fltarr(11)
> arrayY = fltarr(11)
> window, 1
> x1 = !X & y1 = !Y & p1 = !P
> window,2
> x2 = !X & y2 = !Y & p2 = !P
> for i=0, 10 Do begin
     arrayY[i] = cos(i+1)
>
     arrayX[i] = sin(i+1)
>
     arrayT[i] = i
> wset, 1
> !X = x1 & !Y = x1 & !P = p1
  plots,arrayT[i], arrayX[i], /continue
> wset, 2
> !X = x2 & !Y = y2 & !P = p2
   plots,arrayT[i], arrayY[i], /continue
>
> endfor
> end
How about:
arrayT = fltarr(11)
arrayX = fltarr(11)
arrayY = fltarr(11)
window, 1
plot,[0,10],[-10,10], /NoData,title='plot 1'
x1 = !X & y1 = !Y & p1 = !P
window,0
plot,[0,10],[-5,5], /NoData,title='plot 2'
x2 = !X & y2 = !Y & p2 = !P
for I=1, 10 Do begin
   arrayY[I] = cos(I+1)
   arrayX[I] = sin(I+1)
   arrayT[I] = I
endfor
for I=0, 10-1 Do begin
wset, 1
```

```
plots,arrayT[I], arrayX[I]
plots,arrayT[I+1], arrayX[I+1], /continue

wset, 0
plots,arrayT[I], arrayY[I]
plots,arrayT[I+1], arrayY[I+1], /continue

endfor
end

Cheers,
bob
```

Subject: Re: plots?
Posted by bin\_zheng\_99 on Tue, 20 Aug 2002 13:26:02 GMT
View Forum Message <> Reply to Message

```
David Fanning <david@dfanning.com> wrote in message
news:<MPG.17cb6d6733fc1915989969@news.frii.com>...
> helen (bin zheng 99@yahoo.com) writes:
>> I have a problem about using plots. I want to use two plots for two
>> different data sets at the same time. If I just use one plots for one
>> data set, there is no problem. But when I use two, it doesn't work. It
>> seems the two plots interrupt each other. I want to know why?
>
> I really can't tell what you are trying to do, but if you
> put a couple of plots into your code so you have a good
> reference point, it appears you are at least plotting
> into both windows. I've never seen the CONTINUE keyword
> before, and can't really tell what it does (or is suppose
> to do) in this program.
>
> pro testPlots
> arrayT = fltarr(11)
> arrayX = fltarr(11)
> arrayY = fltarr(11)
> window, 1
> plot,[0,10],[-10,10], /NoData
> x1 = !X & y1 = !Y & p1 = !P
> window.2
> plot,[0,10],[-5,5], /NoData
> x2 = !X & y2 = !Y & p2 = !P
> for I=0, 10 Do begin
    arrayY[I] = cos(I+1)
    arrayX[I] = sin(I+1)
```

```
arrayT[I] = I
> wset. 1
> !X = x1 & !Y = x1 & !P = p1
> plots,arrayT[I], arrayX[I], /continue
> wset. 2
> !X = x2 & !Y = y2 & !P = p2
   plots,arrayT[I], arrayY[I], /continue
> endfor
> end
>
 Does this give you any clues!?
>
 Are you trying to do this?
>
    arrayT = fltarr(11)
>
    arravX = Sin(fltarr(11) + 1)
>
    arrayY = Cos(fltarr(11) + 1)
    Window, 3, array T, array X
>
    Window, 4, arrayT, arrayY
> Cheers,
> David
```

Hello, David,

Thanks David for your help. But I still have not solved my problem. My problem is whether I can plot two different data in two windows at the same time? Because I want to track a target's movement and display its x (arrayX) and y (arrayY) position against the time (arrayT) at the real time. So that I can see the moving from the plots in these two windows. So, I write a simple program to test if I can plot two different data (arrayX against arrayT, arrayX against arrayT) at the same time and still get correct result? Is there a way to do this?

Thanks very much for any suggestion!

Subject: Re: plots?

Posted by R.Bauer on Tue, 20 Aug 2002 14:31:56 GMT

View Forum Message <> Reply to Message

## helen wrote:

- > David Fanning <david@dfanning.com> wrote in message
- > news:<MPG.17cb6d6733fc1915989969@news.frii.com>...
- >> helen (bin\_zheng\_99@yahoo.com) writes:

```
>>
>>> I have a problem about using plots. I want to use two plots for two
>>> different data sets at the same time. If I just use one plots for one
>>> data set, there is no problem. But when I use two, it doesn't work. It
>>> seems the two plots interrupt each other. I want to know why?
>>
>> I really can't tell what you are trying to do, but if you
>> put a couple of plots into your code so you have a good
>> reference point, it appears you are at least plotting
>> into both windows. I've never seen the CONTINUE keyword
>> before, and can't really tell what it does (or is suppose
>> to do) in this program.
>>
>> pro testPlots
>> arrayT = fltarr(11)
>> arrayX = fltarr(11)
>> arrayY = fltarr(11)
>> window, 1
>> plot,[0,10],[-10,10], /NoData
>> x1 = !X & y1 = !Y & p1 = !P
>> window,2
>> plot,[0,10],[-5,5], /NoData
>> x2 = !X & y2 = !Y & p2 = !P
>> for I=0, 10 Do begin
      arrayY[I] = cos(I+1)
>>
      arrayX[I] = sin(I+1)
>>
>>
      arrayT[I] = I
>> wset, 1
>> !X = x1 \& !Y = x1 \& !P = p1
>> plots,arrayT[I], arrayX[I], /continue
>> wset. 2
>> !X = x2 \& !Y = y2 \& !P = p2
>> plots,arrayT[I], arrayY[I], /continue
>> endfor
>> end
>>
>> Does this give you any clues!?
>> Are you trying to do this?
>>
     arrayT = fltarr(11)
     arrayX = Sin(fltarr(11) + 1)
>>
     arrayY = Cos(fltarr(11) + 1)
>>
     Window, 3, array T, array X
>>
     Window, 4, arrayT, arrayY
>>
>>
>> Cheers,
```

>> >> David > Hello, David,

- > Thanks David for your help. But I still have not solved my problem. My
- > problem is whether I can plot two different data in two windows at the
- > same time? Because I want to track a target's movement and display its
- > x (arrayX) and y (arrayY) position against the time (arrayT) at the
- > real time. So that I can see the moving from the plots in these two
- > windows. So, I write a simple program to test if I can plot two
- > different data (arrayX against arrayT, arrayX against arrayT) at the
- > same time and still get correct result? Is there a way to do this?

> Thanks very much for any suggestion!

Dear Helen.

this a normal common problem and may be I can help. idl saves always only the last state of coordination vars of a window to several system variables. So there is a transformation matrix neccesary for each window you create depending on sizes, type and range. The routines savesysvar and restsysvar are doing this for you.

After "plot" in first window or in your example creation of the window you have to store the system vars by p1=savesysvar() and for the second window plot into p2.

If you now actualize first window you have to restore their belonging system variables by restsysvar,p1 and if you switch to plot on the other window you have to set restsysvar,p2

http://www.fz-juelich.de/icg/icg-i/idl\_icglib/idl\_source/idl \_html/dbase/download/restsysvar.tar.gz http://www.fz-juelich.de/icg/icg-i/idl\_icglib/idl\_source/idl \_html/dbase/download/savesysvar.tar.gz

or as idl 5.5 binary

http://www.fz-juelich.de/icq/icq-i/idl icqlib/idl source/idl html/dbase/download/restsysvar.sav http://www.fz-juelich.de/icg/icg1/idl\_icglib/idl\_source/idl\_ html/dbase/download/savesysvar.sav

(Remember a idl compiled file with the extension sav is automaticly loaded the first time it is used. This is the same behaviour as for idl sources (.pro). They run on each idl platform with the same idl version)

For further routines and licensing please have a look at http://www.fz-juelich.de/icg/icg-i/idl icglib/idl lib intro. html

```
best regards
```

Reimar

```
pro test
arrayT = fltarr(11)
arrayX = fltarr(11)
arrayY = fltarr(11)
window, 1
x_1 = X & y_1 = Y & p_1 = P
p1=savesysvar()
window.2
x^2 = X & y^2 = Y & p^2 = P
p2=savesysvar()
for i=0, 10 Do begin
  arrayY[i] = cos(i+1)
  arrayX[i] = sin(i+1)
  arrayT[i] = i
    wset, 1
restsysvar,p1
    !X = x1 \& !Y = x1 \& !P = p1
         plots,arrayT[i], arrayX[i], /continue
    wset, 2
restsysvar,p2
    !X = x2 \& !Y = y2 \& !P = p2
         plots,arrayT[i], arrayY[i], /continue
endfor
end
Forschungszentrum Juelich
email: R.Bauer@fz-juelich.de
http://www.fz-juelich.de/icg/icg-i/
a IDL library at ForschungsZentrum Juelich
http://www.fz-juelich.de/icg/icg-i/idl_icglib/idl_lib_intro. html
```

```
Subject: Re: plots?
Posted by David Fanning on Tue, 20 Aug 2002 14:37:43 GMT
View Forum Message <> Reply to Message
```

helen (bin\_zheng\_99@yahoo.com) writes:

> Thanks David for your help. But I still have not solved my problem. My

- > problem is whether I can plot two different data in two windows at the
- > same time? Because I want to track a target's movement and display its
- > x (arrayX) and y (arrayY) position against the time (arrayT) at the
- > real time. So that I can see the moving from the plots in these two
- > windows. So, I write a simple program to test if I can plot two
- > different data (arrayX against arrayT, arrayX against arrayT) at the
- > same time and still get correct result? Is there a way to do this?

I think I would drop the CONTINUE keyword and just draw from the last point to this point:

```
pro testPlots
arrayT = fltarr(11)
arrayX = fltarr(11)
arrayY = fltarr(11)
window, 1
plot,[0,10],[-10,10], /NoData
x1 = !X & y1 = !Y & p1 = !P
window,2
plot,[0,10],[-10,10], /NoData
x2 = !X & y2 = !Y & p2 = !P
for I=1, 10 Do begin
  arrayY[I] = cos(I+1)
  arrayX[I] = sin(I+1)
  arrayT[I] = I
 wset, 1
 !X = x1 \& !Y = y1 \& !P = p1
    plots,[arrayT[i-1], arrayT[l]], $
       [arrayX[i-1], arrayX[I]]
 wset, 2
 !X = x2 \& !Y = y2 \& !P = p2
 print, [arrayY[i-1], arrayY[I]]
    plots,[arrayT[i-1], arrayT[l]], $
       [arrayY[i-1], arrayY[I]]
endfor
end
This works perfectly, as far as I can tell.
Cheers,
David
David W. Fanning, Ph.D.
Fanning Software Consulting, Inc.
Phone: 970-221-0438, E-mail: david@dfanning.com
```

Coyote's Guide to IDL Programming: http://www.dfanning.com/ Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: plots?

Posted by MKatz843 on Tue, 20 Aug 2002 18:30:06 GMT

View Forum Message <> Reply to Message

Helen, IDL is more elegant than you suppose.

I would suggest using arrays rather than FOR loops. (David meant findgen() rather then fltarr(), I assume.) With the plots outside of a loop, you won't need to use the /continue keyword.

Whenever I need to set up a plot and then draw the plot in two steps, I use the /data keyword. Then you don't need to hassle with !X, !Y, and the like. This is done in testPlots2 below.

An even more compact version is in testPlots3 below. This may or may not work for you, but I combine the creation of the plot and the actual plotting into one step using plot rather than plot & plots. They keywords to plot let you choose the domain and range (x and y) yourself, and the ystyle=1 setting allows you to force the use of [-5,5] rather than the automatically-selected [-6,6].

```
pro testPlots2
window, 1
plot,[0,10],[-10,10], /NoData
window,2
plot,[0,10],[-5,5], /NoData
I = findgen(11)
arrayY = cos(I+1)
arrayX = sin(I+1)
arrayT = I
wset, 1
plots, arrayT, arrayX, /data
wset, 2
plots, arrayT, arrayY, /data
end
pro testPlots3
I = findgen(11)
```

arrayY = cos(I+1)

```
arrayX = sin(I+1)
arrayT = I

window, 1
plot, arrayT, arrayX, /data, xrange=[0,10], yrange=[-10,10]
window, 2
plot, arrayT, arrayY, /data, xrange=[0,10], yrange=[-5,5], ystyle=1
end
```

I hope this points you in the right direction,

M. Katz