

---

Subject: Re: droplist doesn't work under Linux  
Posted by [R.Bauer](#) on Wed, 09 Oct 2002 10:23:46 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Claudia Herklotz wrote:

> My routine worked well untill I added a droplist widget. When I tried to  
> click on the droplist my KDE was killed. But under Windows it worked  
> correctly. Does anyone know about that problem ?  
>  
> Thanks a lot  
> Claudia  
>  
>

Dear Claudia

please can you post a short example.

regards

Reimar

--  
Reimar Bauer

Institut fuer Stratosphaerische Chemie (ICG-I)  
Forschungszentrum Juelich  
email: [R.Bauer@fz-juelich.de](mailto:R.Bauer@fz-juelich.de)

---

a IDL library at ForschungsZentrum Juelich  
[http://www.fz-juelich.de/icg/icg-i/idl\\_icglib/idl\\_lib\\_intro.html](http://www.fz-juelich.de/icg/icg-i/idl_icglib/idl_lib_intro.html)

---

---

Subject: Re: droplist doesn't work under Linux  
Posted by [Claudia Herklotz](#) on Fri, 11 Oct 2002 07:24:08 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hello Reimar,

this is a shortened version of my source code. If you delete subbase\_two and put the droplist widget into subbase\_one or set subbase\_one sensitive, the program is working properly.

Thank you for your help,  
Claudia .

```

PRO TEST_EVENT, event

WIDGET_CONTROL, event.top, GET_UVALUE = data
WIDGET_CONTROL, event.id, GET_UVALUE = source

CASE source OF

'button': BEGIN
  IF event.select EQ 1 THEN $
    WIDGET_CONTROL, (*data).subbase_one, SENSITIVE = 1
  IF event.select EQ 0 THEN $
    WIDGET_CONTROL, (*data).subbase_one, SENSITIVE = 0
END

ELSE:

ENDCASE
END

;-----
PRO TEST

tlb = WIDGET_BASE(ROW = 2)
head_but_base = WIDGET_BASE(tlb, /NONEXCLUSIVE, $
  ROW = 1)
button = WIDGET_BUTTON(head_but_base, $
  UVALUE = 'button')
*** subbase_one = WIDGET_BASE(tlb, ROW = 4, FRAME = 1, $
  SENSITIVE = 0, UVALUE = 'subbase_one')
*** subbase_two = WIDGET_BASE(subbase_one, ROW = 1)

drop_values = strarr(1)
drop_values[0] = 'test'
filter_drop = WIDGET_DROPLIST(subbase_two, $
  VALUE = drop_values, UVALUE = 'filter_drop')

data_store = {subbase_one: subbase_one}
data = ptr_new(data_store)
WIDGET_CONTROL, tlb, SET_UVALUE = data
WIDGET_CONTROL, tlb, /REALIZE
XMANAGER, 'TEST', tlb

END

```

----- Original Message -----

From: "Reimar Bauer" <R.Bauer@fz-juelich.de>  
Newsgroups: comp.lang.idl-pwave  
Sent: Wednesday, October 09, 2002 12:23 PM  
Subject: Re: droplist doesn't work under Linux

> Claudia Herklotz wrote:  
>> My routine worked well until I added a droplist widget. When I tried to  
>> click on the droplist my KDE was killed. But under Windows it worked  
>> correctly. Does anyone know about that problem ?  
>>  
>> Thanks a lot  
>> Claudia  
>>  
>>  
>  
> Dear Claudia  
>  
> please can you post a short example.  
>  
> regards  
>  
> Reimar  
>  
>  
>  
>  
> --  
> Reimar Bauer  
>  
> Institut fuer Stratosphaerische Chemie (ICG-I)  
> Forschungszentrum Juelich  
> email: R.Bauer@fz-juelich.de  
> -----  
> a IDL library at ForschungsZentrum Juelich  
> [http://www.fz-juelich.de/icg/icg-i/idl\\_icglib/idl\\_lib\\_intro.html](http://www.fz-juelich.de/icg/icg-i/idl_icglib/idl_lib_intro.html)  
> ======