
Subject: IDL and SQL

Posted by [MKatz843](#) on Wed, 06 Nov 2002 16:47:06 GMT

[View Forum Message](#) <> [Reply to Message](#)

Has anyone out there made any efforts to link IDL to an SQL database?
Even if the actions were write-only from IDL, I'm interested.

Thanks,

M. Katz

Subject: Re: IDL and SQL

Posted by [dmarino](#) on Thu, 07 Nov 2002 21:26:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

MKatz843@onebox.com (M. Katz) wrote in message

news:<4a097d6a.0211060847.30c8960b@posting.google.com>...

> Has anyone out there made any efforts to link IDL to an SQL database?

> Even if the actions were write-only from IDL, I'm interested.

>

> Thanks,

>

> M. Katz

I am very new to IDL but have done some Perl-ing in my day, so what I like to do is spawn a perl DBI script to interact with an SQL server and spawn so nicely returns an array of rows.

I have done this with Sybase DBs, PostgreSQL DBs and MySQL

That avoids doing DataMiner stuff, which I don't really know about, but I think costs money?? (please correct me if I'm wrong on that).

Just a suggestion, really, this is probably not recommended by the gurii.

That is a hack, but being mainly a Perl guy that's a lot more acceptable than it will probably be to this group ;-)

D Marino
Digitalglobe

Subject: Re: IDL and SQL

Posted by [Andy Loughe](#) on Fri, 08 Nov 2002 19:36:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

M. Katz wrote:

```
> Has anyone out there made any efforts to link IDL to an SQL database?
> Even if the actions were write-only from IDL, I'm interested.
>
> Thanks,
>
> M. Katz
```

Here's something I put together once to read output from MySQL into IDL.

Nothing very fancy... very brute force...

```
function get_mysql_vars, datain, heading, floatit=floatit,
longit=longit, info=info

;
; Obtain variable names from a MySQL database query, and
; store the associated values into identically named
; variables within an IDL data structure.
;
; Originator: Andrew F. Loughe :: 11 OCT 2000
;
; ASSUMPTIONS:
; 1) That the MySQL query results in a 2-D table sent to STDOUT.
; 2) That the command issued was mysql -t ('|' delimited data).
;
; PARAMETER:
; datain : Parameter containing the table of actual data.
; heading : Parameter containing the variables to process (MySQL table
heading).
;
; KEYWORDS:
; floatit : converts those variables listed, to type=float.
; longit : converts those variables listed, to type=long.
; info : only return the variable names (MySQL table heading).
;

on_error, 2
;; start_time = systime(1) ; Let's do some MySQL-like timing
of the read

usage="data = get_mysql_vars(data, heading, floatit='area, yy',
longit='id', /info)"
if (N_params() lt 2) then message, usage
```

```

num_vars = N_elements(heading) ; Number of variables (fields) to process
num_rows = N_elements(datain) ; Number of rows (records) in the table
snum_rows = strtrim(num_rows, 2)
if (num_rows ge 100000L) then print, '**** ' + strtrim(num_rows,2) + $
                                ' records may take awhile ****'

; Announce to the user which variables are being processed.
format = "(a, a, " + strtrim(num_vars-1,2) + "(", ',a))"
print, '---> Database variables(' + strtrim(num_vars,2) + '): ', $
      heading, format=format
if (KEYWORD_SET(info)) then begin
    print, '**** NOTHING RETURNED. INFO. ONLY!!!'
    return, -999
endif

; Find location of all '|' characters and create a format statement for
reads.
test_str = datain(0) ; Create format for: record = datain(0)
test_len = strlen(test_str)

; Store output STRING variables into a DATA STRUCTURE called dataS.
; Then copy results into a structure which can contain LONGS and FLOATS
(dataout).
cmd1      = 'dataS = {' ; Structure used with reads
cmd2      = 'dataout = {' ; Structure for mapping dataS --->
dataout
convert_cmd = " ; Command for mapping dataS ---> dataout

for ii = 0L, num_vars-1L do begin ; Loop through all the variables
    str_var = heading(ii) ; Get current variable name to process

; Initially, read all data as STRINGS. Make command to create the
structure of strings.
    format_type = 'a'
    cmd1      = cmd1 + str_var + ":' '"
    if (ii lt num_vars-1L) then cmd1 = cmd1 + ','
    if (ii eq num_vars-1L) then cmd1 = cmd1 + '}' ; data: All string reads

; Convert some data to longs and floats? Make command to create new
structure (dataout).
    iv = where( str_var eq longit, counting ) ; dataout: longs?
    iv = where( str_var eq floatit, countflt ) ; dataout: floats?
    case 1 of
        (counting gt 0): begin ; LONGS into dataout
            cmd2      = cmd2 + str_var + ':lonarr(' +
snum_rows + ')'
            convert_cmd = convert_cmd+'dataout.'+str_var+'='+$
                        'long(TEMPORARY(dataS.' + str_var

```

```

+ '))'
        end
        (countflt gt 0): begin      ; FLOATS into dataout
            cmd2      = cmd2 + str_var + ':fltarr(' +
snum_rows + ')'
            convert_cmd = convert_cmd+'dataout.'+str_var+'='+ $
                        'float(TEMPORARY(dataS.' + str_var
+ '))'
        end
    else:      begin      ; STRINGS into dataout
        cmd2      = cmd2 + str_var + ':strarr(' +
snum_rows + ')'
        convert_cmd = convert_cmd+'dataout.'+str_var+'='+ $
                    'strtrim(TEMPORARY(dataS.' +
str_var + '),2)'
        end
    endcase
    if (ii lt num_vars-1L) then cmd2      = cmd2 + ','      ;
TERMINATORS
    if (ii eq num_vars-1L) then cmd2      = cmd2 + '}'
    if (ii lt num_vars-1L) then convert_cmd = convert_cmd + ' & '

; Find position of all '|' characters, and create the necessary format
statement.
    if (ii eq 0) then begin
        pos      = 0
        tab_pos = pos + 1
        formats = format_type
        format = '(2x,'      ; Initial format string (will be built upon)
    endif else begin
        pos      = strpos( test_str, '|', pos+1)
        if ( pos ge 0 ) then tab_pos = [ [tab_pos], pos+1 ]
        formats = [ [formats], format_type ]
        format =
format+formats(ii-1)+strtrim(tab_pos(ii)-tab_pos(ii-1)-3,2)+ ',3X,'
    endelse
endfor
format = format + format_type + strtrim(test_len-tab_pos(ii-1)-3,2) + ',2x)'

; Replicate the STRING data structure, and read the data, then map
dataS --> dataout
jnk  = execute(cmd1)      ; Execute cmd1 to create data
structure (dataS)
dataS = replicate( dataS, num_rows ) ; Create array of structures (dataS)
reads, datain, dataS, format=format ; Read dataS string structure.
jnk  = execute(cmd2)      ; Create a structure of arrays
(dataout)
jnk  = execute(convert_cmd)      ; Map dataS --> dataout

```

```
; Print MySQL-like end message.  
;; print, strtrim(num_vars,2) + ' variables, each with ' + snum_rows + $  
;; ' elements (' +  
strtrim(string(systime(1)-start_time,format='(f29.2)'),2) + ' sec)'
```

return, dataout ; Return the output data structure to the calling routine.

end

Subject: Re: IDL and SQL

Posted by [MKatz843](#) on Thu, 14 Nov 2002 19:36:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

dmarino, Andy, thanks for the feedback!

Since I last posted I've learned that there exists something called the IDL DataMiner which sells for \$500 and which interacts with ODBC databases.

Has anyone out there had any good or bad experiences with it?
I'm contemplating a purchase.

Thanks.

M. Katz

Subject: Re: IDL and SQL

Posted by [Mark Hadfield](#) on Thu, 14 Nov 2002 20:36:02 GMT

[View Forum Message](#) <> [Reply to Message](#)

"M. Katz" <MKatz843@onebox.com> wrote in message
news:4a097d6a.0211141136.281f73c5@posting.google.com...

> Since I last posted I've learned that there exists something called
> the IDL DataMiner which sells for \$500 and which interacts with ODBC
> databases.

>

> Has anyone out there had any good or bad experiences with it?

Does the job for me (Windows NT/2000, interacting with databases generated by MS Access & Excel via Windows ODBC drivers).

It's been around for a while & I think the bugs have been ironed out.

--

Mark Hadfield "Ka puwaha te tai nei, Hoesa tatou"
m.hadfield@niwa.co.nz
National Institute for Water and Atmospheric Research (NIWA)

Subject: Re: IDL and SQL
Posted by [rmoss4](#) on Thu, 14 Nov 2002 20:39:34 GMT
[View Forum Message](#) <> [Reply to Message](#)

M. Katz wrote:

- > dmarino, Andy, thanks for the feedback!
- >
- > Since I last posted I've learned that there exists something called
- > the IDL DataMiner which sells for \$500 and which interacts with ODBC
- > databases.
- >
- > Has anyone out there had any good or bad experiences with it?
- > I'm contemplating a purchase.
- >
- > Thanks.
- >
- > M. Katz

We have used DataMiner to interface to Oracle 7/8 databases for 3 or 4 years now. We have had no problems, and it works as advertised. It gets my recommendation if you want an easy, IDL based interface to your ODBC databases.

Robert Moss, PhD
rmoss4@houston.rr.com
