
Subject: Re: how to interrupt in IDL for windows ?

Posted by [David Fanning](#) on Wed, 23 Apr 2003 15:56:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

Kristian Kjaer (Kristian.Kjaer@Risoe.DK) writes:

- > Failing that, does anyone have a widget stop button that could be
- > queried inside loops and appropriately reacted on?

My progress bar can be easily modified to do that:

http://www.dfanning.com/programs/progressbar__define.pro

Cheers,

David

--

David W. Fanning, Ph.D.

Fanning Software Consulting, Inc.

Phone: 970-221-0438, E-mail: david@dfanning.com

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>

Toll-Free IDL Book Orders: 1-888-461-0155

Subject: Re: how to interrupt in IDL for windows ?

Posted by [Craig Markwardt](#) on Wed, 23 Apr 2003 21:55:28 GMT

[View Forum Message](#) <> [Reply to Message](#)

Kristian Kjaer <Kristian.Kjaer@Risoe.DK> writes:

- >
- > I am using Craig Markwardt's nice MPFITFUN. Usually it converges fast
- > but sometimes by mistake I let it loose with the wrong start parameters,
- > too many free parameters, and a large number of allowed iterations. Then
- > I can only sit and wait for my IDL prompt to come back, or kill the
- > whole process and loose some of my work.
- >

I think if you use the /ITERSTOP keyword to any of the MPFIT functions, then it will check for control-G and break out of the fitting loop. Why control-G? I'm an Emacs user...

If you want to make it into a widget with a "stop" button, then you probably want to use the ITERPROC. Here is an example of how to set up a small window (INFO.TLB is the top level base of the whole application):

```
geom = widget_info(info.tlb, /geometry)
xpos = geom.xoffset + geom.xsize/2 - 100
```

```

ypos = geom.yoffset + geom.ysize/2 - 50

tlb = widget_base(title='Fitting Status', row=1, xoffset=xpos, yoffset=ypos)
stopbut = widget_button(tlb, value='STOP')
col = widget_base(tlb, column=1)
stat1line = widget_label(col, value=' Iteration:      ', /align_left)
stat2line = widget_label(col, value='Chi-square:      ', /align_left)
stat3line = widget_label(col, value='      DOF:      ', /align_left)
statline = [stat1line, stat2line, stat3line]

;; Render the status widget
widget_control, tlb, /realize

;; Perform the fit - put your own fitting routine here
p1 = mpfitfun('clockfit_model', t1, dt1, dt2, p0, parinfo=pi, yfit=mdl1, $
    functargs={partitions: part, clockset: fs, parttype: ptype}, $
    iterproc='clockfit_iterproc', status=status, $
    iterargs={stopbut:stopbut, statline: statline})

;; Safely destroy the widget
if widget_info(tlb, /valid_id) then begin
    widget_control, tlb, /destroy
endif

```

And listed below is the CLOCKFIT_ITERPROC routine which updates the display and traps any clicks on the STOP button.

Craig

```

pro clockfit_iterproc, fcn, p, iter, fnorm, dof=dof, $
    stopbut=stopbut, statline=statline, _EXTRA=extra

;; Be sure there are widgets available to interact with
if n_elements(stopbut) EQ 0 OR n_elements(statline) EQ 0 then return
if widget_info(stopbut, /valid_id) EQ 0 OR $
    widget_info(statline(0), /valid_id) EQ 0 then return

;; Adjust the text values
widget_control, statline(0), $
    set_value=string(iter, format=('" Iteration: ",I0)')
if fnorm GT 1d6 then fmt = 'E10.4' else fmt = 'D8.1'
widget_control, statline(1), $
    set_value=string(fnorm, format=('"Chi-square: "',+fmt+'))
widget_control, statline(2), $
    set_value=string(dof, format=('"      DOF: ",I0)')

```

```

;; Check the widget stop button. If not pressed, then return
event = widget_event(/nowait, stopbut)
evname = tag_names(event, /structure_name)
if evname EQ " OR event.id EQ 0 then return

;; If the widget stop button was pressed, then cancel the fit and
;; return
if evname EQ 'WIDGET_BUTTON' AND event.select then begin
  widget_control, statline(0), set_value=""
  widget_control, statline(1), set_value=' Fitting Cancelled'
  widget_control, statline(2), set_value=""

  event1 = widget_event(/nowait, stopbut)
  wait, 2 ;; Pause for dramatic effect

  widget_control, event.top, /destroy
  common mpfit_error, mperr
  mperr = -1
endif

return
end

```

--

 Craig B. Markwardt, Ph.D. EMAIL: craigmnet@cow.physics.wisc.edu
 Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response
