
Subject: problem with hidden lines in SURFACE in IDL version 5.5 and 5.6

Posted by [Kristian Kjaer](#) on Wed, 23 Apr 2003 14:56:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

I used to enjoy a barely-documented feature of the IDL SURFACE procedure:

If the data are on a 'topologically rectangular' grid, then I could use the SURFACE procedure on them without the need to TRIGRID the data onto a strictly rectangular grid.

However this feature seems to be broken since version 5.5.

Do y'all see the same, and does anyone know a work-around?

I try to avoid TRIGRID because

- * it is slow,

- * it interpolates the data points (bad!), and

- * it used to give a one-half pixel offset to the data, although I think this has been fixed in IDL 5.x

- Kristian

```
; Document a problem with hidden lines in SURFACE in IDL version 5.5 and 5.6:
```

```
; Make up some surface data:
```

```
x=-2.447+findgen(204)/203*(16.3659+2.447)
```

```
y=14.0+findgen(181)/180*(18.5-14.0)
```

```
z=1/(1+(x/8)^4)#(1/(1+(y-16.5)^6))*2500
```

```
; Plot the data:
```

```
surface,z,x,y,ax=45,az=-30,/hor
```

```
; It also works to have x and y the same SIZE as z:
```

```
xx=x#(1+y-y)
```

```
yy=(1+x-x)#y
```

```
; Plot the data. This looks the same as before:
```

```
surface,z,xx,yy,ax=45,az=-30,/hor
```

```
; Apply the following nonlinear transformation:
```

```
kvec=4.81949
```

```
degree=!pi/180.
```

```
xxx =kvec*sin(xx*degree)
```

```
yyy =kvec*sqrt(1+cos(xx*degree)^2-2*cos(xx*degree)*cos(yy*degree ))
```

```
; Now xxx and yyy are not on a rectangular grid.
```

```
; One could use trigrid etc. to interpolate to a new rectangular grid.
```

```
; However, the following is much easier and faster, and it
```

```
; also works correctly in IDL through version 5.3:
```

surface,z,xxx,yyy,ax=45,az=-30,/hor

; However, in IDL5.5 and IDL5.6, the hidden lines come out wrong.
