
Subject: sec : U Re: problem with checkbox in cw_form
Posted by [Andrew Cool](#) on Tue, 29 Apr 2003 03:56:42 GMT
[View Forum Message](#) <> [Reply to Message](#)

Sergey Koposov wrote:

>
> Hello!
> Because, this widget is used in very complicated program, and it would
> be nice if the values of some parameters entered by user were obtained
> with single cw_form (it is more simple to get the states of fields with
> using cw_form then standart widget construction).
> Moreover, I don't believe that it is impossible to make a single
> checkbox in cw_form. It would be very strange , I think. :)
> Cheers,
> Sergey K
>
> Pavel Romashkin wrote:
>> Why not create the single checkbox in a separate exclusive base, not as
>> part of cw_form?
>>
>> Cheers,
>> Pavel
>>
>> "iċ½xīċ½iċ½iċ½" wrote:
>>
>>> Can somebody tell me how to create only one checkbox in the cw_form. I dont
>>> how to do this, because , by default, if there is only one item in the
>>> initial value field (in the parameters of cw_form) IDL create a simple
>>> button, but no the checkbox.
>>> Thanks,
>>> Sergey Koposov

Sergey,

CW_FORM is available as a .PRO file in your IDL disribution,
e.g. look for C:\RSI\IDL56\LIB\CW_FORM.PRO.

CW_FORM.PRO is hardwired to produce single "standard" button if
you only supply 1 value.

But there's no reason why you can't take a copy of RSI's CW_FORM.PRO
and put it into your own IDL path, preferably sensibly renamed.

Below I've take a brute force approach and just copied the code for
multiple buttons into the area for a singel button. It works nicely,
producing a single checked button.

You might wish to make a more sensitive amendment to the code ;-)

Cheers,

Andrew

```
'BUTTON': BEGIN
  CW_FORM_APPEND, extra, e, 'LABEL_LEFT', /USE_VALUE
  CW_FORM_APPEND, extra, e, 'LABEL_TOP', /USE_VALUE
  exclusive = CW_FORM_PARSE(e, 'EXCLUSIVE')
  no_release = CW_FORM_PARSE(e, 'NO_RELEASE')
  values = strtok(a[2], '|', /EXTRACT, ESC='\')

  if n_elements(values) ge 2 then begin
    type = 0
    if CW_FORM_PARSE(e, 'SET_VALUE', temp) then begin
      result = execute('sval=fix('+temp+')')
      new = CW_BGROUPE(parent, strtok(a[2], '|', /EXTRACT), $
        EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
        FRAME=frame, NO_RELEASE = no_release, $
        SET_VALUE = sval, _EXTRA=extra)
    endif else begin
      new = CW_BGROUPE(parent, strtok(a[2], '|', /EXTRACT), $
        EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
        FRAME=frame, NO_RELEASE = no_release, _EXTRA=extra)
    endelse
    WIDGET_CONTROL, new, GET_VALUE=value
  endif else begin
;A.D. Cool Comment out original RSI code for 1 button value
    ; type = 2
    ;new = WIDGET_BUTTON(parent, value=values[0], FRAME=frame,
    _EXTRA=extra)
    ;value = 0L

;A.D. Cool Insert a copy of RSI code for 2 or more button values
```

```
    type = 0
    if CW_FORM_PARSE(e, 'SET_VALUE', temp) then begin
      result = execute('sval=fix('+temp+')')
      new = CW_BGROUPE(parent, strtok(a[2], '|', /EXTRACT), $
        EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
        FRAME=frame, NO_RELEASE = no_release, $
        SET_VALUE = sval, _EXTRA=extra)
    endif else begin
      new = CW_BGROUPE(parent, strtok(a[2], '|', /EXTRACT), $
        EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
        FRAME=frame, NO_RELEASE = no_release, _EXTRA=extra)
```

```
endelse
WIDGET_CONTROL, new, GET_VALUE=value

endelse
```

Andrew D. Cool
Electromagnetics & Propagation Group
Intelligence, Surveillance & Reconnaissance Division
Defence Science & Technology Organisation
PO Box 1500, Edinburgh
South Australia 5111

Phone : 061 8 8259 5740 Fax : 061 8 8259 6673
Email : andrew.cool@no-spam.dsto.defence.gov.au

Subject: Re: sec : U Re: problem with checkbox in cw_form
Posted by [Sergey Koposov](#) on Tue, 29 Apr 2003 20:47:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

Andrew, Great thanks for the idea and for the example.

Cheers,

Sergey K

Andrew Cool wrote:

> Sergey Koposov wrote:

>

>> Hello!

>> Because, this widget is used in very complicated program, and it would
>> be nice if the values of some parameters entered by user were obtained
>> with single cw_form (it is more simple to get the states of fields with
>> using cw_form then standart widget construction).

>> Moreover, I don't believe that it is impossible to make a single
>> checkbox in cw_form. It would be very strange , I think. :)

>> Cheers,

>> Sergey K

>>

>> Pavel Romashkin wrote:

>>

>>> Why not create the single checkbox in a separate exclusive base, not as
>>> part of cw_form?

>>>

>>> Cheers,

>>> Pavel

>>>

>>> "iċ^{1/2}xīċ^{1/2}iċ^{1/2}iċ^{1/2}" wrote:

```

>>>
>>>
>>>> Can somebody tell me how to create only one checkbox in the cw_form. I dont
>>>> how to do this, because , by default, if there is only one item in the
>>>> initial value field (in the parameters of cw_form) IDL create a simple
>>>> button, but no the checkbox.
>>>> Thanks,
>>>>     Sergey Koposov
>
>
>
> Sergey,
>
> CW_FORM is available as a .PRO file in your IDL disribution,
> e.g. look for C:\RSI\IDL56\LIB\CW_FORM.PRO.
>
> CW_FORM.PRO is hardwired to produce single "standard" button if
> you only supply 1 value.
>
> But there's no reason why you can't take a copy of RSI's CW_FORM.PRO
> and put it into your own IDL path, preferably sensibly renamed.
>
> Below I've take a brute force approach and just copied the code for
> multiple buttons into the area for a singel button. It works nicely,
> producing a single checked button.
>
> You might wish to make a more sensitive amendment to the code ;- )
>
> Cheers,
>
> Andrew
>
>
> 'BUTTON': BEGIN
>   CW_FORM_APPEND, extra, e, 'LABEL_LEFT', /USE_VALUE
>   CW_FORM_APPEND, extra, e, 'LABEL_TOP', /USE_VALUE
>   exclusive = CW_FORM_PARSE(e, 'EXCLUSIVE')
>   no_release = CW_FORM_PARSE(e, 'NO_RELEASE')
>   values = strtok(a[2], '|', /EXTRACT, ESC='\')
>
>   if n_elements(values) ge 2 then begin
>     type = 0
>     if CW_FORM_PARSE(e, 'SET_VALUE', temp) then begin
>       result = execute('sval=fix('+temp+')')
>       new = CW_BGROUPO(parent, strtok(a[2], '|', /EXTRACT), $
>       EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
>       FRAME=frame, NO_RELEASE = no_release, $
>       SET_VALUE = sval, _EXTRA=extra)

```

```

>     endif else begin
>         new = CW_BGROUP(parent, strtok(a[2], '|', /EXTRACT), $
>         EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
>         FRAME=frame, NO_RELEASE = no_release, _EXTRA=extra)
>     endelse
>     WIDGET_CONTROL, new, GET_VALUE=value
> endif else begin
> ;A.D. Cool Comment out original RSI code for 1 button value
>     ; type = 2
> ;new = WIDGET_BUTTON(parent, value=values[0], FRAME=frame,
> _EXTRA=extra)
> ;value = 0L
>
> ;A.D. Cool Insert a copy of RSI code for 2 or more button values
>
>     type = 0
>     if CW_FORM_PARSE(e, 'SET_VALUE', temp) then begin
>         result = execute('sval=fix('+temp+')')
>         new = CW_BGROUP(parent, strtok(a[2], '|', /EXTRACT), $
>         EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
>         FRAME=frame, NO_RELEASE = no_release, $
>             SET_VALUE = sval, _EXTRA=extra)
>     endif else begin
>         new = CW_BGROUP(parent, strtok(a[2], '|', /EXTRACT), $
>         EXCLUSIVE = exclusive, NONEXCLUSIVE = 1-exclusive, $
>         FRAME=frame, NO_RELEASE = no_release, _EXTRA=extra)
>     endelse
>     WIDGET_CONTROL, new, GET_VALUE=value
>
> endelse
>
>
> -----
> Andrew D. Cool
> Electromagnetics & Propagation Group
> Intelligence, Surveillance & Reconnaissance Division
> Defence Science & Technology Organisation
> PO Box 1500, Edinburgh
> South Australia 5111
>
> Phone : 061 8 8259 5740   Fax : 061 8 8259 6673
> Email  : andrew.cool@no-spam.dsto.defence.gov.au
> -----

```
