
Subject: Re: Theoretical Programmers Wanted

Posted by [David Fanning](#) on Wed, 08 Oct 2003 01:24:12 GMT

[View Forum Message](#) <> [Reply to Message](#)

David Fanning writes:

```
> Now, here is another file, very similar to the first.
>
> PRO Test2
>   tlb = Widget_Base(Column=1, XOffset=200, YOffset=100)
>   label = Widget_Label(tlb, Value='000', XSize=100, /Align_Center)
>   Widget_Control, tlb, /Realize, Set_UValue=label
>   XManager, 'test2', tlb, /No_Block
>   FOR j=0,49 DO BEGIN
>     Widget_Control, label, Set_Value=String(j,format='(I3.3)')
>     Wait, 0.1
>   ENDFOR
>   Widget_Control, tlb, /Destroy
> END
>
> When you run it, a graphical user interface appears and the
> label counts up to 49. Perfect! But now you make a save file
> out of this:
>
> IDL> .compile test2
> IDL> Resolve_All
> IDL> Save, File='test2.sav', /Routines
>
> When you quit IDL and double click the save file, you get
> the label appearing in the top-level base, but no count up
> on the label. It stays stuck at 000. :-(
>
> Here's my theoretical question: Why?
```

Note that if I comment out the XManager call, TEST2 works perfectly as a save file. I actually think I understand this whole business in the sort of fuzzy, beer-blurry way that you understand the waitress taking your order is in love with you. But I'm just finding it hard to explain it to others. Perhaps I need fresh words. :-)

Cheers,

David

--

David W. Fanning, Ph.D.
Fanning Software Consulting, Inc.

Subject: Re: Theoretical Programmers Wanted
Posted by [Chris Lee](#) on Wed, 08 Oct 2003 08:24:47 GMT
[View Forum Message](#) <> [Reply to Message](#)

In article <MPG.19ed1529cceabfd989704@news.frii.com>, "David Fanning"
<david@dfanning.com> wrote:

```
> David Fanning writes:
>
>> Now, here is another file, very similar to the first.
>> PRO Test2
>>   tlb = Widget_Base(Column=1, XOffset=200, YOffset=100) label =
>>   Widget_Label(tlb, Value='000', XSize=100, /Align_Center)
>>   Widget_Control, tlb, /Realize, Set_UValue=label XManager,
>>   'test2', tlb, /No_Block
>>   FOR j=0,49 DO BEGIN
>>     Widget_Control, label, Set_Value=String(j,format='(I3.3)')
>>     Wait, 0.1
>>   ENDFOR
>>   Widget_Control, tlb, /Destroy
>> END
>> When you run it, a graphical user interface appears and the label
>> counts up to 49. Perfect! But now you make a save file out of this:
>>
>> IDL> .compile test2
>> IDL> Resolve_All
>> IDL> Save, File='test2.sav', /Routines
>> When you quit IDL and double click the save file, you get the label
>> appearing in the top-level base, but no count up on the label. It stays
>> stuck at 000. :-( Here's my theoretical question: Why?
> Note that if I comment out the XManager call, TEST2 works perfectly as a
> save file. I actually think I understand this whole business in the sort
> of fuzzy, beer-blurry way that you understand the waitress taking your
> order is in love with you. But I'm just finding it hard to explain it to
> others. Perhaps I need fresh words. :-)
> Cheers,
> David
>
```

Not being able to double-click to run the save file (Linux) I may be missing something, but the save file works if it is restored from within IDL for me, with or without the call to XManager.

Could it be the /no_block keyword that's stopping it counting when you double-click to run it?

Chris.
