
Subject: Re: Bug in WHERE_ARRAY.PRO
Posted by [steale](#) on Mon, 01 Aug 1994 15:15:46 GMT
[View Forum Message](#) <> [Reply to Message](#)

Via e-mail, stl@maz.sma.ch (Stephen Strebel) wrote:

> darn, my news server has problems. Below is a copy of the fixed
> function. Could you please do me a favour and post this to the net, I
> will be away on vacation after today. thanks a bunch,

```
;
;
;+
; NAME:
; where_array.pro
;
; PURPOSE:
; Return the indices of where vector B exists in vector A.
; Basically a where(B eq A) where B and A are 1 dimensional arrays.
;
;
; CATEGORY:
;   Array
;
; CALLING SEQUENCE:
; result = where_array(A,B)
;
; INPUTS:
; A vector that might contain elements of vector B
; B vector that we would like to know which of its
;   elements exist in A
;
; OPTIONAL INPUTS:
;
; KEYWORD PARAMETERS:
; iA_in_B return instead the indices of A that are in
;   (exist) in B
;
; OUTPUTS:
; Index into B of elements found in vector A. If no
; matches are found -1 is returned. If the function is called
; with incorrect arguments, a warning is displayed, and -2 is
; returned (see side effects for more info)
;
; OPTIONAL OUTPUTS:
;
; COMMON BLOCKS:
; None
;
```

```

; SIDE EFFECTS:
; If the function is called incorrectly, a message is displayed
; to the screen, and the !ERR_STRING is set to the warning
; message. No error code is set, because the program returns
; -2 already
;
;
; RESTRICTIONS:
; This should be used with only Vectors. Matrices other than
; vectors will result in -2 being returned. Also, A and B must
; be defined, and must not be strings!
;
;
;
; PROCEDURE:
;
;
; EXAMPLE:
; IDL> A=[2,1,3,5,3,8,2,5]
; IDL> B=[3,4,2,8,7,8]
; IDL> result = where_array(a,b)
; IDL> print,result
;
;
; SEE ALSO:
; where
;
;
; MODIFICATION HISTORY:
; Written by: Dan Carr at RSI (command line version) 2/6/94
; Stephen Strebel 3/6/94
; made into a function, but really DAN did all
; the thinking on this one!
; Stephen Strebel 6/6/94
; Changed method, because died with Strings (etc)
; Used ideas from Dave Landers. Fast TOO!
; Strebel 30/7/94
; fixed checking structure check
;
;
;-
FUNCTION where_array,A,B,IA_IN_B=ia_in_B

; Check for: correct number of parameters
; that A and B have each only 1 dimension
; that A and B are defined
if (n_params() ne 2 or (size(A))(0) ne 1 or (size(B))(0) ne 1 $
or n_elements(A) eq 0 or n_elements(B) eq 0) then begin
message,'Improper parameters',/Continue
message,'Usage: result = where_array(A,B,[IA_IN_B=ia_in_b]',/Continue
return,-2
endif

;parameters exist, lets make sure they are not structures

```

```

if ((size(A))((size(A))(0)+1) eq 8 or $
(size(B))((size(B))(0)+1) eq 8) then begin
message,'Improper parametrs',/Continue
message,'Parameters cannot be of type Structure',/Continue
return,-2
endif

```

```

; build two matrices to compare
Na = n_elements(a)
Nb = n_elements(b)
I = lindgen(Na,Nb)
AA = A(I mod Na)
BB = B(I / Na)

```

```

;compare the two matrices we just created
I = where(AA eq BB)
Ia = i mod Na
Ib = i / na

```

```

; normally (without keyword, return index of B that
; exist in A
if keyword_set(iA_in_B) then index = Ia $
else index = Ib

```

```

;make sure a valid value was found
if Ia(0) eq -1 or Ib(0) eq -1 then index = -1

```

```

return,index

```

```

END

```

```

--

```

David Steele | Internet : steele@wesson.phys.ucalgary.ca

Department of Physics and Astronomy | SPAN : CANCEL::STEELE

The University of Calgary | Phone : +1 403 220 8651

OPINIONS EXPRESSED WITHIN ARE MY OWN AND NOT THOSE OF THE UNIVERSITY OF
CALGARY