Subject: Re: find boundary routine Posted by btt on Thu, 18 Mar 2004 22:47:40 GMT

View Forum Message <> Reply to Message

Brian Frizzelle wrote:

```
> Let me apologize if this post is a bit lengthy. And in case it's
> important, I'm using IDL 6.0 on a Windows machine.
>
> I need help calculating the perimeters of regions. I have an input
> array of roughly 900 by 1200 cells which contains 15 different
> categories (coded 1 through 15). For each category, I need to find the
> total perimeter length among all of its regions.
>
> I found David Fanning's FIND_BOUNDARY routine and ran it on this
> array, but it seemed to stop at the first region that it found. So I
> wrote a script that subsetted each array first by category, then by
> region within the category (regions were created with LABEL_REGION).
> Running FIND BOUNDARY again, I got an output for each category, but
> the numbers seemed off.
>
> So I resorted to creating a simple 5x5 array with two categories, one
> region each, to test the perimeter output of FIND_BOUNDARY.
> - Category 1 has 16 cells and a perimeter of 18.
> - Category 2 has 9 cells and a perimeter of 18.
> * FIND_BOUNDARY output a perimeter of 2 for each category.
> * FIND_BOUNDARY also only give me an output array with 2 X/Y
> coordinates.
>
> Has anyone else found this to be a problem? Maybe I'm passing in the
> wrong parameters. Here are the details of what I've done so far. Any
> help would be greatly appreciated.
>
 Brian Frizzelle
>
> arrayTest: regCat1: regCat2:
> 11122 11100 00011
> 11122 11100 00011
> 11112
           11110
                       00001
> 11222 11000 00111
>
> IDL> bndry = find_boundary(regCat1, XSize=5, YSize=5, Perimeter=perim)
> IDL> print, perim
```

2.0000000 > IDL> print, bndry

```
> 0 0 > 0 1
```

Hello,

I think David's FIND_BOUNDARY is looking for the 1-dimensional subscripts of the 'blob' within the image. Try...

```
index = where(arrayTest EQ 1, cnt)
If cnt GT 0 Then $
  bndry = find_boundary(index, XSize=5, YSize=5, Perimeter=perim) else
  bndry = -1
```

Be careful using LABEL_REGION, it assign features that lie along the image edge to the background.

Ben Ben

Subject: Re: find_boundary routine
Posted by David Fanning on Fri, 19 Mar 2004 02:47:39 GMT
View Forum Message <> Reply to Message

Brian Frizzelle writes:

- > Let me apologize if this post is a bit lengthy. And in case it's
- > important, I'm using IDL 6.0 on a Windows machine.

>

- > I need help calculating the perimeters of regions. I have an input
- > array of roughly 900 by 1200 cells which contains 15 different
- > categories (coded 1 through 15). For each category, I need to find the
- > total perimeter length among all of its regions.

>

- > I found David Fanning's FIND_BOUNDARY routine and ran it on this
- > array, but it seemed to stop at the first region that it found. So I
- > wrote a script that subsetted each array first by category, then by
- > region within the category (regions were created with LABEL_REGION).
- > Running FIND_BOUNDARY again, I got an output for each category, but
- > the numbers seemed off.

>

- > So I resorted to creating a simple 5x5 array with two categories, one
- > region each, to test the perimeter output of FIND_BOUNDARY.
- > Category 1 has 16 cells and a perimeter of 18.
- > Category 2 has 9 cells and a perimeter of 18.
- > * FIND_BOUNDARY output a perimeter of 2 for each category.

- > * FIND BOUNDARY also only give me an output array with 2 X/Y
- > coordinates.

>

- > Has anyone else found this to be a problem? Maybe I'm passing in the
- > wrong parameters. Here are the details of what I've done so far. Any
- > help would be greatly appreciated.

Here is an example of a 5 by 5 array, with the middle 9 pixels making up the region:

```
IDL> array=[[0,0,0,0,0],[0,1,1,1,0],[0,1,1,1,0],[0,1,1,1,0],[0,0, 0,0,0]] IDL>indices = Where(array GT 0) IDL>pts = Find_Boundary(indices, XSize=5, YSize=5, Perimeter=p) IDL>Print, p
8.0
```

I had to make a small change to the Find_Boundary to accommodate this few a number of indices. I had to change line 316 from this:

```
boundaryPts = IntArr(2, Long(xsize) * ysize / 4L)
```

To this:

```
boundaryPts = IntArr(2, Long(xsize) * ysize / 2L)
```

You might think the correct "perimeter" would be 9 in this case, but you have to remember that the algorithm is calculating from the center of each pixel. A quick sketch of these 9 pixels and their centers will convince you that the correct answer is 8.

Other combinations of pixels in my tests gave similar correct results. I think the algorithm is working properly.

Cheers,

David

--

David W. Fanning, Ph.D. Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.dfanning.com/Phone: 970-221-0438, IDL Book Orders: 1-888-461-0155

Subject: Re: find_boundary routine

Posted by brian frizzelle on Wed, 24 Mar 2004 18:29:01 GMT

View Forum Message <> Reply to Message

David and Ben,

Thanks for the assistance. I now understand how David's routine works, and it attacks this perimeter problem in a different manner than what I needed. So I wrote a different routine which will calculate the boundary of a region in an array, as long as all cells in the region are coded with a 1.

The reason that the FIND_BOUNDARY routine didn't work for me is that I needed to calculate the perimeters from the pixel corners rather than the centers. So a one-pixel region should have a perimeter of 4, and a 2-by-2 region should have a perimeter of 8. In your routine, the one-pixel region's perimeter would be 0, and the 2x2 pixel region's perimeter would be 1.

If anyone is interested, I can post my code.

Brian