
Subject: Re: array dimensions and subscripts
Posted by [Craig Markwardt](#) on Tue, 27 Apr 2004 15:06:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

Benjamin Hornberger <benjamin.hornberger@stonybrook.edu> writes:

> Hi all,
>
> I have a 3d data array A (n_columns, n_rows, n_data) where columns and
> rows make up an image and for each pixel in the image I recorded n_data
> different data values.
>
> Then I have a 1d array B with n_data entries, and I want to subtract B
> from A such that for each element in A, the element from B in the
> corresponding data channel is subtracted. Obviously, A-B won't work. I

This has been covered several times. A good place to start is JD's
dimension juggling tutorial
(http://www.dfanning.com/tips/rebin_magic.html).

REBIN/REFORM, which is what you would need to do, is easy enough.
However, it is also straightforward to use a FOR loop. In my own
opinion, if you can do enough subtractions in a single FOR loop
iteration, then it will be fast.

At that stage, it's up to you to decide which method is more elegant
and maintainable.

Craig

--

Craig B. Markwardt, Ph.D. EMAIL: craigmnet@REMOVEcow.physics.wisc.edu
Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response

Subject: Re: array dimensions and subscripts
Posted by [David Fanning](#) on Tue, 27 Apr 2004 15:07:18 GMT
[View Forum Message](#) <> [Reply to Message](#)

Benjamin Hornberger writes:

> I have a 3d data array A (n_columns, n_rows, n_data) where columns and
> rows make up an image and for each pixel in the image I recorded n_data
> different data values.
>
> Then I have a 1d array B with n_data entries, and I want to subtract B

> from A such that for each element in A, the element from B in the
> corresponding data channel is subtracted. Obviously, A-B won't work. I
> can imagine two ways:
>
> 1. For loop
>
> result = fltarr(n_columns, n_rows, n_data) ;; initialize
> for i=0, n_data-1 do results[:, *, i] = A[:, *, i] - B[i]
>
> 2. Blowing up B to 3d (which I can't manage to do without a for loop
> either)
>
> B1 = fltarr(n_column, n_rows, n_data)
> for i=0, n_data-1 do B1[:, *, i] = B[i]
> result = A - B1
>
> But these solutions don't seem very elegant and efficient to me. Is
> there any way to make it work with a single array operation using the *
> subscript, or something similar?

While you are waiting for an answer, I'd browse the Dimensional
Juggling Tutorial. I have a feeling it is going to be mentioned
somewhere in the answer. :-)

http://www.dfanning.com/tips/rebin_magic.html

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>