
Subject: Re: reading registry on windows system
Posted by [Karsten Rodenacker](#) on Fri, 12 Nov 2004 10:52:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

Maybe getenv(/environment) gives, what you are looking for.

Regards

Karsten

On 12 Nov 2004 02:06:49 -0800, Michael Wiekenberg <norford@gmx.de> wrote:

> Hello everyone,
>
> i'am surching for a posibility to read a key value out of the
> registry.
> My Problem:
> I'd like to save files in a standard path. this is on a unix system
> '~/myprog/'
>
> on a windows system it should be the myprog dir in the personal dir of
> user which is setted in
> HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\ Explorer\Shell
> Folders\personal
>
> But how can i read the value of that key to use it in IDL?
>
> Or exists a better methode to get the user dir?
>
> Thanks fpr reading and maybe for thinking about!
> Would be happy about some suggestions or resolutions :]

--

Karsten Rodenacker

----- :-)

GSF - Forschungszentrum Institute of Biomathematics and Biometry

D-85758 Oberschleissheim Postfach 11 29

Karsten.Rodenacker@gsf.de | <http://ibb.gsf.de/> | DEL _ for reply

<http://ibb.gsf.de/homepage/karsten.rodenacker/>

Tel: +49 89 31873401 | FAX: ..3369

Subject: Re: reading registry on windows system
Posted by [Ralf Schaa](#) on Fri, 12 Nov 2004 15:36:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

Michael Wiekenberg wrote:

> Hello everyone,

>
> i'am surching for a posibility to read a key value out of the
> registry.
> My Problem:
> I'd like to save files in a standard path. this is on a unix system
> '~/myprog/'
>
> on a windows system it should be the myprog dir in the personal dir of
> user which is setted in
> HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\ Explorer\Shell
> Folders\personal
>
> But how can i read the value of that key to use it in IDL?
>
> Or exists a better methode to get the user dir?
>
> Thanks fpr reading and maybe for thinking about!
> Would be happy about some suggestions or resolutions :]

since I like perl in combination with spawn, I suggest:
Win32::Registry::File - Perl interface to MS-Windows registry files

cheers
-ralf

Subject: Re: reading regestry on windows system
Posted by [Rick Towler](#) on Fri, 12 Nov 2004 19:51:12 GMT
[View Forum Message](#) <> [Reply to Message](#)

Michael Wiekenberg wrote:

> Hello everyone,
>
> i'am surching for a posibility to read a key value out of the
> registry.

<snip>

> But how can i read the value of that key to use it in IDL?
>
> Or exists a better methode to get the user dir?

Not that this is the easiest way but this would be a very simple .dln to write. With Ronn Kling's "Calling C from IDL" it would probably only take you a few hours, even if you are a C novice. For hints, you can check out my directInput.dln. It contains an couple of unrelated functions to get system metrics. you could chop out all of the

directInput stuff and use these as starting points.

On the windows side there are a number of ways to set/get keys. The Win32 api would probably be easiest if you are unfamiliar with MFC.

<http://www.acoustics.washington.edu/~towler/programs/directInputSource.zip>

If you get this up and running, please share! :)

-Rick

Subject: Re: reading registry on windows system
Posted by [Mark Hadfield](#) on Fri, 12 Nov 2004 21:51:57 GMT
[View Forum Message](#) <> [Reply to Message](#)

Michael Wiekenberg wrote:

- > Hello everyone,
- >
- > i'am surching for a posibility to read a key value out of the
- > registry.
- > My Problem:
- > I'd like to save files in a standard path. this is on a unix system
- > '~/myprog/'
- >
- > on a windows system it should be the myprog dir in the personal dir of
- > user which is setted in
- > HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\ Explorer\Shell
- > Folders\personal

On my system that key has the value

D:\Documents and Settings\Hadfield\My Documents

It seems odd to put programs in a "documents" directory. I should think a more suitable location (and a better match to ~/myprog/ on Unix) is one level up, ie

D:\Documents and Settings\Hadfield

On my system the latter directory is available as an environment variable, USERPROFILE. It would be easier to access an environment variable than to read the registry.

This is a Windows 2000 system--I don't know about Windows 9x.

You may also be interested in how IDL addresses this issue. The documentation says the following under environment variables:

HOME

IDL uses the value of the \$HOME environment variable when storing user-specific information in the local file system.

Note

Under Microsoft Windows, the HOME environment variable may not be set in all cases. If it is not set, IDL first attempts to substitute the USERPROFILE environment variable (which usually looks something like C:\Documents and Settings\username where username is the login name of the current user). If USERPROFILE is not set, IDL uses the value of the first of the following it finds: the TEMP environment variable, the TMP environment variable, the Windows system directory.

Finally, note that in IDL 6.1 the APP_USER_DIR and APP_USER_DIR_QUERY functions were added to support storage of user-specific info.

--

Mark Hadfield "Ka puwaha te tai nei, Hoesa tatou"
m.hadfield@niwa.co.nz
National Institute for Water and Atmospheric Research (NIWA)

Subject: Re: reading registry on windows system
Posted by [norford](#) on Tue, 16 Nov 2004 14:41:48 GMT
[View Forum Message](#) <> [Reply to Message](#)

Thank you all for help.

i'am use the following solution:
path=GETENV('USERPROFILE')+...
