## Subject: Re: where and NAN numbers Posted by maarten on Wed, 12 Jan 2005 12:08:32 GMT View Forum Message <> Reply to Message What version are you using, because in 6.1.1. the results are: IDL> u = [!values.f\_nan, 1, 2, 3] IDL> print, where(u eq 3) 3 IDL> print, where(u ge 3) 3 euskalmet07@ej-gv.es wrote: > Hi dear IDL user, > Maybe my question is too obvious, but I canī¿½t guess the response. > Having the vector: > IDL> u = [!values.f\_nan, 1, 2, 3] > why is different the resulting vector in these following two WHERE functions? > IDL> print, where(u eq 3) > 0 3 > % Program caused arithmetic error: Floating illegal operand

Subject: Re: where and NAN numbers
Posted by Haje Korth on Wed, 12 Jan 2005 14:24:28 GMT
View Forum Message <> Reply to Message

% Program caused arithmetic error: Floating illegal operand

Use finite function to pre-filter for nans.

> Any response would be appreciated.

> IDL> print, where(u ge 3)

```
<euskalmet07@ej-gv.es> wrote in message
news:36519195.0501120402.5de60fc0@posting.google.com...
> Hi dear IDL user,
>
```

```
Having the vector:
IDL> u = [!values.f_nan, 1, 2, 3]
why is different the resulting vector in these following two WHERE functions?
IDL> print, where(u eq 3)
0 3
% Program caused arithmetic error: Floating illegal operand
IDL> print, where(u ge 3)
IDL> print, where(u ge 3)
% Program caused arithmetic error: Floating illegal operand
% Program caused arithmetic error: Floating illegal operand
Any response would be appreciated.
```

Subject: Re: where and NAN numbers
Posted by Mark Hadfield on Wed, 12 Jan 2005 23:16:46 GMT
View Forum Message <> Reply to Message

## maarten wrote:

What version are you using, because in 6.1.1. the results are:
IDL> u = [!values.f\_nan, 1, 2, 3]
IDL> print, where(u eq 3)
3
IDL> print, where(u ge 3)
3

The result of a comparison operation between a NaN and an "ordinary" number will depend on the platform. (At least I vaguely recall some dicussion of this somewhere, perhaps this group or perhaps another one.) It is not wise to rely on getting logically consistent results. For example on IDL 6.1.1 (win32), NaN is not equal to 0 (according to the EQ and NE operators) but it is neither larger or smaller than 0 (according to the LT and GT operators). So, as another poster has suggested, it is good practice to use the FINITE function to establish whether a floating point number is finite; if it's not the results from comparison operations will likely be misleading.

Mark Hadfield "Ka puwaha te tai nei, Hoea tatou" m.hadfield@niwa.co.nz
National Institute for Water and Atmospheric Research (NIWA)