Subject: Re: Need ideas for a data structure Posted by steinhh on Thu, 03 Nov 1994 11:04:42 GMT

View Forum Message <> Reply to Message

In article <3992q9\$2pp@aplcomm.jhuapl.edu>, CroucAR1@subtech1.spacenet.jhuapl.edu writes:

|>

- > I'm trying to devise a way of dealing with a bunch of data items which will
- > consist of a fixed number of header fields and a widely varying number of data
- > entries. For one such item, an anonymous structure seems appropriate, but I
- > don't see how I can generalize this to an array.

|>

- |> If I define an array of structures based on the largest array (which I won't
- |> know ahead of time anyway), I'll waste a huge amount of memory.

|>

- > I thought of building an array of pointers to anonymous structures, but the
- > structures seem too anonymous for this to work.


|> [..]

|> PS: I'm bi - it needs to work with both IDL and PV-Wave

I was just about to propose IDL handles, but then I saw your PS, which makes it slightly more difficult.

But despair not! The solution is to do your own memory management --I know it's not pretty, nor very efficient, but it works!

I gather that you have a data structure that could be represented by the following "conglomerate":



and you'd like to store an array of such data conglomerate.

The fixed info is easily put into an array, with two tags, "start" and "length", in addition to those representing fixed data.

Assuming that each "Entry" is of the same data type -- this is crucial -create a global (common block) array of, say, a thousand entries, and associate with it a global counter Nused (initialized to zero), keeping track of how much of the array that's in use.

Now, each time you need a new conglomerate data sturcture, create the

Fixed info part. You ought to know by this time how many entries are needed, so initialize the "start" tag in the fixed info with the current value of "Nused", and increase Nused with the number of entriest that are reserved for the new data conglomerate.

If the entries are also variable, you need to go one step further down into the data structure, and implement the same idea there...

Stein Vidar

Subject: Re: Need ideas for a data structure Posted by mark_cadwell on Sat, 05 Nov 1994 01:22:34 GMT View Forum Message <> Reply to Message

I don't know about IDL, but in PV-Wave I created a flexable record type that works similarly to what you describe.

There is a set of non-changing header elements with things like titles, axes annotation, data start and stop times, etc. There is also an element that contains the size of the data arrays that follow. The file is opened and read into PV-Wave with a READU function call. You have to create a data structure in which to put the stuff you read. You can define one data structure that has everything up to and including the element that tells you array sizes.

Once you have that information, use it to create a second data structure that has all the header stuff AND arrays of the proper size. Rewind the data file with the function "POINT_LUN, UNIT, 0". This sets the I/O pointer back to the beginning of your file so you can read it again (this time with your data arrays).

It may not be the most elegant solution, but it has worked very well for me. The only thing you have to look out for is that the data arrays must start on a fullword boundry. If you need to, you can pad your data structures with a few empty bytes to get to the fullword boundry.

-------mark_cadwell@qmail4.trw.sp.com