
Subject: Re: Multiple Spawn Commands
Posted by [Jo Klein](#) on Fri, 14 Jul 2006 16:16:57 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Ryan,
I'm not sure I understand what you're trying to do - if you simply want multiple commands to be executed in the same UNIX shell, you can simply separate them with semicolons such as
mystring='ls; echo Hoorah! A listing!'
spawn,mystring
Similarly, in a bash environment, you could do
mystring='foreach f in 1 2 3; do echo \$f; done'
and spawn it. I'm sure you can derive the csh syntax from here.
Hope this helps,
Jo

Subject: Re: Multiple Spawn Commands
Posted by [Ryan.](#) on Fri, 14 Jul 2006 16:43:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

Jo,
Thank you for your response, that is going to make my life a lot easier but i can't seem to get it work properly in a UNIX environment. How do you write a foreach loop in a UNIX environment in one line? I have experimented a bit with it but it keeps complaining to me about misplace brackets, what is the proper syntax?

Thanks again,
Ryan.

Subject: Re: Multiple Spawn Commands
Posted by [Maarten Sneep](#) on Fri, 14 Jul 2006 18:27:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

In article <1152895388.545979.198960@75g2000cwc.googlegroups.com>,
"Ryan." <rchughes@brutus.uwaterloo.ca> wrote:

> Jo,
> Thank you for your response, that is going to make my life a lot easier
> but i can't seem to get it work properly in a UNIX environment. How do
> you write a foreach loop in a UNIX environment in one line? I have
> experimented a bit with it but it keeps complaining to me about
> misplace brackets, what is the proper syntax?

What is your shell:

spawn, "echo \$SHELL"
should tell. Because of the syntax you use in your original post, I think you're using a csh derivative. It has been a while, but I think a foreach loop looks like:

```
spawn, "foreach i (item1 item2 item3); action $i; end"
```

An O'Reilly book on shells will help you here, but often it is easier, and more portable, to perform the action in IDL.

If all fails:

```
for ii=0,n_elements(files)-1 do $  
  spawn, "file_dump.ps " + files[ii]
```

(yeah, I know, lots of overhead, not pretty, but at least it'll work.)

Maarten

--

A: Because it messes up the order in which people normally read text.

Q: Why is top-posting such a bad thing?

A: Top-posting.

Q: What is the most annoying thing on usenet?

Subject: Re: Multiple Spawn Commands

Posted by [Jo Klein](#) on Tue, 18 Jul 2006 11:04:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Ryan,

I notice you've gone for the IDL loop option, which is probably more portable, so just for the record: This is the way you can do it in a UNIX environment if you're running bash or sh. I just checked the doc, csh and tcsh do not allow the use of a semicolon to delimit commands. To make my one line solution work, you would have to switch to a bash environment before starting IDL, such as

```
> bash
```

```
> idl
```

Cheers,

Jo
