Subject: Re: Altered device coordinates after first call Posted by David Fanning on Mon, 16 Oct 2006 16:24:16 GMT

View Forum Message <> Reply to Message

Juan Arrieta writes:

- > Please have a look at my code, the data is of course fictitious, but
- > the general idea is to produce a nice looking letter-size output. If
- > you want to see the PS, uncomment the corresponding lines. The code as
- > it is will produce a direct graphics plot.

In the example code, you have a NOERASE on the PLOT command. Do you have this keyword on the real plots in your original code? If so, I would remove it and see if things go better for you. :-)

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Altered device coordinates after first call Posted by David Fanning on Mon, 16 Oct 2006 16:36:42 GMT View Forum Message <> Reply to Message

Juan Arrieta writes:

- > Please have a look at my code, the data is of course fictitious, but
- > the general idea is to produce a nice looking letter-size output. If
- > you want to see the PS, uncomment the corresponding lines. The code as
- > it is will produce a direct graphics plot.

Humm. Well, there is a LOT going wrong in this code. :-)

The main thing is that you are drawing graphics in DATA coordinates, but you haven't established a DATA coordinate system in the code. So it's using the *last* one that did get established, which could be anything at all. That's why you can't reproduce anything.

It looks to me like you want to draw graphics in a NORMAL (normalized) coordinate system. If so, you will need to set a NORMAL keyword on all your PLOTS and XYOUTS commands.

I would also draw the plots *first*, then put all the annotation on the plots. It is the NOERASE keyword on your PLOT commands that I think is really screwing you up here. I see why you want to do it, since all your annotation disappears when the first plot is drawn, but it plays absolute havoc with your data coordinate system.

Cheers,

David

--

David Fanning, Ph.D. Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Altered device coordinates after first call Posted by David Fanning on Mon, 16 Oct 2006 16:41:29 GMT View Forum Message <> Reply to Message

David Fanning writes:

> Humm. Well, there is a LOT going wrong in this code. :-)

This gets you closer to where you want to be, although you are still drawing the logo off the page! :-)

Cheers,

David

PRO TSTDIAGRAM

; EXAMPLE FOR TESTING THE OUTPUT IN A LETTER-SIZE DEVICE (8.5X11)

; SET THE DEVICE (8.5X11IN PAPER (LANDSCAPE), WITH ONE INCH MARGINS) thisDevice = !D.NAME ;SET_PLOT,'PS'

;DEVICE,/INCHES,FILENAME='TST.ps',XSIZE=9.0,YSIZE=6.5,/LANDSCAPE,XOFFSET=1.0,YOFFSET=10.0

;;; THE REST OF THE CODE IS WHERE I WOULD BE ADDING MY PLOTS

!Y.OMARGIN = [3.5,3.5] !P.MULTI=[0,3,2] FOR J = 0,5 DO PLOT, FINDGEN(10), noerase=(j EQ 0)

```
: EDGE COORDINATES
X0 = 0.0
X1 = 1.0
Y0 = 0.0
Y1 = 1.0
: BOX
PLOTS,[0,0],[0,1], /NORMAL
PLOTS,[0,1],[1,1], /NORMAL
PLOTS,[1,1],[1,0], /NORMAL
PLOTS.[1.0].[0.0]. /NORMAL
; HEADER AND FOOTER
PLOTS,[0,1],[0.95,0.95], /NORMAL
PLOTS,[0,1],[0.05,0.05], /NORMAL
: HEADER AND FOOTER BINS
PLOTS,[0.25,0.25],[1.0,0.95], /NORMAL: SECOND HEADER BIN
PLOTS,[0.50,0.50],[1.0,0.95], /NORMAL; THIRD HEADER BIN
PLOTS,[0.75,0.75],[1.0,0.95], /NORMAL; FOURTH HEADER BIN
PLOTS,[0.25,0.25],[0.0,0.05], /NORMAL; SECOND FOOTER BIN
PLOTS,[0.50,0.50],[0.0,0.05], /NORMAL; THIRD FOOTER BIN
PLOTS,[0.75,0.75],[0.0,0.05], /NORMAL; FOURTH FOOTER BIN
: NASA LOGO AND "PREPARED BY" STRING
NASA = '!10nasa!N!X'
XYOUTS,0,-0.05,NASA,SIZE=2, /NORMAL
XYOUTS,1,-0.05, Prepared by J. J. Arrieta-Camacho', ALIGN=1.0, /NORMAL
: TITLE
XYOUTS,0.5,1.025, 'December 18, 2018', ALIGN=0.5, SIZE=2.5, /NORMAL
: EARTH, MOON, AND OTHER SYMBOLS
EARTH = '!20S!N!X'
MOON = '!20V!N!X'
EQUINOX = '!20x!N!X'
DELTA = '!4D!N!X'
RAAN = '!4X!N!X'
TRAN = '!4x!N!X'
; DIRECTION OF MANEUVER (EARTH-MOON OR MOON-EARTH) PLACED IN THE FIRST
; HEADER BIN
STR = 'Maneuver: '+EARTH+' - '+MOON
XYOUTS,(0.25-0.0)/2.0,0.965,STR,ALIGN=0.5,CHARSIZE=1.5, /NORMAL
: TYPE OF MANEUVER
STR = 'Ballistic (TLI)'
```

XYOUTS,0.25+(0.5-0.25)/2.0,0.965,STR,ALIGN=0.5,CHARSIZE=1.5, /NORMAL

; RADIUS OF EARTH PARKING ORBIT STR = '!SH!D'+EARTH+'!N'+'='+'200 km' XYOUTS,0.50+(0.75-0.50)/2.0,0.965,STR,ALIGN=0.5,CHARSIZE=1.5 , /NORMAL

; RADIUS OF MOON TARGET ORBIT (PERIAPSIS) STR = '!SH!D'+MOON+'!N'+'='+'200 km' XYOUTS,0.75+(1.05-0.75)/2.0,0.965,STR,ALIGN=0.5,CHARSIZE=1.5 , /NORMAL

; COORDINATE SYSTEM STR = 'TEME J2000' XYOUTS,0.0+(0.25-0.00)/2.0,0.015,STR,ALIGN=0.5,CHARSIZE=1.5, /NORMAL

; RIGHT ASCENSION OF THE ASCENDING NODE (TRANSFER ORBIT) STR = RAAN + '=' + '237.45 deg' XYOUTS,0.25+(0.50-0.25)/2.0,0.015,STR,ALIGN=0.5,CHARSIZE=1.5 , /NORMAL

; TRANSFER TIME STR = 'TLC '+'='+'72.012 h' XYOUTS,0.50+(0.75-0.50)/2.0,0.015,STR,ALIGN=0.5,CHARSIZE=1.5 , /NORMAL

; DELTA-V STR = DELTA+'V'+'='+'3.4526 km/s' XYOUTS,0.75+(1.00-0.75)/2.0,0.015,STR,ALIGN=0.5,CHARSIZE=1.5 , /NORMAL

;DEVICE,/CLOSE SET_PLOT,thisDevice !P.MULTI=0 END

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: http://www.dfanning.com/

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Altered device coordinates after first call Posted by David Fanning on Mon, 16 Oct 2006 16:48:31 GMT View Forum Message <> Reply to Message

David Fanning writes:

> FOR J = 0,5 DO PLOT, FINDGEN(10), noerase=(j EQ 0)

WHOOPS! That NOERASE was an experiment and wasn't suppose to be there. Sorry. The line should read:

FOR J = 0.5 DO PLOT, FINDGEN(10)

Note that this code produces decent PostScript output, except that your NASA logo and title are inside of your avowed 5% margin.

Cheers.

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: http://www.dfanning.com/
Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Altered device coordinates after first call Posted by Juan Arrieta on Mon, 16 Oct 2006 19:10:19 GMT View Forum Message <> Reply to Message

Wow Dave, thanks a lot.

Your suggestions (as expected) worked like a charm. I really appreciate them.

It is much better, as you suggest, to first set up the plots, and them draw the frames and margins.

The NASA logo and others are created outside of the margin (the screen) because I'm not interested in viewing them on the screen, but when you create the PS output, they do appear as "footnotes" in the paper. This is important when creating a printed report, where I do want the NASA logo to appear, and my name. I should also add a "thanks to Dave Fanning" in that section:)

Another situation is still freaking me out: after I run the code, the SECOND time the direct graphics appear yellow! (the first ones are white). I have nothing against that color, but I did not request it! This happens to me all the time, when I change the device and set it back. My device is "X".

I will look into the yellow problem, but the code now works as expected.

Many thanks, I owe you a beer (after all your suggestions, maybe I should get a keg :)

/ Juan Arrieta

```
David Fanning wrote:
> David Fanning writes:
>> FOR J = 0,5 DO PLOT, FINDGEN(10), noerase=(j EQ 0)
>
> WHOOPS! That NOERASE was an experiment and wasn't suppose
  to be there. Sorry. The line should read:
>
    FOR J = 0.5 DO PLOT, FINDGEN(10)
>
 Note that this code produces decent PostScript output,
 except that your NASA logo and title are inside of
  your avowed 5% margin.
  Cheers,
> David
> David Fanning, Ph.D.
> Fanning Software Consulting, Inc.
> Coyote's Guide to IDL Programming: http://www.dfanning.com/
> Sepore ma de ni thui. ("Perhaps thou speakest truth.")
```

Subject: Re: Altered device coordinates after first call Posted by David Fanning on Mon, 16 Oct 2006 19:25:14 GMT View Forum Message <> Reply to Message

Juan Arrieta writes:

- > Wow Dave, thanks a lot.
- > Your suggestions (as expected) worked like a charm. I really
- > appreciate them.

That's why I get paid the big bucks on this newsgroup. :-)

> It is much better, as you suggest, to first set up the plots, and them

> draw the frames and margins.

- > Another situation is still freaking me out: after I run the code, the
- > SECOND time the direct graphics appear yellow! (the first ones are
- > white). I have nothing against that color, but I did not request it!
- > This happens to me all the time, when I change the device and set it
- > back. My device is "X".

>

>

>

- > I will look into the yellow problem, but the code now works as
- > expected.

If you are actually using a NASA logo, rather than what you showed us here, I would guess that some colors get loaded to show that image. A simple fix would just be to load a color table first (this should probably be done *anyway* if colors are important to you, and when are they NOT?):

LoadCT, 0, /Silent

- > Many thanks, I owe you a beer (after all your suggestions, maybe I
- > should get a keg:)

When I find a real job, we call ALL celebrate! :-)

Cheers.

David

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Sepore ma de ni thui. ("Perhaps thou speakest truth.")