
Subject: hist_nd to place just one point on a grid

Posted by [MarioIncandenza](#) on Tue, 24 Apr 2007 22:10:15 GMT

[View Forum Message](#) <> [Reply to Message](#)

IDL Wizards,

I use hist_nd a great deal. One of the important things I do with it is match gridded maps to point data sets and vice versa. Like this:

```
IDL> histogram = hist_nd(transpose([[point_x],[point_y]]),  
[dx_grid,dy_grid],min=[minx_grid,miny_grid],max=[maxx_grid,maxy_grid],reverse_indices=ri)
```

followed by:

```
IDL> matched_pts = point_x * 0.0; initialize array to hold sampled  
output
```

```
IDL> for i=0,n_elements(histogram)-1 do if(histogram[i] gt 0) then  
matched_points[ri[ri[i]:(ri[i+1]-1)]] = gridded_data[i]
```

or:

```
IDL> grid_totals = gridded_data * 0.0; initialize array to hold  
gridded output
```

```
IDL> for i=0,n_elements(histogram)-1 do if(histogram[i] gt 0) then  
grid_totals[i] = total(point_data[ri[ri[i]:(ri[i+1]-1)]])
```

My problem is that hist_nd is unhappy when the inputs [point_x] and [point_y] contain only one point. I could code an exception for this case, but surely there is a more elegant solution?
