
Subject: Re: Minimum between two arrays; no, not just Min(A-B)

Posted by [JD Smith](#) on Tue, 18 Sep 2007 22:53:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Tue, 18 Sep 2007 07:19:00 -0700, leatherback wrote:

> Hi All,

>

> I am working with time series data, and image scenes. For each point in my

> time series I try to find the correct satellite scene to use. So I have

> two arrays, one with dates of observations, one with image scene dates.

>

> These dates are in long integer (Unix timestamps).

>

> I *could* of course replicate my image scenes array to the length of the

> timeseries array, calculate the difference for each date, and find out

> where it is, something along these lines:

>

> [/color]

```
[color=blue]> datelist = rebin(dates, n_elements(dates), n_elements( fixes.timestamp))[/color]
```

```
[color=blue]> [/color]
```

```
[color=blue]> for j=0, n_elements(dates)-1 do begin[/color]
```

```
[color=blue]>   datelist[j,*] = datelist[j,*]-fixes.timestamp[/color]
```

```
[color=blue]> endfor[/color]
```

```
[color=blue]> [/color]
```

>

> Or even rebin both arrays, and subtract them. En then loop through them

> using the MIN / WHERE functions to find out where the minimum differences

> are.

>

> However, this does not feel right. Besides that.. the timeseries is

> potentially 100,000+ observations. Add to that a few hundred image dates,

> and you are filling your memory for something quite simple. Anybody here

> have a good idea how to vectorize this problem?

If they are in sorted order, you can use VALUE_LOCATE, which is happy to search for the location of many dates within many satellite timestamps, all at once. Then select which ever of the two is closer, like so:

```
IDL> nv=100
```

```
IDL> obs=randomu(sd,nv) & sat=randomu(sd,nv) & sat=sat[sort(sat)]
```

```
IDL> v=value_locate(sat,obs)
```

```
IDL> m=min(abs(sat[[1#v,1#v+1]]-rebin(1#obs,2,nv)),pos,DIMENSION= 1)
```

```
IDL> v= nv-1 < (v + pos mod 2) > 0
```

```
IDL> print,mean(abs(sat[v]-obs))
```

JD

Subject: Re: Minimum between two arrays; no, not just Min(A-B)
Posted by [leatherback](#) on Wed, 19 Sep 2007 10:55:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi JD,

This worked like a charm! Didn't know the value_locate function.

thanks!

J.

```
> If they are in sorted order, you can use VALUE_LOCATE, which is happy
> to search for the location of many dates within many satellite
> timestamps, all at once. Then select which ever of the two is closer,
> like so:
>
> IDL> nv=100
> IDL> obs=randomu(sd,nv) & sat=randomu(sd,nv) & sat=sat[sort(sat)]
> IDL> v=value_locate(sat,obs)
> IDL> m=min(abs(sat[[1#v,1#v+1]]-rebin(1#obs,2,nv)),pos,DIMENSION= 1)
> IDL> v= nv-1 < (v + pos mod 2) > 0
> IDL> print,mean(abs(sat[v]-obs))
>
> JD
```
