
Subject: Re: correlation and NaN

Posted by [Maarten\[1\]](#) on Wed, 19 Sep 2007 08:53:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Sep 19, 7:08 am, WRC2...@gmail.com wrote:

> Dear,
>
> I would like to calculate correlation factors from arrays which also
> contains NaN values. Now, i checked some newsgroups and got answers
> like this:
>
> indices = [where(finite(Var1) eq 1), where(finite(Var2) eq 1)]
> common_indices = indices(UNIQ(indices, sort(indices)))
> Result = CORRELATE(Var1(common_indices), Var2(common_indices))
>
> or with the another command (get_intersection?? - sorry, forgot the
> right name, and can find it back anymore...)
>
> The first doesn't seem to work in my case ($r^2 = \text{NaN}$), and the second
> is not recognized in my IDL 5.6 version.
> For the first method, maybe it is because one array doesn't contain a
> NaN value???

No, finite() eq 1 filters for values that are non NaN, i.e. it captures all normal numbers.

Does this work:

```
common_indices = where(finite(Var1) and finite(Var2), cnt)
```

```
if cnt gt 0 then $
```

```
    Rsqr = CORRELATE( Var1[common_indices], Var2[common_indices])
```

Maarten
