
Subject: Re: LeGendre Polynomials?

Posted by [thompson](#) on Sun, 26 Feb 1995 19:51:04 GMT

[View Forum Message](#) <> [Reply to Message](#)

chris@mercury.sfsu.edu (Christopher McCarthy) writes:

> To My knowledge IDL does not do Legendre polynomials--an obvious
> oversite if true, given that it does Bessel Functions (except
> beselK!), etc.

> Has anyone written a Legendre Polynomial program?
> Thanks,

> Chris

Try this. Hope it meets your needs.

Bill Thompson

```
=====
=====
FUNCTION LEGENDRE,X,L,M
;
IF N_PARAMS(0) LT 2 THEN BEGIN
  PRINT, '*** LEGENDRE must be called with 2-3 parameters:'
  PRINT, '      X, L [, M ]'
  RETURN,X
END ELSE IF N_PARAMS(0) EQ 2 THEN M = 0
;
IF M LT 0 THEN BEGIN
  PRINT, '*** M must not be less than 0, routine LEGENDRE.'
  RETURN,X
END ELSE IF M GT L THEN BEGIN
  PRINT, '*** M must not be greater than L, routine LEGENDRE.'
  RETURN,X
END ELSE BEGIN
  S = SIZE(X)
  IF S(0) EQ 0 THEN TEST = ABS(X) ELSE TEST = MAX(ABS(X))
  IF TEST GT 1 THEN BEGIN
    PRINT, '*** X must be in the range -1 to 1, routine LEGENDRE.'
    RETURN,X
  ENDIF
ENDELSE
;
PMM = 0.*X + 1.
IF M GT 0 THEN BEGIN
  SOMX2 = SQRT( (1. - X) * (1. + X) )
  FACT = 1.
```

```
FOR I = 1,M DO BEGIN
  PMM = -PMM*FACT*SOMX2
  FACT = FACT + 2.
ENDFOR
ENDIF
;
IF L EQ M THEN PLGNDR = PMM ELSE BEGIN
  PMMP1 = X * (2*M + 1) * PMM
  IF L EQ M+1 THEN PLGNDR = PMMP1 ELSE BEGIN
    FOR LL = M+2,L DO BEGIN
      PLL = (X*(2*LL-1)*PMMP1 - (LL+M-1)*PMM) / (LL-M)
      PMM = PMMP1
      PMMP1 = PLL
    ENDFOR
    PLGNDR = PLL
  ENDELSE
ENDELSE
;
RETURN,PLGNDR
END
```
