Subject: diagrami: Simple Diagrammer for IDL & PV-Wave Language Programs--bug fix
Posted by grunes on Fri, 10 Mar 1995 20:19:16 GMT
View Forum Message <> Reply to Message

Archive-name: diagrami
Submitted-by: grunes@nrlvax.nrl.navy.mil (Mitchell R Grunes)

****diagrami: Simple Diagrammer for IDL & PV-Wave Language Programs****

This is an update, which fixes minor bugs.

Sorry, little or no help can be provided for this program--
and I would need an example of where it failed.
DO NOT POST responses to newsgroups--especially not alt.sources.
If anyone finds this useful, tell me.

```
-----------------------------CUT HERE-----------------------------
      program diagrami       !Diagrammer for IDL and PV-Wave

c EXAMPLE OF OUTPUT:

c     +---------pro Sample,a,b,c                    |   1
c     |         a=indgen(15)^2                     |   2
c     |+--------if a eq b then begin                |   3
c     ||          print,'A equals B'               |   4
c     ||          c=0                              |   5
c     |+--------else begin                         |   6
c     ||          print,'A does not equal B'       |   7
c     ||          c=1                              |   8
c     |+--------endif                              |   9
c     +---------end                                |  10

c Diagrams IDL and PV-Wave begin(or case)-end constructs, functions
c  and procedures, places a * next to goto and return statements.
c
c Program by Mitchell R Grunes, ATSC/NRL (grunes@nrlvax.nrl.navy.mil).
c Revision date: 3/10/95.
c If you find it useful, please send me an e-mail comment--
c  but do NOT send money.

c This program was written in FORTRAN, the One True Language.

c Note--this is a quick and dirty attempt--may not always work quite right.
c  It does not yet handle CASE instances, since I don't use them myself,
c   but it should draw a line around the entire CASE block.

c It is assumed that no fortran carriage control exists on the output
```

```
c  file, so don't specify output to the screen or a terminal.

c I hope this works for you, but bear in mind that nothing short of
c  a full-fledged language parser could really do the job.  Perhaps
c  worth about what you paid for it.    (-:

c Versions: To diagram Fortran: diagramf.for
c                   IDL:     diagrami.for
c                   C:       diagramc.for

      character*160 a,b
      character*16 aa
      character*5 form,fm
      character*1 c
      logical find
      external find
      common icol
      print*,'IDL source filename?'
      a=' '
      read(*,1)a(1:132)
1      format(a132)
      open(1,file=a,status='old')
      print*,'output file?'
      b=' '
      read(*,1)b(1:132)
      open(2,file=b,status='unknown')
c last minute change to reduce spaces in diagram block:
c       print*,'column for line #(60 for screen,91 for laser,112 for print,0 for none)?'
      print*,'column for line #(68 for screen,0 for none)?'
      iline=0
      read*,iline
cwrite(2,*)a
 cwrite(2,*)'********************************************** **************'
      aa='| | | | | | | | '
      i1=0          !# of nest levels before current line
      i2=0          !# of nest levels on  current line
      i3=0          !# of nest levels after current line
      i4=0          !1 to flag start or end of block
      InSub=0       !Inside a subroutine or function?
      nMainEnd=0    !# of mainline programs ended so far
      nline=0
10     read(1,11,end=99)a
11     format(a160)
      nline=nline+1
      fm=' '
      write(fm,'(i5)')nline
      if(nline/100*100.eq.nline)print*,'Line ',fm
```

```
      b=' '          !turn tabs to spaces
      j=1
      do i=1,160
        if(a(i:i).eq.char(9))then
          j=(j-1)/8*8+8+1
        elseif(j.le.160)then
          b(j:j)=a(i:i)
          j=j+1
        endif
      enddo
      i=1
      j=1
      a=' '
      iquote=0               !no ' yet
      idquote=0               !no " yet
      j=1
      do i=1,160
        c=b(i:i)
        if(c.ge.'A'.and.c.le.'Z')c=char(ichar(c)+32)
        if(c.eq.';')goto 15
        if(c.eq."'")iquote=1-iquote
        if(c.eq.'"')idquote=1-idquote
        if(iquote.ne.0.or.idquote.ne.0)c=' '
        if(j.gt.1)then               !(kill multiple spaces)
          if(c.eq.' '.and.a(j-1:j-1).eq.' ')j=j-1
        endif
        a(j:j)=c
        j=j+1
      enddo
15      i2=i1
      i3=i1
      iflag=0        !no goto on line
      if(find(a,'goto',8+32).or.find(a,'return',1+128))iflag=1
      if(find(a,'endif ',2).or.find(a,'endfor ',2)
     &  .or.find(a,'endelse ',2).or.find(a,'endwhile ',2)
     &  .or.find(a,'endcase ',2).or.find(a,'endrep ',2))then
        i3=i3-1
        i4=i4+1
        if(find(a,'begin  ',1))i3=i3+1
      elseif(find(a,'case ',1))then
        i4=i4+1
        i2=i2+1
        i3=i3+1
      elseif(find(a,'begin  ',1))then
        i4=i4+1
        i2=i2+1
        i3=i3+1
      elseif(find(a,'function ',2).or.find(a,'pro ',2))then
```

```
  if(InSub.eq.0)then
    InSub=1
    i2=i2+1
    i3=i3+1
    i4=i4+1
    if(i3.ne.1)then
      PRINT*,'***ERROR--INVALID DIAGRAMMING INDEX line',fm
      WRITE(2,*)'***ERROR--INVALID DIAGRAMMING INDEX!***'
      print*,char(7)
    endif
  endif
  i3=1
elseif(find(a,'end ',2))then
  if(i3.gt.0.or.Insub.gt.0)then         !Problem: IDL end may actually
    i3=i3-1                             ! be an endif, endelse, etc.
    i4=i4+1
    if(i3.eq.0.and.InSub.ne.0)InSub=0
    if(find(a,'begin  ',1))then
      i2=i2+1
      i3=i3+1
    endif
  else
    nMainEnd=nMainEnd+1
    print*,'***MAINLINE END line ',fm
    if(nMainEnd.gt.1)then
      PRINT*,'***ERROR--TOO MANY MAINLINE ENDS!***'
      WRITE(2,*)'***ERROR--TOO MANY MAINLINE ENDS!***'
      print*,char(7)
    endif
  endif
endif
a=' '
if(i1.lt.0.or.i2.lt.0.or.i3.lt.0.or.i4.lt.0)then
  PRINT*,'***ERROR--INVALID DIAGRAMMING INDEX line',fm
  WRITE(2,*)'***ERROR--INVALID DIAGRAMMING INDEX!***'
  print*,char(7)
  i1=max(i1,0)
  i2=max(i2,0)
  i3=max(i3,0)
  i4=max(i4,0)
endif
jj=max(1,min(16,2*i2-1))
if(i2.gt.0)a=aa(1:jj)
if(i4.ne.0)then
  jjj=1
  dowhile(jjj.lt.160.and.b(jjj:jjj).eq.' ')
    jjj=jjj+1
  enddo
```

```
        if(jjj.gt.1)b(1:jjj-1)=
     &   '-------------------------------------------------'
        a(jj:16)='------------------------------'
      endif
      do i=0,i4-1
        a(max(1,min(15,jj-i*2)):max(1,min(15,jj+1-i*2)))='+-'
      enddo
      i4=0
      if(iline.ne.0.and.b(max(1,iline):160).eq.' ')then
        form=fm                         !line #
        if(form(1:1).eq.' ')form(1:1)='|'
        b(iline:iline+4)=form
      endif
      n=160
      dowhile(n.gt.1.and.b(n:n).eq.' ')
        n=n-1
      enddo
      if(iflag.ne.0)a(1:1)='*'
c last minute change to reduce spaces in diagram block:
      write(2,2)(a(i:i),i=1,15,2),(b(i:i),i=1,n)
2      format(132a1)
      i1=i3
      goto 10
99      if(i3.gt.0.or.InSub.ne.0)then
        PRINT*,'***WARNING--SOME NEST LEVELS LEFT HANGING AT END***'
        print*,char(7)
      endif
      end
c------------------------------------------------------------ ------------
      logical function find(a,b,icond) !find b in a, subject to conditions:
                                !icond=sum of the following:
                                !1:  Prior, if exists, must be blank
                                !2:  Must be first non-blank
                                !4:  Prior character, if present,
                                !    must not be alphanumeric.
                                !8:  Prior character, if present,
                                !    must be blank or )
                                !16: Prior character, if present,
                                !    must be blank or ,
                                !32: Next character not alphanumeric
                                !64: Next character not alphabetic
                                !128:Next character must be blank or (
      character*(*) a,b
      character*1   c,cNext
      common icol
      logical result

      ii=len(a)
```

```
      jj=len(b)
      result=.false.
      do i=1,ii-jj+1
        if(a(i:i+jj-1).eq.b)then
          icol1=i                 ! icol1=column of item found
          icol =i+jj              ! icol =colomn after item found

          c=' '
          cNext=' '
          if(icol1.gt.1)c=a(icol1-1:icol1-1)
          if(icol .le.ii)cNext=a(icol:icol)

          result=.true.
          if(result.and.iand(icond,1).ne.0.and.icol1.gt.1)then
            result=c.eq.' '
          endif

          if(result.and.iand(icond,2).ne.0.and.icol1.gt.1)then
            result=a(1:icol1-1).eq.' '
          endif

          if(result.and.iand(icond,4).ne.0)
     &      result=(c.lt.'0'.or.c.gt.'9').and.(c.lt.'a'.or.c.gt.'z')

          if(result.and.iand(icond,8).ne.0)result=c.eq.' '.or.c.eq.')'

          if(result.and.iand(icond,16).ne.0)result=
     &      c.eq.' '.or.c.eq.','

          if(result.and.iand(icond,32).ne.0)
     &      result=(cNext.lt.'0'.or.cNext.gt.'9').and.
     &             (cNext.lt.'a'.or.cNext.gt.'z')

          if(result.and.iand(icond,64).ne.0)
     &      result=(cNext.lt.'a'.or.cNext.gt.'z')

          if(result.and.iand(icond,128).ne.0)
     &      result=cNext.eq.' '.or.cNext.eq.'('

          find=result
          if(result)return
        endif
      enddo
      find=result
      return
      end
----------CUT HERE----------
 ---------- ----------
```

(opinions expressed are mine alone)
Mitchell R Grunes (grunes@nrlvax.nrl.navy.mil)
Allied-Signal Tech. Serv. / Naval Research Lab