
Subject: Re: How to get numbers into passed structure elements
(pass-by-value/reference problem).

Posted by [David Fanning](#) on Wed, 27 Feb 2008 15:25:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

Paul van Delst writes:

- > So, I realise this is one of those pass-by-reference or pass-by-value things, but how does
- > one get around it? Do I:
- > a) make the Type component of the Cloud structure a pointer? (Yuk!)
- > b) change the way I pass the Cloud structure into the CRTM_Read_Cloud_Record() fn?
- > i.e. not reference the cloud structure array via the index [n].
- >
- > I would much prefer (b), but will that entail copying entire structures? The number of
- > "Clouds" associated with any particular "Atm[m]" profile is variable.

Too much misdirection for me to follow this early in the morning,
but if you pass a structure array in by reference, what are you
copying? I think you are only "copying" if you pass something in
by value. I would go with (b).

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: How to get numbers into passed structure elements
(pass-by-value/reference problem).

Posted by [Paul Van Delst\[1\]](#) on Wed, 27 Feb 2008 15:56:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

David Fanning wrote:

- > Paul van Delst writes:
- >
- >> So, I realise this is one of those pass-by-reference or pass-by-value things, but how does
- >> one get around it? Do I:
- >> a) make the Type component of the Cloud structure a pointer? (Yuk!)
- >> b) change the way I pass the Cloud structure into the CRTM_Read_Cloud_Record() fn?
- >> i.e. not reference the cloud structure array via the index [n].
- >>
- >> I would much prefer (b), but will that entail copying entire structures? The number of
- >> "Clouds" associated with any particular "Atm[m]" profile is variable.
- >

> Too much misdirection for me to follow this early in the morning,
> but if you pass a structure array in by reference, what are you
> copying?

Well I meant if I do this:

```
FOR n = 0, Atm.n_Clouds-1 DO BEGIN
  ; Need to store data into (*Atm.Cloud)[n]
  result = CRTM_Read_Cloud_Record( FileID, Cloud, DEBUG=Debug )
  ...Copy Cloud into (*Atm.Cloud)[n]
ENDFOR
```

> I think you are only "copying" if you pass something in
> by value. I would go with (b).

I just completed an experiment where I passed the entire pointer array and looped over clouds in my reader,

```
result = CRTM_Read_Cloud_Record( FileID, *Atm.Cloud, DEBUG=Debug )
```

since it was passing (*Atm.Cloud)[n] that was bugging me up.

I find it a fundamental flaw of IDL that the argument passing mechanism (reference or value) is so exposed to the user that they have to tailor their code to prevent data loss. I understand why it's there, but even Fortran has moved beyond it (for about 18(!) years now).

cheers,

paulv

Subject: Re: How to get numbers into passed structure elements
(pass-by-value/reference problem).

Posted by [lecacheux.alain](#) on Thu, 28 Feb 2008 10:23:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

On 27 fév, 16:56, Paul van Delst <Paul.vanDe...@noaa.gov> wrote:

> David Fanning wrote:

>> Paul van Delst writes:

>

>>> So, I realise this is one of those pass-by-reference or pass-by-value things, but how does
>>> one get around it? Do I:

>>> a) make the Type component of the Cloud structure a pointer? (Yuk!)

>>> b) change the way I pass the Cloud structure into the CRTM_Read_Cloud_Record() fn?

>>> i.e. not reference the cloud structure array via the index [n].

>

>>> I would much prefer (b), but will that entail copying entire structures? The number of

>>> "Clouds" associated with any particular "Atm[m]" profile is variable.

```

>
>> Too much misdirection for me to follow this early in the morning,
>> but if you pass a structure array in by reference, what are you
>> copying?
>
> Well I meant if I do this:
>
>   FOR n = 0, Atm.n_Clouds-1 DO BEGIN
>     ; Need to store data into (*Atm.Cloud)[n]
>     result = CRTM_Read_Cloud_Record( FileID, Cloud, DEBUG=Debug )
>     ...Copy Cloud into (*Atm.Cloud)[n]
>   ENDFOR
>
>> I think you are only "copying" if you pass something in
>> by value. I would go with (b).
>
> I just completed an experiment where I passed the entire pointer array and looped over
> clouds in my reader,
>
>   result = CRTM_Read_Cloud_Record( FileID, *Atm.Cloud, DEBUG=Debug )
>
> since it was passing (*Atm.Cloud)[n] that was bugging me up.
>
> I find it a fundamental flaw of IDL that the argument passing mechanism (reference or
> value) is so exposed to the user that they have to tailor their code to prevent data loss.
> I understand why it's there, but even Fortran has moved beyond it (for about 18(!) years now).
>
> cheers,
>
> paulv

```

Since IDL pointers point to variables which are global in scope and
 IDL structures are
 global too, I would suggest, in any of your function, to just pass a
 pointer on the used instance
 of CRTM_Atmosphere...
 alx
