
Subject: Re: Solarsoft and idlwave?

Posted by [pgrigis](#) on Fri, 23 May 2008 13:40:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

BG wrote:

> Hey all,
>
> Just discovering all that is wonderful about idlwave, but running into
> a problem.
>
> My current machine is runs bash.
>
> My group uses Solarsoft, which has init scripts for IDL that are all
> written in csh.
>
> If I'm sitting on the (Unix) command line, I do something like:
>
> csh ssw_startup
>
> Which calls the scripts just fine and I get a SSW> prompt in IDL.
>
> However, if I feed a script into idlwave as my startup file (e.g.:
>
> (setq idlwave-shell-explicit-file-name "~/shortcuts/ssw_workaround")
>
> where ssw_workaround is just a script file that just does this:
>
> csh ssw_startup
>
>
> Then when I start the IDL shell in Emacs/IDLWAVE I get this:
>
>
> Process idl exited abnormally with code 1
>

It works for me, but my solarsoft startup script looks like this:

```
-----  
#!/bin/csh -f  
#  
  
setenv SSW      /proj/DataCenter/ssw/  
setenv SSW_INSTR "gen hinode xrt sxt hxt bcs trace eit binaries  
chianti hessi spex xray"  
source $SSW/gen/setup/setup.ssw  
  
# start sswidl
```

sswidl

Maybe you can try something like that and see if it works.

Ciao,
Paolo

>
> And my IDL process is toast.
>
>
> Any ideas about this? I think it all has to do with the fact that the
> environmental variables in my csh init scripts aren't persisting...but
> I haven't been able to come up with a good workaround.
>
> Cheers,
>
> Brian

Subject: Re: Solarsoft and idlwave?
Posted by [BG](#) on Fri, 23 May 2008 18:25:34 GMT
[View Forum Message](#) <> [Reply to Message](#)

As usual, the simplest thing is the one that works.

Thanks!

-BG

On May 23, 6:40 am, pgri...@gmail.com wrote:

> BG wrote:
>> Hey all,
>
>> Just discovering all that is wonderful about idlwave, but running into
>> a problem.
>
>> My current machine is runs bash.
>
>> My group uses Solarsoft, which has init scripts for IDL that are all
>> written in csh.
>
>> If I'm sitting on the (Unix) command line, I do something like:
>

```

>> csh ssw_startup
>
>> Which calls the scripts just fine and I get a SSW> prompt in IDL.
>
>> However, if I feed a script into idlwave as my startup file (e.g.:
>
>> (setq idlwave-shell-explicit-file-name "~/shortcuts/ssw_workaround")
>
>> where ssw_workaround is just a script file that just does this:
>
>> csh ssw_startup
>
>> Then when I start the IDL shell in Emacs/IDLWAVE I get this:
>
>> Process idl exited abnormally with code 1
>
> It works for me, but my solarsoft startup script looks like this:
>
> -----
> #!/bin/csh -f
> #
>
> setenv SSW      /proj/DataCenter/ssw/
> setenv SSW_INSTR "gen hinode xrt sxt hxt bcs trace eit binaries
> chianti hessi spex xray"
> source $SSW/gen/setup/setup.ssw
>
> # start sswidl
> sswidl
> -----
>
> Maybe you can try something like that and see if it works.
>
> Ciao,
> Paolo
>
>
>
>> And my IDL process is toast.
>
>> Any ideas about this? I think it all has to do with the fact that the
>> environmental variables in my csh init scripts aren't persisting...but
>> I haven't been able to come up with a good workaround.
>
>> Cheers,
>
>> Brian

```
