
Subject: Add a colorbar in a filled contour

Posted by duxiyu@gmail.com on Wed, 25 Jun 2008 09:01:46 GMT

[View Forum Message](#) <> [Reply to Message](#)

Dear all,

I am using D Fanning's colorbar routine.

But I have some questions about the corresponding value for each color.

For example,

```
A=DIS(31,41)
DEVICE, DECOMPOSED=0
LOADCT, 5, NCOLORS=100
CONTOUR, A, POSITION=[0.15, 0.15, 0.95, 0.75], $
  C_COLORS=INDGEN(100), NLEVELS=100, /FILLI
```

For $\min(A)=0$ and $\max(A)=25$, the color with index '0' should present the value '0' and the color with index '99' should present the value '25'.

Therefore, when I use the COLORBAR routine, the keywords RANGE should be given.

```
COLORBAR, NCOLORS=100, POSITION=[0.15, 0.85, 0.95, 0.90],
RANGE=[min(A), max(A)]
Is it right?
```

If the minimum or maximum of the array has a floating-point value like 3.24, is the above command to add the colorbas still right?

Best regards,
Du Jian

Subject: Re: Add a colorbar in a filled contour

Posted by [Rosie](#) on Thu, 13 Sep 2012 11:48:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wednesday, June 25, 2008 10:01:46 AM UTC+1, dux...@gmail.com wrote:

> Dear all,

>

> I am using D Fanning's colorbar routine.

> But I have some questions about the corresponding value for each
> color.

>

> For example,

>

> A=DIS(31,41)

> DEVICE, DECOMPOSED=0
> LOADCT, 5, NCOLORS=100
> CONTOUR, A, POSITION=[0.15, 0.15, 0.95, 0.75], \$
> C_COLORS=INDGEN(100), NLEVELS=100, /FILLI
>
> For min(A)=0 and max(A)=25, the color with index '0' should present
> the value '0' and the color with index '99' should present the value
> '25'.
> Therefore, when I use the COLORBAR routine, the keywords RANGE should
> be given.
> COLORBAR, NCOLORS=100, POSITION=[0.15, 0.85, 0.95, 0.90],
> RANGE=[min(A), max(A)]
> Is it right?
>
> If the minimum or maximum of the array has a floating-point value like
> 3.24, is the above command to add the colorbas still right?
>
> Best regards,
> Du Jian
