

---

Subject: Re: SGI escape sequences

Posted by hofer on Mon, 06 Apr 1992 14:00:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

In article <1992Apr3.150440.5531@jhunix.hcf.jhu.edu>,

murthy\_j@jhunix.hcf.jhu.edu (Jayant Murthy) writes:

> Does anyone have a list of the escape sequences for an SGI IRIS Indigo  
> keyboard? I want to define the keys and the old vt200 assignments on  
> my DECstation don't work.

>

> Thanks

> Jayant Murthy

> murthy@pha.jhu.edu

>

In the following piece of code I define some keycodes to work on a vms  
vaxstation as well as on a SGI (PI 4D/35). You will find the keycodes  
produced by the funtion keys of the iris keyboard in the list (SGIF1 ...  
SGIF12). I do not know about other keycodes, such as Insert etc.

Hope this helps.

Remo Hofer

```
; Initialise keyboard (in VMS they are predefined)
IF STRLOWCASE(STRTRIM(!VERSION.OS, 2)) NE 'vms' THEN BEGIN

    keys = [
        'F1', '\033[11~'], $ ; vt200 codes
        'F2', '\033[12~'], $
        'F3', '\033[13~'], $
        'F4', '\033[14~'], $
        'F5', '\033[15~'], $
        'F6', '\033[17~'], $
        'F7', '\033[18~'], $
        'F8', '\033[19~'], $
        'F9', '\033[20~'], $
        'F10', '\033[21~'], $
        'F11', '\033[23~'], $
        'F12', '\033[24~'], $
        'F13', '\033[25~'], $
        'F14', '\033[26~'], $
        'HELP', '\033[28~'], $
        'DO', '\033[29~'], $
        'F17', '\033[31~'], $
        'F18', '\033[32~'], $
        'F19', '\033[33~'], $
        'F20', '\033[34~'], $
        'PF1', '\033OP'], $
```

```

['PF2', '\033OQ'], $
['PF3', '\033OR'], $
['PF4', '\033OS'], $
['SGIF1', '\033[001q'], $ ; SGI winterm codes
['SGIF2', '\033[002q'], $
['SGIF3', '\033[003q'], $
['SGIF4', '\033[004q'], $
['SGIF5', '\033[005q'], $
['SGIF6', '\033[006q'], $
['SGIF7', '\033[007q'], $
['SGIF8', '\033[008q'], $
['SGIF9', '\033[009q'], $
['SGIF10', '\033[010q'], $
['SGIF11', '\033[011q'], $
['SGIF12', '\033[012q']]
s = SIZE(keys)
FOR i=0, s(2)-1 DO DEFINE_KEY, keys(0, i), ESCAPE=keys(1, i)

```

```

; self defined keys not possible in vms
DEFINE_KEY, 'SGIF1', 'sxm_main_menu', /TERMINATE
DEFINE_KEY, 'SGIF2', 'sxm_help', /TERMINATE

```

```
ENDIF
```

```

DEFINE_KEY, 'F1', 'sxm_main_menu', /TERMINATE
DEFINE_KEY, 'PF1', 'sxm_main_menu', /TERMINATE
DEFINE_KEY, 'DO', 'sxm_main_menu', /TERMINATE
DEFINE_KEY, 'F2', 'sxm_help', /TERMINATE
DEFINE_KEY, 'PF2', 'sxm_help', /TERMINATE
DEFINE_KEY, 'HELP', 'sxm_help', /TERMINATE

```

---

```
-- 
RFC822: <hofer@urz.unibas.ch> or <hofer%urz.unibas.ch@CERNVAX.BITNET>
X.400: S=hofer;OU=urz;O=unibas;P=SWITCH;A=ARCOM;C=CH
HEPNET/SPAN: CHGATE::YOGI::HOFER or 20579::48130::HOFER
```

---