
Subject: Re: skip_lun question
Posted by [natha](#) on Tue, 31 Mar 2009 21:00:20 GMT
[View Forum Message](#) <> [Reply to Message](#)

It must be the same
I found the problem,

Sorry
B.

Subject: Re: skip_lun question
Posted by [David Fanning](#) on Tue, 31 Mar 2009 21:04:15 GMT
[View Forum Message](#) <> [Reply to Message](#)

llo writes:

```
> I've a question with the skip_lun function.
>
> Looks the following example:
> I've a .dat file that contains a BYTARR(180,240,24) and I want to read
> a 180x240 matrix on the 7th position ([*,*,7])
>
> I tried something like that:
>
> openr, un$lun, file, /get_lun
> skip_lun, un$lun, (180.*240.*7)
> data=bytarr(180,240)
> readu, un$lun, data
> -----
> Now I verify the reading.....
>
> point_lun, un$lun, 0
> all_data=bytarr(180,240,24)
> readu, un$lun, all_data
>
> print, total(abs(all_data[*,*,7]-data))
> IDL> 6.71223e+06
>
> The result is so different and I don't know why.
> Any suggestions? Does anybody knows how is the information saved in a
> DAT file.
```

SKIP_LUN!? That's a new one for me. :-)

First of all, [*,*,7] is the *eighth* position. I presume this isn't your problem is it? The *seventh* position is [*,*,6].

Anyway, I would do this with an associated variable:

```
Openr, lun, file, /Get_lun  
data = Assoc(lun, Bytarr(180,240,24))
```

Then, if I wanted the 7th frame of data:

```
thisframe = data[6]
```

Cheers,

David

--

David Fanning, Ph.D.

Coyote's Guide to IDL Programming (www.dfanning.com)

Sepore ma de ni thui. ("Perhaps thou speakest truth.")
