Subject: NetCDF and empty variables Posted by renaud.dussurget on Fri, 17 Apr 2009 13:18:11 GMT View Forum Message <> Reply to Message

Hi,

I've been trying reading a NC file with David Fanning's (very handy!) NCDF_DATA object, and it failed reading a file while parsing it. After trying to understand where it was crashing, I've realised that this variable was empty (though it is supposed to have 3 dimensions) and that IDL NCDF_VARGET function was not able to deal with this problem...

An example:

6

```
IDL>ncid = NCDF_OPEN('myFile.nc')
IDL>varId = NCDF_VARID(ncid, 'HISTORY_INSTITUTION')
IDL>out=NCDF VARINQ(ncid, VarId)
IDL>help, out, /str
** Structure <a9c098>, 5 tags, length=56, data length=52, refs=1:
 NAME
             STRING
                       'HISTORY INSTITUTION'
                STRING 'CHAR'
 DATATYPE
 NDIMS
              LONG
                             3
 NATTS
              LONG
                             3
 DIM
            LONG
                     Array[3]
IDL>print, out.dim
```

IDL>NCDF_VARGET, ncid, varld, data, COUNT=cnt

12

I have found a simple way to deal with this, however I don't really like it...

IDL>cmd = 'NCDF_VarGet, ncid, varId, dataIDL>res= EXECUTE(cmd)% Array dimensions must be greater than 0.

% Array dimensions must be greater than 0.

And then in the code, write something like this IF (res EQ 0) THEN data = -1

Does anyone has a better solution???

Thanks Bye

Subject: Re: NetCDF and empty variables

Posted by renaud.dussurget on Tue, 21 Apr 2009 15:49:38 GMT

View Forum Message <> Reply to Message

On 21 avr, 02:11, Mark <mark.h...@gmail.com> wrote:

> On Apr 21, 12:18 am, renaud.dussur...@gmail.com wrote:

>

- >> NCDF INQUIRE and NCDF DIMINQ just give what the
- >> properties of the variable should be, and not what
- >> it really is in the file (i.e. no
- >> data)

- > To misquote a very wise man who wasn't talking about NetCDF files,
- > what is is, what isn't isn't, there is no should.

- > Perhaps you could put a copy of the file on an FTP server, so we could
- > look at it. Or if it's small, maybe you could convert it to CDL (text)
- > format and post that on the group.

I've posted the a link to the original file on the other post:

ftp://ftp.ifremer.fr/ifremer/argo/dac/coriolis/69003/69003_p rof.nc

Renaud

Subject: Re: NetCDF and empty variables Posted by David Fanning on Tue, 21 Apr 2009 18:38:23 GMT View Forum Message <> Reply to Message

renaud.dussurget@gmail.com writes:

> I've posted the a link to the original file on the other post:

ftp://ftp.ifremer.fr/ifremer/argo/dac/coriolis/69003/69003_p rof.nc

Pretty weird. NONE of the HISTORY_* variables were populated in this file. I've modified my nCDF Browser routine to handle this strange state of affairs.

Download this new file:

http://www.dfanning.com/programs/ncdf_data__define.pro

Cheers.

David

David Fanning, Ph.D.

Coyote's Guide to IDL Programming (www.dfanning.com)

```
Subject: Re: NetCDF and empty variables
Posted by Mark[1] on Wed, 22 Apr 2009 03:48:24 GMT
View Forum Message <> Reply to Message
```

```
On Apr 22, 6:38 am, David Fanning <n...@dfanning.com> wrote:
> renaud.dussur...@gmail.com writes:
>> I've posted the a link to the original file on the other post:
>> ftp://ftp.ifremer.fr/ifremer/argo/dac/coriolis/69003/69003_p rof.nc
>
> Pretty weird. NONE of the HISTORY_* variables were
> populated in this file. I've modified my nCDF Browser
> routine to handle this strange state of affairs.
> Download this new file:
>
   http://www.dfanning.com/programs/ncdf_data__define.pro
>
>
> Cheers,
>
> David
> --
> David Fanning, Ph.D.
> Coyote's Guide to IDL Programming (www.dfanning.com)
> Sepore ma de ni thui. ("Perhaps thou speakest truth.")
```

First, please accept apologies for starting a new thread (I don't know how that happened) and for not reading the other thread thoroughly enough to see that the file had already been posted.

That said, there's nothing weird about this file except that it has an unlimited dimension (N_HISTORY) with size zero. And that's not really very weird at all.

The ncdump utility shows this:

```
$ ncdump -v HISTORY_PARAMETER 69003_prof.nc
netcdf \69003_prof {
dimensions:
    DATE_TIME = 14;
    STRING256 = 256;
    STRING64 = 64;
    STRING32 = 32;
    STRING16 = 16;
    STRING8 = 8;
    STRING4 = 4;
```

```
STRING2 = 2;
N_PROF = 16;
N_PARAM = 2;
N_LEVELS = 94;
N_CALIB = 1;
N_HISTORY = UNLIMITED; // (0 currently)
variables:
...etc

and so does IDL

IDL> id = ncdf_open('C:\Temp\69003_prof.nc')
IDL> inq = ncdf_inquire(id)
IDL> ncdf_diminq, id, inq.recdim, name, size
IDL> print, name, size
N_HISTORY 0
IDL> ncdf_close, id
```

And this is what I said in the first post of the current thread.

Subject: Re: NetCDF and empty variables
Posted by David Fanning on Wed, 22 Apr 2009 04:03:48 GMT
View Forum Message <> Reply to Message

Mark writes:

```
> That said, there's nothing weird about this file except that it has an
> unlimited dimension (N_HISTORY) with size zero. And that's not really
> very weird at all.
> The ncdump utility shows this:
>
> $ ncdump -v HISTORY PARAMETER 69003 prof.nc
> netcdf \69003 prof {
> dimensions:
      DATE_TIME =3D 14;
>
      STRING256 = 3D 256;
>
      STRING64 = 3D 64 :
>
      STRING32 = 3D 32;
>
      STRING16 = 3D 16;
>
      STRING8 = 3D 8;
>
      STRING4 = 3D 4;
>
      STRING2 = 3D 2:
>
      N PROF = 3D 16;
>
      N PARAM =3D2:
      N_LEVELS =3D 94;
>
      N_CALIB = 3D 1;
```

- N_HISTORY =3D UNLIMITED; // (0 currently)
 variables:
 ...etc
 and so does IDL
 IDL> id =3D ncdf_open('C:\Temp\69003_prof.nc')
 IDL> inq =3D ncdf_inquire(id)
 IDL> ncdf_diminq, id, inq.recdim, name, size
 IDL> print, name, size
- > N_HISTORY 0 > IDL> ncdf_close, id

Yeah, so what does that mean that it has an unlimited dimension. Why would someone do that? :-)

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: NetCDF and empty variables
Posted by David Fanning on Wed, 22 Apr 2009 14:30:01 GMT
View Forum Message <> Reply to Message

Mark writes:

- > That said, there's nothing weird about this file except that it has an
- > unlimited dimension (N_HISTORY) with size zero. And that's not really
- > very weird at all.

OK, I understand that I can't read any variable that has this unlimited dimension set to zero. So, how do I determine ahead of time (that is, before I read the variable) whether that variable is using this dimension?

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Subject: Re: NetCDF and empty variables
Posted by David Fanning on Wed, 22 Apr 2009 15:29:59 GMT
View Forum Message <> Reply to Message

David Fanning writes:

- > OK, I understand that I can't read any variable that has
- > this unlimited dimension set to zero. So, how do I determine
- > ahead of time (that is, before I read the variable) whether
- > that variable is using this dimension?

Never mind, I figured out that NCDF_VARINQ can return me the IDs of all of the dimensions of the variable. If I have a dimension with a length of zero, I save its ID and later compare it to the dimension IDs returned from the function listed above. If there is a match, I don't read the variable and do something else.

The nCDF Browser has been updated appropriately:

http://www.dfanning.com/ncdf_browser.zip

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: http://www.dfanning.com/
Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: NetCDF and empty variables
Posted by Mark[1] on Thu, 23 Apr 2009 00:29:38 GMT
View Forum Message <> Reply to Message

On Apr 22, 4:03 pm, David Fanning <n...@dfanning.com> wrote:

- > Yeah, so what does that mean that it has an unlimited
- > dimension. Why would someone do that? :-)

Say you have an ocean model with a rectangular grid. For your output netCDF files you would probably have fixed dimensions (x, y and z) for the three spatial dimensions of the model and you would have an unlimited dimension (t) correspond to simulated time. Your model grid

variables would depend on the fixed dimensions in various combinations and you would write this info at the beginning of the model run. Your model state variables (temperature, salinity, velocity components) would depend on x, y, z AND t, and you would write snapshots of these as the model runs, stepping along the t dimension each time. By making the t dimension unlimited you don't have to know how many snapshots you're going to write in advance. If the model hasn't written any snapshots yet--perhaps it crashed before it could--then the size of the time dimension is 0.