

---

Subject: Startup on LINUX Question

Posted by [David Fanning](#) on Thu, 04 Jun 2009 23:31:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Folks,

I have an IDL startup file on my LINUX machine. The first line in the file is this:

DEVICE, RETAIN=2, TRUE\_COLOR=1, SET\_CHARACTER\_SIZE=[9,12]

When I start up IDL 7.0.1 in the IDL Workbench this file is executed (there is a print statement at the end of the file to let me know it executed). And, indeed, graphics windows are retained, etc. \*But\* when I issue a plot command, I still have tiny fonts. At some random time during the day (I have no idea when), something in IDL "wakes up" and all of my graphics from then on contain the larger font I specified in my startup file. This can take an hour, sometimes I don't notice the larger fonts until after lunch.

If I have small fonts and I .reset my IDL session, I re-run my startup file, and I still have small fonts.

If I have larger fonts and I .reset my IDL session, I continue to have larger fonts.

Does anyone have the faintest idea what might be going on here?

Cheers,

David

--

David Fanning, Ph.D.

Coyote's Guide to IDL Programming ([www.dfanning.com](http://www.dfanning.com))

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

---

---

Subject: Re: Startup on LINUX Question

Posted by [Paul Van Delst\[1\]](#) on Fri, 05 Jun 2009 18:41:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

David Fanning wrote:

> Folks,  
>  
> I have an IDL startup file on my LINUX machine. The first  
> line in the file is this:  
>

```
> DEVICE, RETAIN=2, TRUE_COLOR=1, SET_CHARACTER_SIZE=[9,12]
>
> When I start up IDL 7.0.1 in the IDL Workbench this file
> is executed (there is a print statement at the end of the file
> to let me know it executed). And, indeed, graphics windows are
> retained, etc. *But* when I issue a plot command, I still have tiny
> fonts. At some random time during the day (I have no idea when),
> something in IDL "wakes up" and all of my graphics from then on
> contain the larger font I specified in my startup file. This
> can take an hour, sometimes I don't notice the larger fonts
> until after lunch.
>
> If I have small fonts and I .reset my IDL session,
> I re-run my startup file, and I still have small fonts.
> If I have larger fonts and I .reset my IDL session,
> I continue to have larger fonts.
>
> Does anyone have the faintest idea what might be going
> on here?
```

No because, well, you know, it's IDL :o) Still weird tho'.

I use IDL on linux exclusively (well, sometime on the IBM systems too, but that's v6.something) and have never seen this behaviour. My startup file looks like:

```
DEVICE, TRUE_COLOR=24
DEVICE, RETAIN=2, DECOMP=0
WINDOW, /FREE, /PIXMAP, COLORS = -5
PLOT, [ 0 ]
WDELETE, !D.WINDOW
DEVICE, SET_CHARACTER_SIZE = [ 6, 9 ]
PRINT, 'Number of colors is ', !D.N_COLORS
PRINT, 'Color table size is ', !D.TABLE_SIZE
COLORS
COMPILE_OPT DEFINT32, STRICTARR
```

The only difference I can see is that I issue the DEVICE commands on separate lines. Or maybe the

```
DEVICE, SET_CHARACTER_SIZE = [ 6, 9 ]
should always be issued after the
WINDOW, /FREE, /PIXMAP, COLORS = -5
PLOT, [ 0 ]
WDELETE, !D.WINDOW
??
```

My IDL version:

```
IDL> help, !version,/structure
** Structure !VERSION, 8 tags, length=76, data length=76:
   ARCH      STRING  'x86'
   OS        STRING  'linux'
   OS_FAMILY  STRING  'unix'
   OS_NAME    STRING  'linux'
   RELEASE    STRING  '7.0'
   BUILD_DATE STRING  'Oct 25 2007'
   MEMORY_BITS INT    32
   FILE_OFFSET_BITS
                  INT    64
```

cheers,

paulv

---

---

---

**Subject:** Re: Startup on LINUX Question  
Posted by [R.Bauer](#) on Mon, 08 Jun 2009 08:13:21 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

David Fanning schrieb:

> Folks,  
>  
> I have an IDL startup file on my LINUX machine. The first  
> line in the file is this:  
>  
> DEVICE, RETAIN=2, TRUE\_COLOR=1, SET\_CHARACTER\_SIZE=[9,12]  
>  
> When I start up IDL 7.0.1 in the IDL Workbench this file  
> is executed (there is a print statement at the end of the file  
> to let me know it executed). And, indeed, graphics windows are  
> retained, etc. \*But\* when I issue a plot command, I still have tiny  
> fonts. At some random time during the day (I have no idea when),  
> something in IDL "wakes up" and all of my graphics from then on  
> contain the larger font I specified in my startup file. This  
> can take an hour, sometimes I don't notice the larger fonts  
> until after lunch.  
>  
> If I have small fonts and I .reset my IDL session,  
> I re-run my startup file, and I still have small fonts.  
> If I have larger fonts and I .reset my IDL session,  
> I continue to have larger fonts.  
>  
> Does anyone have the faintest idea what might be going  
> on here?  
>  
> Cheers,

>  
> David

Hi David

[http://www.fz-juelich.de/icg/icg-1/idl\\_icglib/idl\\_source/idl.all](http://www.fz-juelich.de/icg/icg-1/idl_icglib/idl_source/idl.all)  
we never have had that problem.

I am not sure what rerun means. But it sounds a bit you don't have an important env var.

export IDL\_STARTUP=/pwd/your\_startup.pro

We do use the same startup for all of our platforms.

pick up the pieces.

cheers  
Reimar

if float(!version.release) ge 6.0 then path\_cache,/clear,enable=0

```
var=getenv('IDL_PRECOMPILED')
if strpos(var,'1') gt -1 then  DEFSYSV, '!icg', $
    CREATE_STRUCT(NAME='!ICG', 'USER', "", 'HOST', "", 'IDL_SOURCE', "",
'IDLDE', "", 'SEP', " "
    , 'A', ['/idl_work/aaa', '/idl_lib/aaa'
    ,'/idl_precompiled','/idl_links','/idl_work', '/idl_lib',
    '/idl_experiment', '/idl_model','/easy/program/idl', '/idl
    _obsolete'] )
```

```
if strpos(var,'1') eq -1 then  DEFSYSV, '!icg', $
    CREATE_STRUCT(NAME='!ICG', 'USER', "", 'HOST', "", 'IDL_SOURCE', "",
'IDLDE', "", 'SEP', " "
    , 'A', ['/idl_work/aaa', '/idl_lib/aaa'
    ,'/idl_links','/idl_work', '/idl_lib', '/idl_experiment',
    '/idl_model','/easy/program/idl', '/idlObsolete'] )
```

delvar,var

```
; seperator definition
IF !version.os_family EQ 'unix' THEN !icg.sep =':'
IF !version.os_family EQ 'Windows' THEN !icg.sep =','
```

; host and user

```

IF !version.os_family EQ 'unix' THEN BEGIN & SPAWN,'whoami', b &
!icg.user = b & ENDIF
IF !version.os_family EQ 'unix' THEN BEGIN & SPAWN,'hostname', b &
!icg.host = b & ENDIF
IF !version.os_family EQ 'Windows' THEN !icg.user = GETENV('username')
IF !version.os_family EQ 'Windows' THEN !icg.host = GETENV('computername')
!icg.user=STRLOWCASE(!icg.user)
!icg.host=STRLOWCASE(!icg.host)

IDL_SMTP_SRV=GETENV('IDL_SMTP_SRV')

; idl source
!icg.idl_source=GETENV('IDL_SOURCE')
IF !icg.idl_source EQ " THEN PRINT,'DEFINE IDL_SOURCE ENVIRONMENT
VARIABLE, STANDARD PARAMETERS WILL BE USED'

IF !version.os_family EQ 'unix' AND !icg.idl_source EQ " THEN
!icg.idl_source ='/usr/local/icg/icg/idl_source'
IF !version.os_family EQ 'Windows' AND !icg.idl_source EQ " THEN
!icg.idl_source='S:\links\idl_source'

;IF !version.os_family EQ 'unix' AND STRMID(!icg.host,0,3) EQ 'icg'
THEN !icg.idl_source =' /usr/local/icg/icg/idl_source'
;
;IF !version.os_family EQ 'unix' AND STRMID(!icg.host,0,3) EQ 'aix'
THEN !icg.idl_source =' /usr/local/nfs/ich227.icg/icg/idl_source'
;IF !version.os_family EQ 'unix' AND STRMID(!icg.host,0,3) EQ 'zam'
THEN !icg.idl_source =' /usr/local/nfs/idl_source'
;IF !version.os_family EQ 'Windows' THEN
!icg.idl_source=GETENV('IDL_SOURCE')
;IF !icg.idl_source EQ " THEN !icg.idl_source='S:\links\idl_source'

; idlde
IF !version.os_family EQ 'Windows' THEN !icg.idlde=GETENV('IDLDE')
IF !icg.idlde EQ " THEN !icg.idlde!=dir

; grafics
IF !version.os_family EQ 'Windows' then DEVICE, DECOMPOSED=0

;2001-05-10 herausgenommen
;if strlowlcase(!version.os) eq 'linux' then device,decomposed=0
;if strlowlcase(!version.os) eq 'linux' then
window,0,xsize=20,ysize=20,color=256
;if strlowlcase(!version.os) eq 'linux' then wdelete,0

if strlowlcase(!version.os) eq 'linux' then device, get_visual_depth=depth
if strlowlcase(!version.os) eq 'linux' then device, true_color=depth
if strlowlcase(!version.os) eq 'linux' then window, /free, / pixmap,

```

```

colors=-10
if strlowlcase(!version.os) eq 'linux' then wdelete, !d.window
;if strlowlcase(!version.os) eq 'linux' then device,bypass_translation=0
; bug in idl5.5 keine gute Loesung
if strlowlcase(!version.os) eq 'linux' then device, decomposed=0, retain=2
delvar,depth

;2001-05-10 Aenderung abgeschlossen

!p.background=255
!p.color=0
iF !version.os_family EQ 'unix' then device, pseudo_color = 8
IF !version.os_family EQ 'unix' THEN device, retain = 2

; expand path
!icg.a = !icg.idl_source + !icg.a
IF !version.os_family EQ 'unix' AND STRMID(!icg.host,0,3) EQ 'ich' THEN
b='+/usr/local/idl/idl/lib'
IF !version.os_family EQ 'unix' AND STRMID(!icg.host,0,3) EQ 'icg' THEN
b='+/usr/local/idl/idl/lib'
IF !version.os_family EQ 'unix' AND STRMID(!icg.host,0,3) EQ 'aix' THEN
b='+/usr/local/idl/idl/lib'
IF !version.os_family EQ 'unix' AND STRMID(!icg.host,0,3) EQ 'zam' THEN
b='+/usr/local/idl/idl/lib'
IF !version.os_family EQ 'Windows' THEN b=!icg.idlde+'/lib'

; add the icg1 lib for all ICG-1 users
IF !version.os_family EQ 'unix' AND strpos(!icg.user,'icg1') gt -1 then $
b = b + !icg.sep+ '+/usr/local/icg/icg1/idl'

IF !version.os_family EQ 'Windows' AND strpos(!icg.user,'icg1') gt -1 then $
b = b + !icg.sep+ '+S:/links/icg1/idl'

; loop thru all path items
FOR i=0, N_ELEMENTS(!icg.a)-1 DO b=b+!icg.sep+'+'+!icg.a[i]
; expand the path
b = EXPAND_PATH(b)

; Add to existing path
!path = !path+!icg.sep+b

; get rid of used variables
DELVAR, b, i

;default widget font
;IF !VERSION.OS_FAMILY eq 'unix' then
widget_control,default_font='-adobe-helvetica-medium-r-norma l--12-*-*-60-*-*'
if strlowlcase(!version.os) eq 'linux' then

```

```
widget_control,default_font='-adobe-helvetica-medium-r-norma l--12-*-*-*-60-*-*'  
  
IF !VERSION.OS_FAMILY eq 'Windows' then  
  widget_control,default_font='HELVETICA*VARIABLE*14'  
  
; print an informational message  
PRINT, 'Your !PATH settings have been modified by idl.all (Wed Oct 6  
14:12:45 2004)'  
PRINT, '-----'  
PRINT, 'Welcome '+!icg.user+'@'+!icg.host+' to IDL Version: ' +  
!version.release+' !'  
PRINT, 'Current time: '+SYSTIME()
```

---