Subject: Re: How not to plot blank/zero points? Posted by penteado on Sun, 02 Aug 2009 05:17:25 GMT

View Forum Message <> Reply to Message

On Aug 2, 12:50 am, Adam Solomon <rampa...@gmail.com> wrote:

- > I have an array (matrix, about 13 columns) of strings consisting of
- > numbers and blanks*. When I plot the data in each column, the blanks
- > get plotted as zeroes, so if I just plot points, things are OK (as
- > long as I start my plot range above 0), but if I want to connect the
- > points with lines then there are lines going to and from these blank
- > points.

>

- > How do I make IDL not plot these blank points (or points equal to 0)?
- > The only way I've found is by plotting in log (so the points don't
- > even show up) but for various reasons I'd rather not use log.

>

- > *If I were to do this as a floating point array, the blanks all become
- > 0.000, and that doesn't help.

Saying your array is called data, here are 3 ways to do it:

1) Filter out the blanks, using where() to find the points you want, as in:

iplot,data[where(data ne 0.0)]

assuming the blanks are 0.0. If they are empty strings, as your descritpion suggests:

iplot,data[where(data ne ")]

or use whatever value the blanks happen to have in the argument of where()

2) If you want to plot only values in a certain range, use the min_value and/or max_value keywords: iplot,data,min_value=minv with minv of a proper value, higher than 0., and lower than the minimum you want to plot

3) Mark the points you do not want to plot with NaN, as in: data[where(data eq 0.0)]=!values.f_nan iplot,data

Everything with a value of NaN is ignored by iplot.

Subject: Re: How not to plot blank/zero points?
Posted by Adam Solomon on Sun, 02 Aug 2009 05:25:25 GMT
View Forum Message <> Reply to Message

On Aug 1, 10:17 pm, pp <pp.pente...@gmail.com> wrote:

> On Aug 2, 12:50 am, Adam Solomon <rampa...@gmail.com> wrote:

> I have an array (matrix, about 13 columns) of strings consisting of

>> numbers and blanks*. When I plot the data in each column, the blanks

>> get plotted as zeroes, so if I just plot points, things are OK (as

>> long as I start my plot range above 0), but if I want to connect the

>> points with lines then there are lines going to and from these blank

>> points.

>

>> How do I make IDL not plot these blank points (or points equal to 0)?

>> The only way I've found is by plotting in log (so the points don't

>> even show up) but for various reasons I'd rather not use log.

>

>> *If I were to do this as a floating point array, the blanks all become

>> 0.000, and that doesn't help.

>

> Saying your array is called data, here are 3 ways to do it:

>

> 1) Filter out the blanks, using where() to find the points you want,

> as in:

> iplot,data[where(data ne 0.0)]

> assuming the blanks are 0.0. If they are empty strings, as your

> descritpion suggests:

> iplot,data[where(data ne ")]

> or use whatever value the blanks happen to have in the argument of

> where()

>

> 2) If you want to plot only values in a certain range, use the

> min_value and/or max_value keywords:

> iplot,data,min_value=minv

> with minv of a proper value, higher than 0., and lower than the

> minimum you want to plot

>

> 3) Mark the points you do not want to plot with NaN, as in:

> data[where(data eq 0.0)]=!values.f_nan

> iplot,data

> Everything with a value of NaN is ignored by iplot.

Thanks!! I use plot (I'm not sure what iplot is) - will these work with plot as well? Unable to try at the moment.

Subject: Re: How not to plot blank/zero points?
Posted by Adam Solomon on Sun, 02 Aug 2009 19:47:18 GMT
View Forum Message <> Reply to Message

On Aug 1, 10:17 pm, pp <pp.pente...@gmail.com> wrote:

> On Aug 2, 12:50 am, Adam Solomon <rampa...@gmail.com> wrote:

>

- >> I have an array (matrix, about 13 columns) of strings consisting of
- >> numbers and blanks*. When I plot the data in each column, the blanks
- >> get plotted as zeroes, so if I just plot points, things are OK (as
- >> long as I start my plot range above 0), but if I want to connect the
- >> points with lines then there are lines going to and from these blank
- >> points.

>

- >> How do I make IDL not plot these blank points (or points equal to 0)?
- >> The only way I've found is by plotting in log (so the points don't
- >> even show up) but for various reasons I'd rather not use log.

- >> *If I were to do this as a floating point array, the blanks all become
- >> 0.000, and that doesn't help.

>

>

Saying your array is called data, here are 3 ways to do it:

- > 1) Filter out the blanks, using where() to find the points you want.
- > as in:
- > iplot,data[where(data ne 0.0)]
- > assuming the blanks are 0.0. If they are empty strings, as your
- > descritpion suggests:
- > iplot,data[where(data ne ")]
- > or use whatever value the blanks happen to have in the argument of
- > where()

>

- > 2) If you want to plot only values in a certain range, use the
- > min_value and/or max_value keywords:
- > iplot,data,min value=minv
- > with minv of a proper value, higher than 0., and lower than the
- > minimum you want to plot

- > 3) Mark the points you do not want to plot with NaN, as in:
- > data[where(data eq 0.0)]=!values.f_nan
- > iplot,data
- > Everything with a value of NaN is ignored by iplot.

Excellent!! I didn't try #1, but both #2 and #3 worked brilliantly. Thanks.