
Subject: Re: Fun with Int_tabulated.pro

Posted by [Jeremy Bailin](#) on Sat, 31 Oct 2009 15:12:10 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Oct 30, 1:20 pm, wlandsman <wlands...@gmail.com> wrote:

```
> I ran into a couple of gotchas with int_tabulated.pro this
> morning,    It performs numerical integration for the simple case:
>
> IDL> x = findgen(5)
> IDL> y = x^2
> IDL> print,int_tabulated(x,y)
> 21.3333
>
> But if one has flipped both vectors (say while converting wavelength
> to frequency), then -- even though a plot of the two vectors looks
> exactly the same -- int_tabulated gives a different answer.
>
> IDL> x = reverse(x) & y = reverse(y)
> IDL> print,int_tabulated(x,y)
> 42.3619
>
> A closer look at the int_tabulated documentation tells us that if X is
> not monotonic increasing, then one needs to set the /SORT keyword.
> So now we follow the documentation:
>
> IDL> print,int_tabulated(x,y,/sort)
> 21.3333
>
> and get the right answer again.  But as the documentation also "sort"
> of warns
> you, setting the /SORT keyword reorders the input X and Y variables.
> This is
> probably not a problem unless one has modified the Y vector on the fly
> by
> some factor f
>
> f = findgen(5) + 0.5
> print,int_tabulated(x, y*f,/sort)
>
> Upon output, the X vector has been sorted, but the Y vector has not,
> since it
> was passed as part of a temporary variable y*f.  So one has lost
> the one to
> one correspondence between X and Y, screwing up all subsequent
> processing.
>
> --Wayne
```

It looks ridiculous, but here's a workaround:

```
print, int_tabulated(x+0, y*f, /sort)
```

-Jeremy.

Subject: Re: Fun with Int_tabulated.pro

Posted by [pgrigis](#) on Mon, 02 Nov 2009 14:15:36 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Oct 31, 10:12 am, Jeremy Bailin <astroco...@gmail.com> wrote:

> On Oct 30, 1:20 pm, wlandsman <wlands...@gmail.com> wrote:

>

>

>

>> I ran into a couple of gotchas with int_tabulated.pro this

>> morning, It performs numerical integration for the simple case:

>

>> IDL> x = findgen(5)

>> IDL> y = x^2

>> IDL> print,int_tabulated(x,y)

>> 21.3333

>

>> But if one has flipped both vectors (say while converting wavelength

>> to frequency), then -- even though a plot of the two vectors looks

>> exactly the same -- int_tabulated gives a different answer.

>

>> IDL> x = reverse(x) & y = reverse(y)

>> IDL> print,int_tabulated(x,y)

>> 42.3619

>

>> A closer look at the int_tabulated documentation tells us that if X is

>> not monotonic increasing, then one needs to set the /SORT keyword.

>> So now we follow the documentation:

>

>> IDL> print,int_tabulated(x,y,/sort)

>> 21.3333

>

>> and get the right answer again. But as the documentation also "sort"

>> of warns

>> you, setting the /SORT keyword reorders the input X and Y variables.

>> This is

>> probably not a problem unless one has modified the Y vector on the fly

>> by

>> some factor f

>

>> f = findgen(5) + 0.5

```
>> print,int_tabulated(x, y*f,/sort)
>
>> Upon output, the X vector has been sorted, but the Y vector has not,
>> since it
>> was passed as part of a temporary variable y*f. So one has lost
>> the one to
>> one correspondence between X and Y, screwing up all subsequent
>> processing.
>
>> --Wayne
>
> It looks ridiculous, but here's a workaround:
>
> print, int_tabulated(x+0, y*f, /sort)
```

I was looking at that thinking - yes, I see why that would help...
I feel an IDL hangover coming up :)

Ciao,
Paolo

Hint for the less addicted: issue help,x and
help,x+0 to see the subtle difference

```
>
> -Jeremy.
```
