
Subject: Re: Reorganizing 2D FFT for Conventional Viewing [?]
Posted by [Rolf P. W"urtz](#) on Thu, 22 Jun 1995 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

trond@smith.phys.ucalgary.ca (Trond Steinar Trondsen) wrote:
> I'm trying to rearrange the 2D FFT so that zero frq is in the middle,
> and all other frqs end up in the right place.

```
sx = size(x)
y=fft(x, -1)
rearranged = shift(y,sx(1)/2, sx(2)/2)
```

If youre array dimensions are even, zero frq cannot be in the middle,
it ends up at coords sx(1)/2, sx(2)/2.

Greetings
Rolf

Subject: Re: Reorganizing 2D FFT for Conventional Viewing [?]
Posted by [rivers](#) on Thu, 22 Jun 1995 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

In article <3s9jdc\$dsc@ds2.acs.ucalgary.ca>, trond@smith.phys.ucalgary.ca (Trond Steinar Trondsen) writes:

> I'm trying to rearrange the 2D FFT so that zero frq is in the middle,
> and all other frqs end up in the right place. Using the Fourier shift
> theorem prior to transforming does work, but it really slows things down!
> Doing lots of loops to simply rearrange the final array takes a while
> too, and it doesn't look very nice....
> Any _elegant_ (fast) ways of doing this?
>

```
a = fltarr(256, 256)
b = fft(a, 1)
; b will be 256x256 with the zero frequency in the "corners"
b = shift(b, 128, 128) ; Put zero frequency in the middle
```

Mark Rivers	(312) 702-2279 (office)
CARS	(312) 702-9951 (secretary)
Univ. of Chicago	(312) 702-5454 (FAX)
5640 S. Ellis Ave.	(708) 922-0499 (home)
Chicago, IL 60637	rivers@cars3.uchicago.edu (Internet)

Subject: Re: Reorganizing 2D FFT for Conventional Viewing [?]
Posted by [Chris Jacobsen](#) on Fri, 23 Jun 1995 07:00:00 GMT

For 2D FFT, I like to do

```
n=256  
it=complexarr(n,n)  
it_xform=shift(fft(shift(it,n/2,n/2),-1),n/2,n/2)
```
