

---

Subject: Re: lon-lat coordinates for Geotiff images?  
Posted by [David Fanning](#) on Wed, 04 Aug 2010 12:49:20 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Dave Poreh writes:

```
> I have some geotiff images (DEM). I can read these files with:  
> im=read_tiff(file)  
> And I can contour them:  
> CONTOUR, im, /FILL, NLEVELS = 7  
> But in the contour I get the pixel locations in the x-y axis (local  
> coordinates). Does anybody know how could I get lon-lat coordinates in  
> x-y axis?
```

In a contour plot you have some kind of regular (or irregular) grid. That is to say, your labels are labels of straight lines. That is seldom true of a map, where straight lines don't seem to exist.

There is a grid of straight lines associated with a map-projected image, however. This is the XY grid, which can be read directly from the GeoTiff file:

[http://www.dfanning.com/map\\_tips/tiffoverlay.html](http://www.dfanning.com/map_tips/tiffoverlay.html)

I would create these vectors using tools from the Catalyst Library:

```
mapCoord = GeoCoord('mygeoTiffFile.tif')  
mapCoord -> GetProperty, XRANGE=xr, YRANGE=yr  
image = Read_Tiff('mygeoTiffFile.tif')  
s = Size(image, /DIMENSIONS)  
xvec = Scale_Vector(Findgen(s[0]), xr[0], xr[1])  
yvec = Scale_Vector(Findgen(s[1]), yr[0], yr[1])
```

Then, you could draw your contour plot:

```
pos = [0.15, 0.15, 0.9, 0.9]  
Contour, Reverse(image,2), xvec, yvec, XStyle=1, $  
YStyle=1, Position=pos, NLEVELS=7, /FILL
```

If you wanted to know the latitude and longitude of any point in the image, you could convert the XY location to a lon/lat location:

```
mapStruct = mapCoord->GetMapStructure()  
lonlat = Map_Proj_Inverse(x, y, MAP_STRUCTURE=mapStruct)  
lon = lonlat[0]
```

```
lat = lonlat[1]
```

If you wanted to see a lat/lon map grid on your contour map, you could easily add it like this:

```
grid = Obj_New('Map_Grid', MAPCOORD=mapCoord, /AUTODRAW_GRID, $
  COLOR='gray')
mapCoord -> SetProperty, POSITION=pos, GRID_OBJECT=grid
mapCoord -> Draw, /OVERLAYS
```

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

---

Subject: Re: lon-lat coordinates for Geotiff images?  
Posted by [d.poreh](#) on Thu, 05 Aug 2010 09:39:33 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

On Aug 4, 5:49 am, David Fanning <n...@dfanning.com> wrote:

> Dave Poreh writes:

>> I have some geotiff images (DEM). I can read these files with:

>> im=read\_tiff(file)

>> And I can contour them:

>> CONTOUR, im, /FILL, NLEVELS = 7

>> But in the contour I get the pixel locations in the x-y axis (local

>> coordinates). Does anybody know how could I get lon-lat coordinates in

>> x-y axis?

>

> In a contour plot you have some kind of regular (or irregular)

> grid. That is to say, your labels are labels of straight lines.

> That is seldom true of a map, where straight lines don't seem

> to exist.

>

> There is a grid of straight lines associated with a map-

> projected image, however. This is the XY grid, which can

> be read directly from the GeoTiff file:

>

> [http://www.dfanning.com/map\\_tips/tiffoverlay.html](http://www.dfanning.com/map_tips/tiffoverlay.html)

>

> I would create these vectors using tools from the

> Catalyst Library:

>

```
> mapCoord = GeoCoord('mygeoTiffFile.tif')
> mapCoord -> GetProperty, XRANGE=xr, YRANGE=yr
> image = Read_Tiff('mygeoTiffFile.tif')
> s = Size(image, /DIMENSIONS)
> xvec = Scale_Vector(Findgen(s[0]), xr[0], xr[1])
> yvec = Scale_Vector(Findgen(s[1]), yr[0], yr[1])
>
> Then, you could draw your contour plot:
>
> pos = [0.15, 0.15, 0.9, 0.9]
> Contour, Reverse(image,2), xvec, yvec, XStyle=1, $
>   YStyle=1, Position=pos, NLEVELS=7, /FILL
>
> If you wanted to know the latitude and longitude of
> any point in the image, you could convert the XY location
> to a lon/lat location:
>
> mapStruct = mapCoord->GetMapStructure()
> lonlat = Map_Proj_Inverse(x, y, MAP_STRUCTURE=mapStruct)
> lon = lonlat[0]
> lat = lonlat[1]
>
> If you wanted to see a lat/lon map grid on your contour map, you
> could easily add it like this:
>
> grid = Obj_New('Map_Grid', MAPCOORD=mapCoord, /AUTODRAW_GRID, $
>   COLOR='gray')
> mapCoord -> SetProperty, POSITION=pos, GRID_OBJECT=grid
> mapCoord -> Draw, /OVERLAYS
>
> Cheers,
>
> David
> --
> David Fanning, Ph.D.
> Fanning Software Consulting, Inc.
> Coyote's Guide to IDL Programming:http://www.dfanning.com/
> Sepore ma de ni thui. ("Perhaps thou speakest truth.")
```

Thanks David it was very helpful!

Cheers

Dave

---