Subject: Re: concatenate by columns
Posted by David Fanning on Fri, 06 Aug 2010 22:11:55 GMT

View Forum Message <> Reply to Message

Astro Fest writes:

- > Is there a better way to concatenate by columns than converting to
- > rows, concatenating, and converting back? This is the way I'm doing
- > it now, which seems really clunky.

>

- > For example, say I have:
- > IDL> a = indgen(2,10) & b = indgen(2,6)
- > which are placeholders for arrays given by array_indices. I want to
- > get c as a (2,16) array... and currently I'm doing
- > IDL> c = transpose([[transpose(a)],[transpose(b)]])

Yes.

```
IDL> a = indgen(2,10) & b = indgen(2,6)
IDL> c = [[a],[b]]
IDL> help, c
C INT = Array[2, 16]
```

http://www.dfanning.com/tips/array_concatenation.html

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: concatenate by columns Posted by penteado on Fri, 06 Aug 2010 22:15:29 GMT

View Forum Message <> Reply to Message

On Aug 6, 7:02 pm, Astro Fest <astrofes...@gmail.com> wrote:

- > Is there a better way to concatenate by columns than converting to
- > rows, concatenating, and converting back? This is the way I'm doing
- > it now, which seems really clunky.

>

- > For example, say I have:
- > IDL> a = indgen(2,10) & b = indgen(2,6)
- > which are placeholders for arrays given by array_indices. I want to
- > get c as a (2,16) array... and currently I'm doing

> IDL> c = transpose([[transpose(a)],[transpose(b)]])

c=[[a],[b]]