
Subject: Re: alternative to execute available?

Posted by [Foldy Lajos](#) on Wed, 13 Oct 2010 14:22:19 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wed, 13 Oct 2010, chris wrote:

```
> Hi there,  
> I'm often using the _extra keyword in my routines together with a  
> simple approach to give variables values, like this one  
>  
> pro test_ex, _extra=ex  
> for i=0l,n_tags(ex)-1l do _=execute((tag_names(ex))[i]+'=ex.(i)')  
> end  
>  
> If I would call this like: test,/hello,d=dist(10)  
> it would give me within the pro: d with the value dist(10) and hello  
> with the value 1  
>  
> It works fine, but has one big limitation. I cannot use this technique  
> if I would like to produce working binaries (sav-files). Is there any  
> way to avoid the execute call without having information which  
> keywords were passed to the test_ex routine?  
>  
> Thanks and regards  
>  
> CR
```

```
for i=0l,n_tags(ex)-1l do (scope_varfetch((tag_names(ex))[i], /enter))=ex.(i)
```

regards,
lajos

Subject: Re: alternative to execute available?

Posted by [rogass](#) on Wed, 13 Oct 2010 15:00:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

On 13 Okt., 16:22, FÖLDY Lajos <fo...@rmki.kfki.hu> wrote:

```
> On Wed, 13 Oct 2010, chris wrote:  
>> Hi there,  
>> I'm often using the _extra keyword in my routines together with a  
>> simple approach to give variables values, like this one  
>  
>> pro test_ex, _extra=ex  
>> for i=0l,n_tags(ex)-1l do _=execute((tag_names(ex))[i]+'=ex.(i)')  
>> end  
>
```

```
>> If I would call this like: test,/hello,d=dist(10)
>> it would give me within the pro: d with the value dist(10) and hello
>> with the value 1
>
>> It works fine, but has one big limitation. I cannot use this technique
>> if I would like to produce working binaries (sav-files). Is there any
>> way to avoid the execute call without having information which
>> keywords were passed to the test_ex routine?
>
>> Thanks and regards
>
>> CR
>
> for i=0l,n_tags(ex)-1l do (scope_varfetch((tag_names(ex))[i], /enter))=ex.(i)
>
> regards,
> lajos
```

Very cool! THANK YOU!

Cheers

CR

Subject: Re: alternative to execute available?

Posted by [David Fanning](#) on Wed, 13 Oct 2010 15:05:25 GMT

[View Forum Message](#) <> [Reply to Message](#)

Chris writes:

```
>> for i=0l,n_tags(ex)-1l do (scope_varfetch((tag_names(ex))[i], /enter))=ex.(i)
>>
>> regards,
>> lajos
>
> Very cool! THANK YOU!
```

Now you're programming like an iTools developer! ;-)

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.

