

---

Subject: How to speed up or remove this FOR loop  
Posted by [johan\[1\]](#) on Fri, 14 Jan 2011 09:00:25 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

I do have 768 profiles, each 24 pixels long, each to whom I want to fit a Gaussain and getting the mean and SD. I am using the following FOR loop calling mpfitexpr. It works fine but it takes forever to complete!

```
expr = 'P[0] + GAUSS1(X, P[1:3])'

t = indgen(24)
start = [20.D, 10, 2., 1000.]

for i=0,(size(profiles,/dim))[1]-1 do begin
  r = profiles[:,i]
  result = mpfitexpr(expr, t, r, 1, start, /QUIET)
endfor
```

Anyway to speed it up or to remove the FOR loop?

---

---

Subject: Re: How to speed up or remove this FOR loop  
Posted by [wlandsman](#) on Fri, 21 Jan 2011 16:02:35 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

On Friday, January 14, 2011 4:00:25 AM UTC-5, johan wrote:

> I do have 768 profiles, each 24 pixels long, each to whom I want to  
> fit a Gaussain and getting the mean and SD. I am using the following  
> FOR loop calling mpfitexpr. It works fine but it takes forever to  
> complete!

```
>
> expr = 'P[0] + GAUSS1(X, P[1:3])'
>
> t = indgen(24)
> start = [20.D, 10, 2., 1000.]
>
> for i=0,(size(profiles,/dim))[1]-1 do begin
>   r = profiles[:,i]
>   result = mpfitexpr(expr, t, r, 1, start, /QUIET)
> endfor
>
```

Before I had suggested using MPFITFUN instead of MPFITEXPR, which should provide a modest speedup since one doesn't need an indirect function evaluation. Now I am going to suggest not to use the MPFIT\* routines at all, but to instead use the ITTVIS supplied GAUSSFIT(). The MPFIT\* routines are more robust, with more checking for overflows, NaNs and more user diagnostics, but for simple Gaussian fits the overhead for GAUSSFIT() is \*much\* lower. (A factor of 4 speedup is possible.) --Wayne

---

Subject: Re: How to speed up or remove this FOR loop  
Posted by [johan\[1\]](#) on Wed, 26 Jan 2011 00:12:49 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

On Jan 21, 4:02 pm, wlandsman <wlands...@gmail.com> wrote:

> On Friday, January 14, 2011 4:00:25 AM UTC-5, johan wrote:

>> I do have 768 profiles, each 24 pixels long, each to whom I want to  
>> fit a Gaussain and getting the mean and SD. I am using the following  
>> FOR loop calling mpfitexpr. It works fine but it takes forever to  
>> complete!

>

>> expr = 'P[0] + GAUSS1(X, P[1:3])'

>

>> t = indgen(24)

>> start = [20.D, 10, 2., 1000.]

>

>> for i=0,(size(profiles,/dim))[1]-1 do begin

>>       r = profiles[:,i]

>>       result = mpfitexpr(expr, t, r, 1, start, /QUIET)

>>   endfor

>

> Before I had suggested using MPFITFUN instead of MPFITEXPR, which should provide a modest speedup since one doesn't need an indirect function evaluation. Now I am going to suggest not to use the MPFIT\* routines at all, but to instead use the ITTVIS supplied GAUSSFIT(). The MPFIT\* routines are more robust, with more checking for overflows, NANs and more user diagnostics, but for simple Gaussian fits the overhead for GAUSSFIT() is \*much\* lower. (A factor of 4 speedup is possible.) --Wayne

I did end up using the native Gaussfit and it works fine and fast. It is a lot of fitting but it as you said, simple fits. Thanks!

---