
Subject: Re: draw spheres in 3D space
Posted by [Junum](#) on Mon, 06 Jun 2011 18:53:41 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 1:50 pm, Junum <junshi...@gmail.com> wrote:

> Hello,
>
> I wan to know how to draw spheres in 3D space with xyz axes.
> For example, I have 7 spheres with radius of 1 and its center is at
> (0,0,0)
> (2,0,0)
> (-2,0,0)
> (0,2,0)
> (0,-2,0)
> (0,0,2)
> (0,0,-1).
> Since I don't have idea for 3D drawing, it is hard to start.
> Could you let me know any clue, help, suggestion?
> Thank you very much.
>
> Sincerely,
> Jun

There was a typo.

A center of the last sphere should be (0,0,-2).

Jun

Subject: Re: draw spheres in 3D space
Posted by [penteado](#) on Mon, 06 Jun 2011 19:03:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 3:53 pm, Junum <junshi...@gmail.com> wrote:

> On Jun 6, 1:50 pm, Junum <junshi...@gmail.com> wrote:
>
>
>
>
>
>
>> Hello,
>
>> I wan to know how to draw spheres in 3D space with xyz axes.
>> For example, I have 7 spheres with radius of 1 and its center is at
>> (0,0,0)
>> (2,0,0)
>> (-2,0,0)
>> (0,2,0)

```
>> (0,-2,0)
>> (0,0,2)
>> (0,0,-1).
>> Since I don't have idea for 3D drawing, it is hard to start.
>> Could you let me know any clue, help, suggestion?
>> Thank you very much.
```

```
>
>> Sincerely,
>> Jun
>
> There was a typo.
> A center of the last sphere should be (0,0,-2).
>
> Jun
```

```
xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0,-2]]
p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
undocumented,linestyle='none')
```

Subject: Re: draw spheres in 3D space
Posted by [Junum](#) on Mon, 06 Jun 2011 19:14:05 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 2:03 pm, Paulo Penteado <pp.pente...@gmail.com> wrote:

```
> On Jun 6, 3:53 pm, Junum <junshi...@gmail.com> wrote:
```

```
>
>
>
>
>
>
```

```
>> On Jun 6, 1:50 pm, Junum <junshi...@gmail.com> wrote:
```

```
>
>>> Hello,
```

```
>
```

```
>>> I wan to know how to draw spheres in 3D space with xyz axes.
```

```
>>> For example, I have 7 spheres with radius of 1 and its center is at
```

```
>>> (0,0,0)
```

```
>>> (2,0,0)
```

```
>>> (-2,0,0)
```

```
>>> (0,2,0)
```

```
>>> (0,-2,0)
```

```
>>> (0,0,2)
```

```
>>> (0,0,-1).
```

```
>>> Since I don't have idea for 3D drawing, it is hard to start.
```

```
>>> Could you let me know any clue, help, suggestion?
```

```
>>> Thank you very much.
```

```
>
```

```

>>> Sincerely,
>>> Jun
>
>> There was a typo.
>> A center of the last sphere should be (0,0,-2).
>
>> Jun
>
> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
> undocumented,linestyle='none')

```

Thank you for suggestion, but I got error message,

```

IDL> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
IDL> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
undocumented,linestyle='none')

```

```

p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
undocumented,linestyle='none')
      ^

```

% Syntax error.

I am using IDL 7.0.

Subject: Re: draw spheres in 3D space

Posted by [David Fanning](#) on Mon, 06 Jun 2011 19:19:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

Paulo Penteado writes:

```

> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
> undocumented,linestyle='none')

```

I admit that's pretty cool. But what does a "radius of one" mean in this context? For example, here are orb objects with a radius of 5, but clearly this radius has nothing whatsoever to do with the axes:

```

p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*], $
sym_object=orb(radius=5),/ undocumented,$
linestyle='none')

```

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: <http://www.idlcoyote.com/>

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: draw spheres in 3D space

Posted by [Michael Galloy](#) on Mon, 06 Jun 2011 19:21:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

On 6/6/11 1:14 PM, Junum wrote:

> On Jun 6, 2:03 pm, Paulo Penteado<pp.pente...@gmail.com> wrote:

>> On Jun 6, 3:53 pm, Junum<junshi...@gmail.com> wrote:

>>

>>

>>

>>

>>

>>> On Jun 6, 1:50 pm, Junum<junshi...@gmail.com> wrote:

>>

>>>> Hello,

>>

>>>> I wan to know how to draw spheres in 3D space with xyz axes.

>>>> For example, I have 7 spheres with radius of 1 and its center is at

>>>> (0,0,0)

>>>> (2,0,0)

>>>> (-2,0,0)

>>>> (0,2,0)

>>>> (0,-2,0)

>>>> (0,0,2)

>>>> (0,0,-1).

>>>> Since I don't have idea for 3D drawing, it is hard to start.

>>>> Could you let me know any clue, help, suggestion?

>>>> Thank you very much.

>>

>>>> Sincerely,

>>>> Jun

>>

>>> There was a typo.

>>> A center of the last sphere should be (0,0,-2).

>>

>>> Jun

>>

>> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0,-2]]

>> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/

>> undocumented,linestyle='none')

```
>
> Thank you for suggestion, but I got error message,
>
> IDL> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
> IDL> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
> undocumented,linestyle='none')
>
> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
> undocumented,linestyle='none')
>                                     ^
> % Syntax error.
>
> I am using IDL 7.0.
```

This should work on older versions of IDL:

```
model = obj_new('IDLgrModel')
model->add, obj_new('orb', pos=[ 0, 0, 0], radius=1., color=[255, 215, 0])
model->add, obj_new('orb', pos=[ 2, 0, 0], radius=1., color=[255, 215, 0])
model->add, obj_new('orb', pos=[-2, 0, 0], radius=1., color=[255, 215, 0])
model->add, obj_new('orb', pos=[ 0, 2, 0], radius=1., color=[255, 215, 0])
model->add, obj_new('orb', pos=[ 0,-2, 0], radius=1., color=[255, 215, 0])
model->add, obj_new('orb', pos=[ 0, 0, 2], radius=1., color=[255, 215, 0])
model->add, obj_new('orb', pos=[ 0, 0,-2], radius=1., color=[255, 215, 0])
```

xobjview, model

Mike

--

Michael Galloy

www.michaelgalloy.com

Modern IDL, A Guide to Learning IDL: <http://modernidl.idldev.com>

Research Mathematician

Tech-X Corporation

Subject: Re: draw spheres in 3D space

Posted by [penteado](#) on Mon, 06 Jun 2011 19:26:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 4:14 pm, Junum <junshi...@gmail.com> wrote:

```
> Thank you for suggestion, but I got error message,
>
> IDL> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
> IDL> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
> undocumented,linestyle='none')
>
> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
```

```
> undocumented,linestyle='none')
>                                     ^
> % Syntax error.
>
> I am using IDL 7.0.
```

That will not work in 7.0. This will:

```
xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
orb=obj_new('orb')
iplot,xyz,/scatter,sym_object=orb
```

Subject: Re: draw spheres in 3D space
Posted by [Junum](#) on Mon, 06 Jun 2011 19:31:22 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 2:21 pm, Michael Galloy <mgal...@gmail.com> wrote:

```
> On 6/6/11 1:14 PM, Junum wrote:
```

```
>
>
>
>
>
>
```

```
>> On Jun 6, 2:03 pm, Paulo Penteado<pp.pente...@gmail.com> wrote:
```

```
>>> On Jun 6, 3:53 pm, Junum<junshi...@gmail.com> wrote:
```

```
>
```

```
>>>> On Jun 6, 1:50 pm, Junum<junshi...@gmail.com> wrote:
```

```
>
```

```
>>>> > Hello,
```

```
>
```

```
>>>> > I wan to know how to draw spheres in 3D space with xyz axes.
```

```
>>>> > For example, I have 7 spheres with radius of 1 and its center is at
```

```
>>>> > (0,0,0)
```

```
>>>> > (2,0,0)
```

```
>>>> > (-2,0,0)
```

```
>>>> > (0,2,0)
```

```
>>>> > (0,-2,0)
```

```
>>>> > (0,0,2)
```

```
>>>> > (0,0,-1).
```

```
>>>> > Since I don't have idea for 3D drawing, it is hard to start.
```

```
>>>> > Could you let me know any clue, help, suggestion?
```

```
>>>> > Thank you very much.
```

```
>
```

```
>>>> > Sincerely,
```

```
>>>> > Jun
```

```
>
```

```
>>>> There was a typo.
```

```

>>>> A center of the last sphere should be (0,0,-2).
>
>>>> Jun
>
>>> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0,-2]]
>>> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
>>> undocumented,linestyle='none')
>
>> Thank you for suggestion, but I got error message,
>
>> IDL> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0,-2]]
>> IDL> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
>> undocumented,linestyle='none')
>
>> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
>> undocumented,linestyle='none')
>>                                     ^
>> % Syntax error.
>
>> I am using IDL 7.0.
>
> This should work on older versions of IDL:
>
> model = obj_new('IDLgrModel')
> model->add, obj_new('orb', pos=[ 0, 0, 0], radius=1., color=[255, 215, 0])
> model->add, obj_new('orb', pos=[ 2, 0, 0], radius=1., color=[255, 215, 0])
> model->add, obj_new('orb', pos=[-2, 0, 0], radius=1., color=[255, 215, 0])
> model->add, obj_new('orb', pos=[ 0, 2, 0], radius=1., color=[255, 215, 0])
> model->add, obj_new('orb', pos=[ 0,-2, 0], radius=1., color=[255, 215, 0])
> model->add, obj_new('orb', pos=[ 0, 0, 2], radius=1., color=[255, 215, 0])
> model->add, obj_new('orb', pos=[ 0, 0,-2], radius=1., color=[255, 215, 0])
>
> xobjview, model
>
> Mike
> --
> Michael Galloywww.michaelgalloy.com
> Modern IDL, A Guide to Learning IDL:http://modernidl.idldev.com
> Research Mathematician
> Tech-X Corporation

```

Thank you very much for help.
 It is really cool.
 How can I add xyz axes on this plot?
 Thank you.

Jun

Subject: Re: draw spheres in 3D space
Posted by [Junum](#) on Mon, 06 Jun 2011 19:40:04 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 2:26 pm, Paulo Penteado <pp.pente...@gmail.com> wrote:

```
> On Jun 6, 4:14 pm, Junum <junshi...@gmail.com> wrote:
>
>> Thank you for suggestion, but I got error message,
>
>> IDL> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
>> IDL> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
>> undocumented,linestyle='none')
>
>> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
>> undocumented,linestyle='none')
>>                                     ^
>> % Syntax error.
>
>> I am using IDL 7.0.
>
> That will not work in 7.0. This will:
>
> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
> orb=obj_new('orb')
> iplot,xyz,/scatter,sym_object=orb
```

Dear Paulo Penteado

Thank you for your help.

Now I don't have any problem, except symbols are too small.

I can change symbol size manually, but what I wanted is seven spheres attached, so I specified size and center of spheres.

Can I specify the size of sphere?

Thank you.

Jun

Subject: Re: draw spheres in 3D space
Posted by [penteado](#) on Mon, 06 Jun 2011 23:15:29 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 4:19 pm, David Fanning <n...@idlcoyote.com> wrote:

```
> Paulo Penteado writes:
>> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
>> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
>> undocumented,linestyle='none')
>
```



```

> I admit that's pretty cool. But what does a "radius
> of one" mean in this context? For example, here are
> orb objects with a radius of 5, but clearly this
> radius has nothing whatsoever to do with the axes:
>
> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*], $
>   sym_object=orb(radius=5),/ undocumented,$
>   linestyle='none')

```

Yes, I had not noticed that a "hard" radius was intended. Those sizes are unrelated to the data space because the spheres are taken as plot symbols, and as such have "soft" sizes. You can see that if you change the size of the window: the symbols will remain the same size, while the axes will change.

Borrowing from Mike's example, this could be done with `iplot` (similarly with `plot3d()`) by making a bunch of spheres with the proper sizes and positions in a model, then putting that model into the plot's data space:

```

xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0,-2]]
model = obj_new('IDLgrModel')
for i=0,6 do model-
> add,obj_new('orb',pos=xyz[*],radius=1.,color=[255, 215, 0])
iplot,xyz,/scale_isotropic,/scatter,sym_index=0
id=itgetcurrent(tool=ot)
oplot3d=ot->getbyidentifier(ot->findidentifiers('*PLOT3D',/
visualization))
oplot3d->add,model

```

Subject: Re: draw spheres in 3D space
 Posted by [Junum](#) on Tue, 07 Jun 2011 04:26:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Jun 6, 6:15 pm, Paulo Penteado <pp.pente...@gmail.com> wrote:

```

> On Jun 6, 4:19 pm, David Fanning <n...@idlcoyote.com> wrote:
>

```

```

>> Paulo Penteado writes:

```

```

>>> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0,-2]]
>>> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*],sym_object=orb(),/
>>> undocumented,linestyle='none')
>

```

```

>> I admit that's pretty cool. But what does a "radius
>> of one" mean in this context? For example, here are
>> orb objects with a radius of 5, but clearly this
>> radius has nothing whatsoever to do with the axes:
>

```

```

>> p=plot3d(xyz[0,*],xyz[1,*],xyz[2,*], $
>>   sym_object=orb(radius=5),/ undocumented,$
>>   linestyle='none')
>
> Yes, I had not noticed that a "hard" radius was intended. Those sizes
> are unrelated to the data space because the spheres are taken as plot
> symbols, and as such have "soft" sizes. You can see that if you change
> the size of the window: the symbols will remain the same size, while
> the axes will change.
>
> Borrowing from Mike's example, this could be done with iplot
> (similarly with plot3d()) by making a bunch o spheres with the proper
> sizes and positions in a model, then putting that model into the
> plot's data space:
>
> xyz=[[0,0,0],[2,0,0],[-2,0,0],[0,2,0],[0,-2,0],[0,0,2],[0,0, -2]]
> model = obj_new('IDLgrModel')
> for i=0,6 do model->add,obj_new('orb',pos=xyz[*],radius=1.,color=[255, 215, 0])
>
> iplot,xyz,/scale_isotropic,/scatter,sym_index=0
> id=itgetcurrent(tool=ot)
> oplot3d=ot->getbyidentifier(ot->findidentifiers('*PLOT3D',/
> visualization))
> oplot3d->add,model

```

Thank very much Paulo.
It helps me a lot.

Jun
