Subject: Reading 32-bit complex numbers in IDL (16-bit real / 16-bit imaginary) Posted by Waqas A. Qazi on Sun, 07 Aug 2011 12:01:34 GMT

View Forum Message <> Reply to Message

Hi,

I couldn't find a discussion of this specific problem on the group, so I am posting it here in hope of a solution.

I have complex data in a binary file, with each value comprising of 4 bytes (32 bits), such that the 32-bit complex number consists of 16-bit real and 16-bit imaginary. I could use define a complex array in IDL and then read the data using the readu command, however the "complex" format in IDL is a 2*32-bit definition, i.e. 32-bit real and 32-bit imaginary. How can I read the 16-bit real - 16-bit imaginary complex number in IDL?

Thanks, Waqas.

Subject: Re: Reading 32-bit complex numbers in IDL (16-bit real / 16-bit imaginary) Posted by Waqas A. Qazi on Mon, 15 Aug 2011 17:58:43 GMT View Forum Message <> Reply to Message

On Aug 13, 6:26 am, Wox <s...@nomail.com> wrote:

- When I say "convert integer to float" I don't mean that you would
 convert 10 to 10.0 for example. The value of the integer is not
 concidered at all, it's the "bit-content" that is used. The integer is
 just a bag of bits that represent a foating point number according to
- > the IEEE754 standard. That's why the function is call BINARYTOFLOAT
- > and not INTEGERTOFLOAT or something. In the example I gave:
- > > IDL> integer='3555'x
- > IDL> f=binarytofloat(integer,precision=0)
- > IDL> print,integer
- > 13653
- > IDL> print,f
- > 0.333252
- > You can see that the integer value 13653 has nothing to do with
- > 0.33325... However both numbers have the same binary representation,
- > namely

>

- > IDL> print,integer,format='(b016)'
- > 0011010101010101

>

- > Note: Since IDL can't handle 16bit floats, the binary representation
- > of f (32bit float) isn't the same anymore as that of 13653. The value
- > of f is correct however: the value represented by 13653 under the
- > half-precision IEEE 754 convention.

Great, thanks Wox, I understand now.

For the specific data I am working with, its not half-precision per se, because the 2-byte binary numbers are defined as integers, not floats. So after reading the 2-byte integers from the binary file, I will not need to convert to any float. I can read each alternating 2byte integer into separate real and imaginary part arrays, and then input these two arrays directly into the complex function (data type converter) in IDL.

Thanks, Waqas.