
Subject: Re: Using PS_START to create A4 Landscape postscript?

Posted by [Matthew](#) on Thu, 29 Sep 2011 19:42:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

You can try something like this:

```
device, 'ps', filename='A4.ps', xsize=21.0/2.54 , ysize=29.7/2.54, /
inches
```

A4 paper is 210x297mm and there are 2.54cm/inch. To remove the margins, you will have to do some work. After you make your last call to DEVICE (as above), you can try the following. Define "margins" to be a 4 element vector: [left_margin, bottom_margin, right_margin, top_margin] where *_margin are the widths of the margins in normal coordinates. In your case [0.0, 0.0, 1.0, 1.0].

This bit of code calculates the region and window of the plot (read about ![xyz].region, ![xyz].window, !p.region, !p.window) in the IDL help files. The end result, "position" will give you the location of the plot in normal coordinates that you can pass to PLOT, etc.

Note that I have tried this in the display window, but not for ps plots yet. I have to call PLOT to initialize the system variables related to plots (!p and ![xyz]).

```
margins_norm = margins
```

```
;initialize the plot region
```

```
plot, !x.range, !y.range, /nodata, /noerase, xstyle=4, ystyle=4
```

```
;convert the margins from normal coordinates to device coordinates
;this would be useful for printing square plots to preserve aspect
ratio
```

```
margins_dev = margins_norm
```

```
margins_dev[0] = margins_norm[0] * !d.x_vsize
```

```
margins_dev[2] = margins_norm[2] * !d.x_vsize
```

```
margins_dev[1] = margins_norm[1] * !d.y_vsize
```

```
margins_dev[3] = margins_norm[3] * !d.y_vsize
```

```
;character size in normal coordinates
```

```
xcharsize = !d.x_ch_size / !d.x_vsize
```

```
ycharsize = !d.y_ch_size / !d.y_vsize
```

```
;Calculate the size of the plotting region. This is the total area of
```

```

the plot,
;including axis labels and titles
x_region = fltarr(2)
y_region = fltarr(2)
x_region[0] = 0.0 + margins_norm[0]
x_region[1] = 1.0 - margins_norm[2]
y_region[0] = 0.0 + margins_norm[1]
y_region[1] = 1.0 - margins_norm[3]
p_region = [x_region[0], y_region[0], x_region[1], y_region[1]]

;Calculate the size of the plot window. This is the region contained
within the
;axes and does not include title, ticklabels, etc.
;Note that the main title is 1.25 times larger than the normal font
size.(ycharsize*1.25).
;the axes need room for tick labels AND axis titles (xcharsize*2.0),
;and the x-axis title/offset subtracts from the space in the y-
direction
x_window = fltarr(2)
y_window = fltarr(2)
x_window[0] = x_region[0] + myttl_offset + xcharsize*2.0
x_window[1] = x_region[1] ;no labels on the right side of
the region
y_window[0] = y_region[0] + mxttl_offset + ycharsize*2.0
y_window[1] = y_region[1] - mttl_offset - ycharsize*1.25
p_window = [x_window[0], y_window[0], x_window[1], y_window[1]]

;calculate the height and width of each individual plot window
plot_width = (p_window[2] - p_window[0]) / ncols
plot_height = (p_window[3] - p_window[1]) / nrows

positions[0] = p_window[0]
positions[1] = p_window[1]
positions[2] = p_window[0] + plot_width
positions[3] = p_window[1] + plot_height

```

Subject: Re: Using PS_START to create A4 Landscape postscript?
 Posted by [Matthew](#) on Thu, 29 Sep 2011 21:28:40 GMT
[View Forum Message](#) <> [Reply to Message](#)

I have found that this does not provide enough space on the left side of the plot for the title on the y axis. This is because the number of characters used to label the tickmarks is different depending on your scale. I am continuing to fiddle with it.

Subject: Re: Using PS_START to create A4 Landscape postscript?
Posted by [David Fanning](#) on Thu, 29 Sep 2011 23:36:47 GMT
[View Forum Message](#) <> [Reply to Message](#)

Rob writes:

> I'm sure this is simple but I can't quite get it to work.
>
> I want to create an A4 landscape postscript file where the plot takes
> up the entire window (i.e. no margins).
>
> I thought I could do this: PS_Start, FILENAME='plot.ps', chasize=1,
> landscape=1, page='A4' but it doesn't seem to work.
>
> I specifically don't want to use the psconfig GUI as this needs to run
> in a loop and create multiple plots, but I thought I could set the
> keywords in ps_start without needing to use ps_config.
>
> Can someone point me in the right direction?

What you are doing here is setting the page size and orientation of the plot. You are not doing anything to set the "window" on the PostScript page where the plot will be located.

Presumably "it doesn't seem to work" means you don't like the defaults PS_Start is choosing for you. If so, then by all means choose your own. The XSIZE, YSIZE, XOFFSET and YOFFSET keywords are the ones you want to use.

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: <http://www.idlcoyote.com/>
Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Using PS_START to create A4 Landscape postscript?
Posted by [rjp23](#) on Fri, 30 Sep 2011 15:09:47 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Sep 30, 12:36 am, David Fanning <n...@dfanning.com> wrote:

- > What you are doing here is setting the page size
- > and orientation of the plot. You are not doing
- > anything to set the "window" on the PostScript
- > page where the plot will be located.
- >
- > Presumably "it doesn't seem to work" means you
- > don't like the defaults PS_Start is choosing for
- > you. If so, then by all means choose your own.
- > The XSIZE, YSIZE, XOFFSET and YOFFSET keywords
- > are the ones you want to use.

Ah I see now. I didn't realise the differentiation between the window and the device. Thanks again :-)
