Subject: Coyote Graphics Updates Posted by David Fanning on Thu, 08 Dec 2011 15:16:05 GMT View Forum Message <> Reply to Message

Folks.

I'm not sure what accounts for the burst in activity in the past week (fears of having to get a real job again, probably!), but I have changed 28 of the 41 Coyote Graphics routines in the past week!

Most of the changes have been documentation changes, as I am switching to the IDLDOC rst method for all new programs, and I wanted to retrofit all of my Coyote Graphics programs so I could have a good set of on-line documentation. There are still niggling typos, etc., but you can find the on-line documentation here:

http://www.idlcoyote.com/idldoc/cg/index.html

There have also been changes to some well-used programs.

cgColor -- I have modified this grandfather of all Coyote Graphics programs to be a bit more useful. It will now accept a three-element array (a color triple) as input, so you can specify *exactly* what color your want in a device and color model independent way. It will also accept byte and integer values, and it will treat such values as indices into the current color table. Previously, you had to make a string of these values first (i.e., '215', rather than just 215). It will also complain vociferously now if you pass it the ambiguous long integer.

Eventually, this will make specifying colors for all Coyote Graphics routines more robust, but we see the effects immediately in changes to cgColorbar.

cgColorBar -- The biggest change to cgColorBar is the ability now to include "out-of-bounds" colors as triangles on either end of the color bar. The keyword OOB_Low and OOB_High allow you to specify the colors you want to use and take advantage of cgColor's new functionality so there are LOTS of options on how you specify the colors you want to use. The shape of the triangle can be adjusted with the OOB_Factor keyword, for those of you who are anal about such

things.

I find I use cgColorBar very often with a handful of colors, and I would like the colors to look like distinct rectangles, in the manner of cgDCBar. This involves some manipulation of keywords, that I think a lot of people don't know how to use. So, I have added a Discrete keyword, that just sets this up for me.

```
cgLoadCT, 33, NColors=10 cgColorbar, NColors=10, /Discrete
```

To add out-of-bounds colors, you do this. Note that the OOB colors are independent of each other. You can use one without the other.

```
cgErase
cgColorbar, NColors=10, /Discrete, $
OOB_Low='white', OOB_High='Black'
```

One motivation for the color bar changes was a desire to make a color bar that more accurately reflects the reality of a filled contour plot.

Often, we create a filled contour plot with a color bar like this:

```
data = cgDemoData(2)
cgLoadCT, 33, NColors=10, Bottom=1
step = (Max(data) - Min(data)) / 10
levels = Indgen(10)*step + Min(data)
cgContour, data, Levels=levels, /Fill, $
Position=[0.1, 0.1, 0.9, 0.825], C_Colors=Indgen(10)+1
cgContour, data, Levels=levels, /Overplot
cgColorbar, NColors=10, Bottom=1, $
Range=[Min(data), Max(data)], Discrete
```

But, this gives us fairly arbitrary contour levels. We often want the levels of our choosing, but when we do so, the last level usually means something like "this color represents all values above this level". In other words, we want something that looks like this:

```
data = cgDemoData(2)
cgLoadCT, 33, NColors=10, Bottom=1
levels = Indgen(10)*150
cgContour, data, Levels=levels, /Fill, $
Position=[0.1, 0.1, 0.9, 0.825], C_Colors=Indgen(10)+1
```

cgContour, data, Levels=levels, /Overplot cgColorbar, NColors=9, Bottom=1, OOB High=10, \$ Range=[Min(levels), Max(levels)], /Discrete

To make this even easier to do, I have added a new OLEVELS keyword to cgContour, so that you can, if you need to, fetch the contour levels that the program actually uses. So now, you can do the same thing, but using NLevels in the cgContour call in the usual way:

data = cqDemoData(2)cgLoadCT, 33, NColors=10, Bottom=1 cgContour, data, NLevels=10, /Fill, OLevels=levels, \$ Position=[0.1, 0.1, 0.9, 0.825], C_Colors=Indgen(10)+1 cgContour, data, Levels=levels, /Overplot cgColorbar, NColors=9, Bottom=1, OOB_High=10, \$ Range=[Min(levels), Max(levels)], /Discrete

cgPS2PDF -- The functionality that caused the biggest change to Coyote Graphics programs was the addition of the cgPS2PDF program that allows me to create PDF files in a machine-independent way from PostScript intermediary files.

I know people use a lot of different routines to do this, and I have tried to retain that kind of flexibility in this program. I'm not out to reinvent the wheel, I just really want the ability to make PDF files from within cgWindow! :-)

This program will use Ghostscript on Windows and UNIX machines, and pstopdf on Macs. If you don't want to use the "gs" command on UNIX machines, you can choose the command you do want to use. For example, the "epstopdf" command probably works better with encapsulated PostScript files than does the "gs" command. You can make that substitution in the program.

A number of Coyote Graphics programs changed to accommodate this new functionality. Among them are cgWindow, cgControl, cgWindow SetDefs, cgWindow GetDefs, and PS End. I wouldn't be surprised if there were others as well.

You can find all of these changes in the latest Coyote Library distribution:

http://www.idlcoyote.com/programs/zip_files/coyoteprograms.z ip

Or, using Subversion at:

http://idl-coyote.googlecode.com/svn/tags/coyote/coyote_libr ary_1.4

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: http://www.idlcoyote.com/

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Coyote Graphics Updates Posted by MariLiza on Tue, 13 Dec 2011 14:16:16 GMT View Forum Message <> Reply to Message

Thanks David!!! :) Your hard work is truly appreciated!!!! All around the World!!!

:-)

-MariLiza

On Dec 8, 5:16 pm, David Fanning <n...@dfanning.com> wrote:

> Folks,

>

- > I'm not sure what accounts for the burst in activity
- > in the past week (fears of having to get a real job
- > again, probably!), but I have changed 28 of the 41
- > Coyote Graphics routines in the past week!

>

- > Most of the changes have been documentation changes,
- > as I am switching to the IDLDOC rst method for all
- > new programs, and I wanted to retrofit all of my
- > Coyote Graphics programs so I could have a good
- > set of on-line documentation. There are still
- > niggling typos, etc., but you can find the on-line
- > documentation here:

>

> http://www.idlcoyote.com/idldoc/cg/index.html

> >

- > There have also been changes to some well-used programs.
- > cgColor -- I have modified this grandfather of all
- > Coyote Graphics programs to be a bit more useful.
- > It will now accept a three-element array (a color
- > triple) as input, so you can specify *exactly* what
- > color your want in a device and color model independent
- > way. It will also accept byte and integer values, and it

```
> will treat such values as indices into the current
> color table. Previously, you had to make a string of
> these values first (i.e., '215', rather than just 215).
> It will also complain vociferously now if you pass
> it the ambiguous long integer.
> Eventually, this will make specifying colors for all
> Coyote Graphics routines more robust, but we see the
> effects immediately in changes to cgColorbar.
>
> cgColorBar -- The biggest change to cgColorBar is
> the ability now to include "out-of-bounds" colors
> as triangles on either end of the color bar. The
> keyword OOB_Low and OOB_High allow you to specify the
> colors you want to use and take advantage of cgColor's
> new functionality so there are LOTS of options on
> how you specify the colors you want to use. The shape
> of the triangle can be adjusted with the OOB_Factor
> keyword, for those of you who are anal about such
> things.
>
> I find I use cgColorBar very often with a handful
> of colors, and I would like the colors to look like
> distinct rectangles, in the manner of cgDCBar. This
> involves some manipulation of keywords, that I think
 a lot of people don't know how to use. So, I have added
  a Discrete keyword, that just sets this up for me.
>
    cqLoadCT, 33, NColors=10
>
    cgColorbar, NColors=10, /Discrete
>
> To add out-of-bounds colors, you do this. Note
 that the OOB colors are independent of each
  other. You can use one without the other.
>
    cgErase
>
    cgColorbar, NColors=10, /Discrete, $
>
      OOB_Low='white', OOB_High='Black'
>
> One motivation for the color bar changes was a desire
> to make a color bar that more accurately reflects the
  reality of a filled contour plot.
> Often, we create a filled contour plot with a color bar
> like this:
>
   data = cqDemoData(2)
   cqLoadCT, 33, NColors=10, Bottom=1
```

```
step = (Max(data) - Min(data)) / 10
   levels = Indgen(10)*step + Min(data)
>
   cgContour, data, Levels=levels, /Fill, $
>
    Position=[0.1, 0.1, 0.9, 0.825], C_Colors=Indgen(10)+1
>
   cgContour, data, Levels=levels, /Overplot
>
   cgColorbar, NColors=10, Bottom=1, $
>
      Range=[Min(data), Max(data)], Discrete
>
>
> But, this gives us fairly arbitrary contour levels. We often
> want the levels of our choosing, but when we do so, the last
> level usually means something like "this color represents all
> values above this level". In other words, we want something
> that looks like this:
>
   data = cgDemoData(2)
>
   cgLoadCT, 33, NColors=10, Bottom=1
>
   levels = Indgen(10)*150
>
   cgContour, data, Levels=levels, /Fill, $
>
    Position=[0.1, 0.1, 0.9, 0.825], C Colors=Indgen(10)+1
>
   cgContour, data, Levels=levels, /Overplot
   cgColorbar, NColors=9, Bottom=1, OOB High=10, $
>
      Range=[Min(levels), Max(levels)], /Discrete
>
>
> To make this even easier to do, I have added a new OLEVELS
> keyword to cgContour, so that you can, if you need to, fetch
> the contour levels that the program actually uses. So now,
> you can do the same thing, but using NLevels in the
> cgContour call in the usual way:
>
   data = cgDemoData(2)
>
   cqLoadCT, 33, NColors=10, Bottom=1
   cgContour, data, NLevels=10, /Fill, OLevels=levels, $
>
    Position=[0.1, 0.1, 0.9, 0.825], C_Colors=Indgen(10)+1
>
   cgContour, data, Levels=levels, /Overplot
   cgColorbar, NColors=9, Bottom=1, OOB_High=10, $
>
      Range=[Min(levels), Max(levels)], /Discrete
>
>
> cgPS2PDF -- The functionality that caused the biggest change
> to Coyote Graphics programs was the addition of the
> cgPS2PDF program that allows me to create PDF files
> in a machine-independent way from PostScript intermediary
> files.
>
> I know people use a lot of different routines to do this,
> and I have tried to retain that kind of flexibility in this
> program. I'm not out to reinvent the wheel, I just really
> want the ability to make PDF files from within cgWindow! :-)
>
```

- > This program will use Ghostscript on Windows and UNIX machines,
- > and pstopdf on Macs. If you don't want to use the "gs"
- > command on UNIX machines, you can choose the command you
- > do want to use. For example, the "epstopdf" command probably
- > works better with encapsulated PostScript files than does
- > the "gs" command. You can make that substitution in the
- > program.

>

- > A number of Coyote Graphics programs changed to accommodate
- > this new functionality. Among them are cgWindow, cgControl,
- > cgWindow_SetDefs, cgWindow_GetDefs, and PS_End. I wouldn't be
- > surprised if there were others as well.

>

- > You can find all of these changes in the latest Coyote Library
- > distribution:

>

- > http://www.idlcoyote.com/programs/zip_files/coyoteprograms.z ip
- Or, using Subversion at:

>

- > http://idl-coyote.googlecode.com/svn/tags/coyote/coyote_libr ary_1.4
- > > Cheers,
- >
- > David > --
- > David Fanning, Ph.D.
- > Fanning Software Consulting, Inc.
- > Coyote's Guide to IDL Programming:http://www.idlcoyote.com/
- > Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Subject: Re: Coyote Graphics Updates Posted by David Fanning on Tue, 13 Dec 2011 15:33:44 GMT View Forum Message <> Reply to Message

MariLiza writes:

- > Thanks David!!! :) Your hard work is truly appreciated!!!! All around
- > the World!!!
- > :-)
- > -MariLiza

Goodness! Coyote wants to know if you would be kind enough to send him your phone number. It's been a long time since he and I have seen so many exclamation marks! ;-)

Cheers,

David

David Fanning, Ph.D. Fanning Software Consulting, Inc. Coyote's Guide to IDL Programming: http://www.idlcoyote.com/ Sepore ma de ni thui. ("Perhaps thou speakest truth.")